

Bauer

RESUBMITTAL N.M. Oil Cons. DIV-Dist. 2
1301 W. Grand Avenue
Artesia, NM 88210

Form 3160-3
(April 2004)

0121

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires March 31, 2007

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER SECRETARY'S POTASH		5. Lease Serial No. NM-69369
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator Pogo Producing Company		7. If Unit or CA Agreement, Name and No.
3a. Address P.O. Box 10340, Midland, TX		8. Lease Name and Well No. Sundance 1 Federal #9
3b. Phone No. (include area code) 432-685-8100		9. API Well No. 30-015-33893
4. Location of Well (Report location clearly and in accordance with any State requirements.) At surface 660' FSL & 190' FWL At proposed prod. zone 1982'		10. Field and Pool, or Exploratory Mesa Verde Bone Spring
14. Distance in miles and direction from nearest town or post office* Approximately 30 miles East of Carlsbad NM		11. Sec., T. R. M. or Bk and Survey or Area Sec 1, T24S, R31E
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 660'	16. No. of acres in lease 640	12. County or Parish Eddy County
17. Spacing Unit dedicated to this well 40	18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 1320'	13. State NM
19. Proposed Depth 8650'	20. BLM/BIA Bond No. on file 29771	RECEIVED JAN 10 2005 CARLSBAD
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3554' GR	22. Approximate date work will start* When Approved	
23. Estimated duration		

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, shall be attached to this form:

- | | |
|---|--|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the authorized officer. |

25. Signature <i>Cathy Wright</i>	Name (Printed/Typed) Cathy Wright	Date 11/03/04
-----------------------------------	--------------------------------------	------------------

Title
Sr. Eng. Tech

Approved by (Signature) /s/ Linda S. C. Rundell	Name (Printed/Typed) /s/ Linda S. C. Rundell	Date 22 DEC 2004
Title STATE DIRECTOR	Office NM STATE OFFICE	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

APPROVAL FOR 1 YEAR

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on page 2)

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS
AND SPECIAL STIPULATIONS
ATTACHED

CARLSBAD CONTROLLED WATER BASIN

[Handwritten signature]

SUNDANCE 1 FEDERAL #9
Drilling Plan

1. Drill 25" hole to 40'. Set 40' of 20" conductor pipe and cmt to surface w/ Redi-mix.
2. Drill 17-1/2" hole to 850'. Run & set 850' of 13-3/8" 54.5# J-55 ST&C csg. Cmt w/ 900 sks Cl "C" cmt + 2% CaCl₂. Circ cmt to surface.
3. Drill 11" hole to 4450'. Run & set 4450' 8-5/8" 32# J-55 ST&C casing. Cmt w/ 1200 sks Cl "C" cmt + add. Circ cmt to surface.
4. Drill 7-7/8" hole to 8650'. Run & set 8650' of 5-1/2" csg as follows: 2650' 17# J-55 LT&C, 5000' 15.5# J-55 LT&C, 1000' 17# J-55 LT&C. Cmt in 3 stages w/ DV tools at 5800' & 3800' ±. Cmt 1st stage w/ 500 sks Cl "H" + add. Cmt 2nd stage w/ 300 sks Cl "C" + add. Cmt 3rd stage w/ 450 sks Cl "C" + add. Circ cmt to surface.

DISTRICT I
P.O. Box 1000, Hobbs, NM 88241-1000

DISTRICT II
P.O. Drawer 110, Artesia, NM 88211-0710

DISTRICT III
1000 Rio Brazos Ed., Artec, NM 87410

DISTRICT IV
P.O. BOX 2088, SANTA FE, N.M. 87504-2088

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-102
Revised February 10, 1994
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

WELL LOCATION AND ACREAGE DEDICATION PLAT

AMENDED REPORT

API Number	Pool Code	Pool Name
	96229	MESA VERDE - BONE SPRNG
Property Code	Property Name	Well Number
	SUNDANCE 1 FEDERAL	9
OGRID No.	Operator Name	Elevation
17891	POGO PRODUCING COMPANY	3554'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
N	1	24-S	31-E		660'	SOUTH	1980'	WEST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres	Joint or Infill	Consolidation Code	Order No.						
40									

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

LOT 4	LOT 3	LOT 2	LOT 1	<p>OPERATOR CERTIFICATION</p> <p>I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief.</p> <p><i>Joe T. Janica</i> Signature</p> <p>Joe T. Janica Printed Name</p> <p>Agent Title</p> <p>08/19/03 Date</p>
39.95 AC	39.96 AC	39.98 AC	39.99 AC	
<p>GEODETIC COORDINATES NAD 27 NME Y = 451858.6 N X = 685560.6 E LAT. 32°14'27.06"N LONG. 103°43'59.42"W</p>				
				<p>SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>July 29, 2003 Date Surveyed</p> <p><i>Ronald J. Edson</i> Signature & Seal of Professional Surveyor</p> <p>03-11-0802 Professional Surveyor</p> <p>Certification No. RONALD J. EDSON 3239 EARY EDSON 12641</p>

APPLICATION TO DRILL

POGO PRODUCING COMPANY
 SUNDANCE "1" FEDERAL # 9
 UNIT "N" SECTION 1
 T24S-R31E EDDY CO. NM

In response to questions asked under Section II of Bulletin NTL-6 the following information on the above well is provided for your consideration.

1. Location of well: 660' FSL & 1980' FWL SECTION 1 T24S-R31E EDDY CO. NM
2. Ground Elevation above Sea Level: 3554'
3. Geological age of surface formation: Quaternary Deposits:
4. Drilling tools and associated equipment: Conventional rotary drilling rig using drilling mud as a circulating medium to remove solids from hole.
5. Proposed drilling depth: 8650'
6. Estimated tops of geological markers:

Basal Anhydrite	4340'	Cherry Canyon	5443'
Delaware Lime	4580'	Brushy Canyon	6680'
Bell Canyon	4600'	Bone Spring	8410'

7. Possible mineral bearing formations:
 Bone Spring Oil

8. Casing Program:

Hole Size	Interval	OD of Casing	Weight	Thread	Collar	Grade
25"	0-40' ^{JSS} 1012-1020'	20"	NA	NA	NA	Conductor
17½"	0-850'	13 3/8"	48#	8-R	ST&C	H-40
11"	0-4450'	8 5/8"	32#	8-R	ST&C	J-55
7 7/8"	0-8650'	5½"	17 & 15.5	8-R	LT&C	J-55

APPLICATION TO DRILL

POGO PRODUCING COMPANY
 SUNDANCE "1" FEDERAL # 9
 UNIT "N" SECTION 1
 T24S-R31E EDDY CO. NM

9. CASING CEMENTING & SETTING DEPTH:

	20"	Conductor	Set 40' of 20" conductor and cement to surface with Redi-mix.
WITNESS	13 3/8"	Surface	Set 850' of 13 3/8" 48# H-40 ST&C casing. cement with 900 Sx. of Class "C" cement + additives, circulate cement to surface.
WITNESS	8 5/8"	Intermediate	Set 4450' of 8 5/8" 32# J-55 ST&C casing. Cement with 1200 Sx. of Class "C" cement + additives, circulate cement to surface.
	5 1/2"	Production	Set 8650' of 5 1/2" casing as follows: 2650' of 5 1/2" 17# J-55 LT&C, 5000' of 5 1/2" 15.5# J-55 LT&C, 1000' of 5 1/2" 17# J-55 LT&C casing. Cement in 3 stages DV Tools at 5800' & 3800'±. 1st stage cement with 500 Sx. of Class "H" + additives, 2nd stage cement with 300 Sx. of Class "C" + additives, 3rd stage cement with 450 Sx. of Class "C" + additives. Circulate cement to surface.

10. PRESSURE CONTROL EQUIPMENT: Exhibit "E" shows a 900 series 3000 PSI working perssure B.O.P. consisting of an annular bag type preventor, middle blind rams, and bottom pipe rams. The B.O.P. will be nipped up on the 13 3/8" casing and tested to API specifications. The B.O.P. will be operated at least once each 24 Hr. period and the blind rams will be operated when the drill pipe is out of on trips. Full opening stabbing valve and upper kelly cock will be available in case if needed. Exhibit "E-1" shows a hydraulically operated closing unit and a 3" 3000 PSI choke manifold with adjustable chokes. No abnormal pressures or temperatures are expected while drilling this well. No problems in offset wells.

11. PROPOSED MUD CIRCULATING SYSTEM:

DEPTH	MUD WT.	VISC.	FLUID LOSS	TYPE MUD SYSTEM
40-850'	8.4-8.7	29-32	NC	Fresh water spud mud add paper to control seepage.
850-4450'	10.0-10.2	29-38	NC	Brine water addpaper to control seepage, use high viscosity sweeps to clean hole.
4450-8650'	8.4-8.7	29-40	*	Fresh water system add Polymer to mud system if water loss control is desired. Use high vis- cosity sweeps to clean hole.

* If water loss control is required in order to log well, run DST's and run casing reduce water with a Polymer system.

Sufficient mud materials will be kept on location at all times in order to combat lost circulation, or unexpected kicks. In order to run DST's, open hole logs, and casing, viscosity, and water loss may have to be adjusted to meet these needs.

APPLICATION TO DRILL

POGO PRODUCING COMPANY
SUNDANCE "1" FEDERAL # 9
UNIT "N" SECTION 1
T24S-R31E EDDY CO. NM

12. LOGGING, CORING, AND TESTING PROGRAM:

- A. Open hole logs: Run Dual Induction, SNP, LDT, CNL, Gamma Ray Caliper from TD back to 8 5/8" casing shoe. Run Cased Hole Gamma Ray, Neutron from 8 5/8" casing shoe back to surface.
- B. Mud logger may be rigged up on hole at 4450' and remain on hole to TD.
- C. No DST's or cores are planned at this time.

13. POTENTIAL HAZARDS:

No abnormal pressures or temperatures are expected. There is no known presence of H²S in this area. If H²S is encountered the operator will comply with the provisions of Onshore Oil and Gas Order No. 6. No lost circulation is expected to occur. All personnel will be familiar with all aspects of safe operation of equipment being used to drill this well. Estimated BHP 4250 PSI, and Estimated BHT 180°.

14. ANTICIPATED STARTING DATE AND DURATION OF OPERATION:

Road and location construction will begin after the BLM has approved the APD. Anticipated spud date will be as soon after BLM approval and as soon as a rig will be available. Move in operation and drilling is expected to take 30 days. If production casing is run then an additional 30 days will be needed to complete well and construct surface facilities and/or lay flowlines in order to place well on production.

15. OTHER FACETS OF OPERATIONS:

After running casing, cased hole Gamma Ray, Neutron Collar logs will be run from TD back to all possible productive zones. The Bone Springs formation will be perforated and stimulated in order to establish production. The well will be swab tested and potentialized as an oil well.

H₂S GEN SULFIDE DRILLING OPERATIO PLAN

1. All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:
 - A. Characteristics of H₂S
 - B. Physical effects and hazards
 - C. Proper use of safety equipment and life support systems.
 - D. Principle and operation of H₂S detectors, warning system and briefing areas.
 - E. Evacuation procedure, routes and first aid.
 - F. Proper use of 30 minute pressure demand air pack.
2. H₂S Detection and Alarm Systems
 - A. H₂S detectors and audio alarm system to be located at bell nipple, end of blowie line (mud pit) and on derrick floor or doghouse.
3. Windssock and/or wind streamers
 - A. Windssock at mudpit area should be high enough to be visible.
 - B. Windssock at briefing area should be high enough to be visible.
 - C. There should be a windssock at entrance to location.
4. Condition Flags and Signs
 - A. Warning sign on access road to location.
 - B. Flags to be displayed on sign at entrance to location. Green flag, normal safe condition. Yellow flag indicates potential pressure and danger. Red flag, danger, H₂S present in dangerous concentration. Only emergency personnel admitted to location.
5. Well control equipment
 - A. See exhibit "E" & "E-1"
6. Communication
 - A. While working under masks chalkboards will be used for communication.
 - B. Hand signals will be used where chalk board is inappropriate.
 - C. Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephoned will be available at most drilling foreman's trailer or living quarters.
7. Drillstem Testing
 - A. Exhausts will be watered.
 - B. Flare line will be equipped with an electric ignitor or a propane pilot light in case gas reaches the surface.
 - C. If the location is near to a dwelling a closed DST will be performed.

8. Drilling contractor supervisor will be required to be familiar with the effects H₂S has on tubular goods and other mechanical equipment.
9. If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

SURFACE USE PLAN

POGO PRODUCING COMPANY
SUNDANCE "1" FEDERAL # 9
UNIT "N" SECTION 1
T24S-R31E EDDY CO. NM

1. EXISTING ROADS: Area maps, Exhibit "B" is a reproduction of a County General Hi-way Map. Exhibit "C" is a reproduction of a USGS Topographic map, showing existing and proposed roads. All existing roads will be maintained in a condition equal to or better than current conditions. Any new roads will be constructed to BLM specifications.
 - A. Exhibit "A" shows the location of the proposed well site as staked.
 - B. From Hobbs New Mexico take U.S. Hi-way West toward Carlsbad New Mexico go 38 miles to CO-29, turn South go 21.5 miles to State Hi-way 128 turn Left (South-East) on State Hi-way 128, go .8 miles, turn Right (South) follow lease road .900'± to Pogo well # -2-turn Left (South) go 1250' to location.
 - C. Exhibit "F" shows where flowlines and powerlines may be constructed to produce this lease.
2. PLANNED ACCESS ROADS: Approximately 1250' of new road will be constructed.
 - A. The access road will be crowned and ditched to a 12' wide traveled surface with a 40' Right-of-Way.
 - B. Gradient on all roads will be less than 5% if possible.
 - C. Turn-outs will be constructed where necessary.
 - D. If needed the roads will be surfaced to the BLM requirements with material obtained from a local source.
 - E. Center line for the new access road will be flagged.
 - F. The road will be constructed to utilize low water crossings where drainage currently exist, and Culverts will be installed where necessary.
3. EXHIBIT "A-1" SHOWS WELLS AND DRY HOLES WITHIN A 1 MILE RADIUS.
 - A. Water wells - None known
 - B. Disposal wells - None known
 - C. Drilling wells - None known
 - D. Producing wells - As shown on Exhibit "A-1"
 - E. Abandoned wells - As shown on Exhibit "A-1"

SURFACE USE PLAN

POGO PRODUCING COMPANY
SUNDANCE "1" FEDERAL # 9
UNIT "N" SECTION 1
T24S-R31E EDDY CO. NM

4. If on completion this well is a producer the operator will lay pipelines and construct powerlines along existing road R-O-W's or other existing R-O-W's. Possible routes of pipelines, flowlines and powerlines are shown on Exhibit "F".

5. LOCATION AND TYPE OF WATER SUPPLY:

Water will be purchased locally from a commercial source and trucked over the access roads or piped to location in flexible lines laid on top of the ground.

6. SOURCE OF CONSTRUCTION MATERIAL:

If possible construction material will be obtained from the excavation of drill site if additional material is needed it will be obtained from a local source and transported over the access roads as shown on Exhibit "C".

7. METHODS OF HANDLING WASTE MATERIAL:

- A. Drill cuttings will be disposed of in the reserve pits.
- B. All trash, junk and other waste material will be contained in trash cages or trash bins to prevent scattering. When the job is completed all contents will be removed and disposed of in a approved sanitary land fill.
- C. Salts remaining after completion of well will be picked up by the supplier, including broken sacks.
- D. Waste water from living quarters will be drained into holes with a minium of 10'. These holes will be covered during drilling and will be back filled when the well is completed. A Porto-John will be provided for the rig crews. This equipment will be properly maintained during the drilling and completion operation and will be removed when all operations are complete.
- E. Remaining drilling fluids will be allowed to evaporate in the reserve pits until the pits are dry enough to be broken out for furthed drying. If the drilling fluids do not evaporate in a reasonable time they will be hauled off by transports to a state approve disposal site. Later pips will be broken out to speed drying. Water produced during completion will be put in reserve pits. Oil and condensate produced will be put in storage tanks and sold.

8. ANCILLARY FACILITIES:

- A. No camps or air strips will be constructed on location.

SURFACE USE PLAN

POGO PRODUCING COMPANY
SUNDANCE "1" FEDERAL # 9
UNIT "N" SECTION 1
T24S-R31E EDDY CO. NM

7. WELL SITE LAYOUT

- A. Exhibit "D" shows the proposed well site layout.
- B. This exhibit indicated proposed location of reserve and sump pits and living facilities.
- C. Mud pits in the active circulating system will be steel pits & the reserve pit is proposed to be unlined unless subsurface condition encountered during pit construction indicate that lining is needed for lateral containment of fluids.
- D. If needed, the reserve pit is to be lined with polyethelene. The pit liner will be 6 mils thick. Pit liner will extend a minimum 2'00" over the reserve pits dikes where the liner will be anchored down.
- E. The reserve pit will be fenced on three sides with four strands of barbed wire during drilling and completion phases. The fourth side will be fenced after all drilling operations have ceased. If the well is a producer, the reserve pit fence will be torn down. The reserve pit and those areas of the location not essential to production facilities will be reclaimed and seeded per BLM requirements.

10. PLANS FOR RESTORATION OF SURFACE

Rehabilitation of the location and reserve pit will start in a timely manner after all drilling operations cease. The type of reclamation will depend on whether the well is a producer or a dry hole.

However, in either event, the reserve pit will be allowed to dry properly, and fluid removed and disposed of in accordance with Article 7.B as previously noted. The pit area will then be leveled and contoured to conform to the original and surrounding area. Drainage systems, if any, will be reshaped to the original configuration with provisions made to alleviate erosion. These may need to be modified in certain circumstances to prevent inundation of the location's pad and surface facilities. After the area has been shaped and contoured, topsoil from the spoil pile will be placed over the disturbed area to the extent possible. Revegetation procedures will comply with BLM standards.

If the well is a dry hole, the pad and road area will be contoured to match the existing terrain. Topsoil will be spread to the extent possible. Revegetation will comply with BLM standards.

Should the well be a producer, the previously noted procedures will apply to those areas which are not required for production facilities.

SURFACE USE PLAN

POGO PRODUCING COMPANY
SUNDANCE "1" FEDERAL # 9
UNIT "N" SECTION 1
T24S-R31E EDDY CO. NM

11. OTHER INFORMATION:

- A. Topography consists of low lying sand dunes with a slight dip to the West. The deep sandy soil supports shinnery oak, native grasses, and an occasional mesquite tree.
- B. The surface is owned by The U.S. Department of Interior and is administered by The Bureau of Land Management. The surface is used for the grazing of livestock and the production of Oil & Gas.
- C. An archaeological survey has been done and is on file in the Carlsbad Field Office of The Bureau of Land Management.
- D. There are no dwellings in the near vicinity of this location.

12. OPERATIOR'S REPRESENTIVES:

Before Construction:


TIERRA EXPLORATION, INC.
P.O. BOX 2188
HOBBS, NEW MEXICO 88241
OFFICE Ph. 505-391-8503
JOE T. JANICA

During and after Construction:

POGO PRODUCING COMPANY
P.O. BOX 10340
MIDLAND, TEXAS 79702-7340
RICHARD WRIGHT
OFFICE Ph. 432-685-8140.

13. CERTIFICATION: I hereby certify that I, or persons under my direct supervision have inspected the proposed drill site and the access roads, and that I am familiar with the conditions which currently exist, that the statements made in this plan are to the best of my knowledge are true and correct, and that the work associated with the operations proposed herein will be performed by POGO PRODUCING COMPANY it's contractors/subcontractors is in confirmity with this plan and the terms and conditions under which it is approved. This statement is subject to the provision of U.S.C. 1001 for the filing of a false report.


NAME : Joe T Janica
DATE : 08/19/03
TITLE : Agent



- Wind Direction Indicators (wind sock or streamers)
- △ H2S Monitors (alarms at bell nipple and shale shaker)
- Briefing Areas
- Remote EOP Closing Unit
- Sign and Condition Flags

EXHIBIT "D"
RIG LAY OUT PLAT

POGO PRODUCING COMPANY
SUNDANCE "1" FEDERAL # 9
UNIT "N" SECTION 1
T24S-R31E EDDY CO. NM




ARRANGEMENT SRRA

900 Series
3000 PSI WP

EXHIBIT "E"
SKETCH OF B.O.P. TO BE USED ON

POGO PRODUCING COMPANY
SUNDANCE "1" FEDERAL # 9
UNIT "N" SECTION 1
T24S-R31E EDDY CO. NM



Typical choke manifold assembly for 3M WP system




EXHIBIT "E-1"
CHOKE MANIFOLD & CLOSING UNIT

POGO PRODUCING COMPANY
SUNDANCE "1" FEDERAL # 9
UNIT "N" SECTION 1
T24S-R31E EDDY CO. NM




EXHIBIT "C"
 TOPOGRAPHIC MAP SHOWING
 ROADS & DIRECTIONS TO

POGO PRODUCING COMPANY
 SUNDANCE "1" FEDERAL # 9
 UNIT "N" SECTION 1