mit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised March 25, 1999

OIL CONSERVATION DIVISION

DISTRICT I 2040 South Pacheco WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 30-005-63719 Santa Fe, New Mexico 87505 5. Indicate Type of Lease DISTRICT II FEE STATE X 811 S. First Street, Artesia, NM 88210 6. State Oil & Gas Lease No. DISTRICT III VA-2011 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) MAR 0 1 7005 GAS OIL CONTROL Z-28 State Unit X WELL WELL OTHER R Well No Name of Operator **ELK OIL COMPANY** 9. Pool Name or Wildcat 3. Address of Operator POST OFFICE BOX 310, ROSWELL, NEW MEXICO 88202-0310 Comanche Spring Pre-Permian 4. Well Location 660 660 West Feet From The South Feet From The Section 10 South Range 26 East NMPM Chaves County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3710' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING CHANGE PLANS COMMENCE DRILLING OPNS. TEMPORARILY ABANDON PLUG AND ABANDONMENT MULTIPLE COMPLETION PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER: Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103 For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Spud well on February 22, 2005. Drilled 17 1/4" hole to 380'. Ran 10 Joints (380') of 11 3/4" 42#, H-40 Casing. Cemented with 330 sxs Premium Plus with 2% CaCl2. Plug down at 8:00 P.M. on 02/22/05. Circulated 75 sxs. WOC 18 hours. Tested to 1000# for 30 minutes, test okay. Resume drilling a 12 1/4" hole. Drilled hole to 1218'. Ran 29 Joint (1220') of 8 5/8", 24# Casing. Cemented with 200 sxs Interfill C and tailed by 200 sxs Premium Plus with 2% CaCl2. Plug down at 10:00 A.M. on 02/25/05. Circulated 75 sxs. WOC 18 hours. Tested to 1000# for 30 minutes, test okay. Resume drilling a 7 7/8" hole. I hereby certify that the information above is true and samplete to the best of my knowledge and belief. SIGNATURE PRESIDENT 02/28/05 TITLE

(This space for State Use)

TYPE OR PRINT

FOR RECORDS ONLY

JOSEPÍI J. KELLY

TELEPHONE NO

505-623-3190

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: