Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103
District I	Energy, Minerals and Natural Resources		June 19, 2008 WELL API NO.
1625 N. French Dr , Hobbs, NM 88240 District II	ON CONGERNATION DRUGION		30-015-38189
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		5. Indicate Type of Lease
District III 1000 Rio Brazos Rd, Aztec, NM 87410	1220 South St. Fran		STATE 🛛 ~ FEE 🗌
District IV 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87	303	6. State Oil & Gas Lease No.
87505	ICEC AND DEPORTS ON WELLS		7. Lease Name on Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPC	NOTICES AND REPORTS ON WELLS PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		7. Lease Name or Unit Agreement Name AID 24 STATE
1. Type of Well: Oil Well	Gas Well Other		8. Well Number #10
2. Name of Operator	~		9. OGRID Number 255333
LIME ROCK RESOURCES A,	L.P.		10. Pool name or Wildcat:
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sul	livan, Farmington, NM 87401		Empire, Glorieta-Yeso (96210)
4. Well Location			
Unit Letter O: 890 feet from the SOUTH line and 1630 feet from the EAST line			
Section 24 Township 17-S Range 28-E NMPM Eddy County			
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3684' GL			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
	ITENTION TO:		SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON CHANGE PLANS	REMEDIAL WORK COMMENCE DRIL	_
TEMPORARILY ABANDON DULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	
DOWNHOLE COMMINGLE		O/IOINO/OLIMEIN	
OTHER:	П	OTHER: Spud	& Surface & Production Casings
	pleted operations. (Clearly state all p		give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
<u>Spud well on 5/12/11</u> . Drilled 12-1/4" hole to 464'. Landed 8-5/8" 24# J-55 csg @ 447'. Cmted lead #1 w/100 sx (163 cf) Thixotropic "C" cmt w/10# kol seal, 0.125# PE flake, 10# gilsonite, & 1% Cacl2 & lead #2 w/275 sx (371 cf) "C" cmt w/2% Cacl2, & 1/8#/sx pe-			
flake. Tailed w/200 sx (264 cf) "C" cmt w/2% Cacl2. Did not circ cmt to surface. Tagged TOC @ 86' & topped off w/redi-mix to surface. On 5/13/11, PT 8-5/8" csg to 600 psi for 30 min – OK.			
Drilled 7-7/8" hole to TD5261' on 5/25/11. Ran open hole logs. Landed 5-1/2" 17# J-55 csg @ 5245'. Cmted lead w/550 sx (1045 cf) 35/65 poz C cmt w/0.125#/sx pe-flake, 3#/sx salt, 0.5% Halad-9, & 3#/sx gilsonite. Tailed w/650 sx (865 cf) "C" cmt w/0.125#/sx p-e-flake, 0.4% Lap-1, 0.5% CFR-3, & ½#/sx D-air. Circ 99 sx cmt to pit. Released drilling rig on 5/26/11. Plan to pressure test the 5-1/2"			
csg before completion operations.			
Spud Date: 5/12/11		Release Date:	5/26/11
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
signature Make	Teppin TITLE Petrolo	eum Engineer - Age	<u>nt</u> DATE <u>6/15/11</u>
Type or print name Mike Pippin	E-mail address:	mike@pippinll	c.com PHONE: _505-327-4573
For State Use Only Field Supervisor			
APPROVED BY: DOUGLE SUpervisor DATE 6-20-)1 Conditions of Approval (if any):			

