

Submit 1 Copy To Appropriate District
Office
District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-37462

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Chevron BOT

8. Well Number
1H

9. OGRID Number
025575

10. Pool name or Wildcat
Cedar Canyon; Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location

Surface Lot 4 : 660 feet from the North line and 330 feet from the West line
BHL Lot 2 : 660 feet from the North line and 1650 feet from the East line
Section 5 Township 24S Range 29E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
2953'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Surface and intermediate casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/16/11 - Resumed drilling at 11:45 AM.


6/17/11 - TD 17-1/2" hole to 580' at 6:15 AM. Set 13-3/8" 48# J-55 ST&C casing at 580'. Cemented with 310 sx Class "C" + 0.125#/sx D130 + 4% D20 + 94#/sx D903 + 2% S1 + 0.2% D46 (yld 1.97, wt 12.9). Tailed in with 200 sx Class "C" + 0.125#/sx D130 + 94#/sx D903 (yld 1.34, wt 14.8). Circulated 13 sx to pit. Tested casing to 600 psi with no pressure loss. WOC 22 hrs 30 min. Reduced hole to 12-1/4" and resumed drilling.

6/20/11 - TD 12-1/4" hole to 3430' at 1:05 PM. Set 9-5/8" 36#, 40# J-55 K-55 LT&C casing at 3430'. Cemented with 625 sx 35:65 Poz "C" + 6% D020 + 5% D044 + 0.2% D046 + 0.125#/sx D130 + 28#/sx D132 + 61#/sx D903 (yld 2.06, wt 12.6). Tailed in with 200 sx Class "C" + 0.2% D013 + 94#/sx D903 (yld 1.33, wt 14.8). Circulated 68 sx to half round. Tested casing to 1000 psi for 30 min with no pressure loss. Redi-mix casing with 4 yds, cement fell back to 35'. WOC 30 hrs 45 min. Reduced hole to 8-3/4" and resumed drilling.

Spud Date:

4/23/11

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE June 23, 2011

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: Donald May TITLE Field Supervisor DATE 7-15-11

Conditions of Approval (if any):