

Submit 3 Copies To Appropriate District Office  
 District I  
 1625 N French Dr., Hobbs, NM 88240  
 District II  
 1301 W Grand Ave., Artesia, NM 88210  
 District III  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 June 19, 2008

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO. 30-015-38189
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name AID 24 STATE
8. Well Number #10
9. OGRID Number 255333
10. Pool name or Wildcat: Empire, Glorieta-Yeso (96210)

SUNDRY NOTICES AND REPORTS ON WELLS  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)


1. Type of Well: Oil Well  Gas Well  Other

2. Name of Operator  
LIME ROCK RESOURCES A, L.P.

3. Address of Operator  
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location  
 Unit Letter O : 890 feet from the SOUTH line and 1630 feet from the EAST line  
 Section 24 Township 17-S Range 28-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3684' GL



12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK  PLUG AND ABANDON   
 TEMPORARILY ABANDON  CHANGE PLANS   
 PULL OR ALTER CASING  MULTIPLE COMPL   
 DOWNHOLE COMMINGLE

SUBSEQUENT REPORT OF:

- REMEDIAL WORK  ALTERING CASING   
 COMMENCE DRILLING OPNS.  P AND A   
 CASING/CEMENT JOB

OTHER:

OTHER: Completion

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 6/19/11, PT 5-1/2" csg to 5000 psi for 30 min-OK. Perfed lower Yeso @ 4819'-20', 4834'-36', 4865'-67', 4883'-84', 4894'-95', 4914'-15', 4940'-41', 4959'-60', 4964'-65', 4971'-72', 5010'-11', 5014'-15', 5030'-31', 5066'-68', 5084'-85', 5102'-03', 5119'-21', 5158'-59' w/2-0.42" spf. Total 44 holes. Treated w/4998 gal 15% NEFE acid & 88 perf balls. On 6/24/11, fraced lower Yeso w/116,120# 16/30 Ottawa & 28,770# 16/30 siber prop sand in 20# X-linked gel.  
 Set 5-1/2" CBP @ 4801'. PT csg & CBP to 4000 psi for 30 min-OK. Perfed middle Yeso @ 4538'-39', 4551'-52', 4557'-58', 4563'-64', 4573'-74', 4585'-86', 4598'-99', 4604'-06', 4620'-21', 4658'-59', 4679'-80', 4682'-83', 4733'-35', 4762'-63', 4770'-72' w/2-0.42" spf. Total 36 holes. Treated perfs w/4998 gal 15% NEFE acid & 72 perf balls. Fraced w/99,922# 16/30 Ottawa & 28,861# siber prop 16/30 sand in 20# X-linked gel.  
 Set 5-1/2" CBP @ 4516'. PT csg to 4000 psi for 30 min-OK. Perfed upper Yeso @ 4212'-15', 4242'-43', 4257'-58', 4279'-80', 4334'-35', 4346'-47', 4357'-58', 4366'-68', 4380'-81', 4402'-03', 4426'-27', 4432'-33'-4446'-48', 4464'-65', 4484'-86', 4493'-94', w/2-0.42" spf. Total 42 holes. Treated perfs w/5000 gal 15% NEFE acid & 84 perf balls. Fraced w/117,091# 16/30 Ottawa & 40,853# 16/30 siber prop sand in 20# X-linked gel.  
 On 6/27/11, MIRUSU. Drilled CBPs @ 4516' & 4801' & CO to PBTD5200'. On 6/28/11, landed 2-7/8" 6.5# J-55 tbg @ 5102'. Ran pump & rods. Released completion rig on 6/29/11.

Spud Date: 5/12/11 Drilling Rig Release Date: 5/26/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 6/29/11

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 7-18-11

Conditions of Approval (if any):