

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-38596
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-5009
7. Lease Name or Unit Agreement Name <i>Carrington State</i>
8. Well Number 4
9. OGRID Number 155615
10. Pool name or Wildcat Empire Glorieta-Yeso

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>
2. Name of Operator Nadel and Gussman Permian, L.L.C.
3. Address of Operator 601 N. Marienfeld #508 Midland, Texas 79701
4. Well Location Unit Letter <u>O</u> : 330 feet from the South line and 1650 feet from the East line Section <u>12</u> Township <u>17S</u> Range <u>28E</u> NMPM County <u>Eddy</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3719' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6-19-11 TD 7-7/8" production hole at 5,400'

Casing: Run 125 joints + 1 marker joint of 5 1/2" 17#/J-55 casing and set at 5,350'.


Cement: Lead: 725 sacks of 50/50/10 Class "C" + 10% Gel + 0.3 % FL-10 + 5% Salt + 0.25% R-38
Properties: 11.9 lb/gal, 2.37 ft³/sk, 13.52 gal/sk.

Tail: 400 sacks of Starbond "C" + 0.3% FL-10 + 0.1% C-20 + 0.25% R-38
Properties: 13.2 lb/gal, 1.55 ft³/sk, 7.86 gal/sk.

Circulate 102 sacks to pit.

Spud Date: 6-11-11

Rig Release Date: 6-20-11



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *J. Goss* TITLE Drilling Engineer DATE 6-27-11

Type or print name Jason Goss E-mail address: jgoss@naguss.com PHONE: 432-682-4429
For State Use Only

APPROVED BY: *David May* TITLE Field Supervisor DATE 7-11-11

Conditions of Approval (if any):