UNITEDSTATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FORMAPPROVED OM B No 1004-0137 Expires March 31, 2007

5 Lease Serial No NM 031383

	KELOKIO OM METER	ויין	M 031383	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.		r an (6.1	6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other	r instructions on reverse	SIUE.	If Unit or CA/Agreement, Name and/or No MNM 71016	
I Type of Well OilWell GasWell Other		ļ	8 Well Name and No	
2 NameofOperator BOPCO, L.P.		Р	oker Lake Unit #67; 306402	
3a Address 3b PhoneNo (include area code)		a code) 3	0-015-25263	
P O Box 2760 Midland Tx 79702 (432)683-2277			Field and Pool, or Exploratory Area	
4 Location of Well (Footage, Sec., T, R, M, or Survey Description) ULK, 1980' FSL 1980' FWL Sec. 3; T-25S; R31E		C	otton Draw; Atoka, South	
		E	County or Parish, State ddy M	
12. CHECK APPROPRIATEBOX(ES)TO INDICATE NATURE	OF NOTICE, REPO	ORT, OR OTHER DATA	
TYPE OF SUBMISSION	ТҮРЕС	F ACTION		
X Acidize		Production (Start/Re	esume) Water Shut-Off	
Notice of Intent Alter Casing	X Fracture Treat	Reclamation	Well Integrity	
X Subsequent Report Casing Repair	New Construction	Recomplete	X OtherPlug-back from	
Final Abandonment Notice Convert to Invest	Plug and Abandon	∐ Temporarīly Abando ¬	on Morrow to	
Final Abandonment Notice Convert to Inject	ction X Plug Back	☐ Water Disposal	Atoka South	
Morrow perfs @ 15,032 - 15,048 were pro	aviously bludged off w/ber	nanent, 6-1/4" b		
Atoka South was perf'd @ 14,320 - 14,34	ff w/permanent 6-1/4" bridg			
Atoka South was perf'd @ 14,320 - 14,341 1/5/10: MIRU Lucky Loaded casing 265 1/6/10. Finished displacing hole w/600 b/1/7/10: Set 7" CIBP @ 14,525'. Capped 1/8/10. Replaced csg valves. Pressured 1/9 - 1/11/10: SD due to weather. 1/12/10: RIH w/tubing assembly. 1/13/10: RU Weatherford, ran depth con 1/14/10: Perforate 14,320 - 14,340', 6 sp 1/15/10: Well static upon arrival. Recover	ff w/permanent 6-1/4" bridg 40'. Plugback operations a 5 bbls. 3% KCL fluid. bls fluid Released packer CIBP w/ 10 sxs CI H ceme I up on casing to 5,000 # - utrol log. Displaced hole was 6 60 deg. ered 42 bbls water Small	re as follows: ent (35' fill). TOO tested good. 850 bbls 3% KC tail gas blow on	5 w/ 10 sxs cmt (35') on top. The CONFIDE C @ 14,490'. L fluid. final swab runs. SWI SD	
Atoka South was perf'd @ 14,320 - 14,34 1/5/10: MIRU Lucky Loaded casing 265 1/6/10. Finished displacing hole w/600 b/ 1/7/10: Set 7" CIBP @ 14,525'. Capped 1/8/10. Replaced csg valves. Pressured 1/9 - 1/11/10: SD due to weather. 1/12/10: RIH w/tubing assembly. 1/13/10: RU Weatherford, ran depth con 1/14/10: Perforate 14,320 - 14,340', 6 sp 1/15/10: Well static upon arrival. Recove 1/16/10 SITP 350 psi. RU HES to acidis	ff w/permanent 6-1/4" bridg 10'. Plugback operations a 5 bbls. 3% KCL fluid. bls fluid Released packer CIBP w/ 10 sxs CI H ceme I up on casing to 5,000 # - utrol log. Displaced hole was of 60 deg. ered 42 bbls water Small ze Atoka perfs 14,320' - 14	re as follows: ent (35' fill). TOO tested good. 850 bbls 3% KC tail gas blow on	5 w/ 10 sxs cmt (35') on top. The CONFIDE Confidence of the CONFIDE Confidence of the Confidence of th	
Atoka South was perf'd @ 14,320 - 14,340 1/5/10: MIRU Lucky Loaded casing 265 1/6/10. Finished displacing hole w/600 bl 1/7/10: Set 7" CIBP @ 14,525'. Capped 1/8/10. Replaced csg valves. Pressured 1/9 - 1/11/10: SD due to weather. 1/12/10: RIH w/tubing assembly. 1/13/10: RU Weatherford, ran depth con 1/14/10: Perforate 14,320 - 14,340', 6 sp 1/15/10: Well static upon arrival. Recove 1/16/10: SITP 350 psi. RU HES to acidiz 14: Thereby certify that the foregoing is true and correct Name (Printed/Typed)	ff w/permanent 6-1/4" bridg 10'. Plugback operations a 5 bbls. 3% KCL fluid. bls fluid Released packer CIBP w/ 10 sxs CI H ceme I up on casing to 5,000 # - utrol log. Displaced hole was of 60 deg. ered 42 bbls water Small ze Atoka perfs 14,320' - 14	re as follows: ent (35' fill). TO(tested good. 850 bbls 3% KC tail gas blow on 1,340'. Acidized	5 w/ 10 sxs cmt (35') on top. The CONFIDE C @ 14,490'. L fluid. final swab runs. SWI SD	
Atoka South was perf'd @ 14,320 - 14,34 1/5/10: MIRU Lucky Loaded casing 265 1/6/10. Finished displacing hole w/600 b/ 1/7/10: Set 7" CIBP @ 14,525'. Capped 1/8/10. Replaced csg valves. Pressured 1/9 - 1/11/10: SD due to weather. 1/12/10: RIH w/tubing assembly. 1/13/10: RU Weatherford, ran depth con 1/14/10: Perforate 14,320 - 14,340', 6 sp 1/15/10: Well static upon arrival. Recove 1/16/10: SITP 350 psi. RU HES to acidi: 14 Thereby certify that the foregoing is true and correct Name (Printed/Typed) Sandra J Belt ext. 149	ff w/permanent 6-1/4" bridg 10'. Plugback operations a 5 bbls. 3% KCL fluid. bls fluid. Released packer CIBP w/ 10 sxs CI H cemel up on casing to 5,000 # - a bridge 10 bls water Small ze Atoka perfs 14,320' - 14 cemel 14.	re as follows: ent (35' fill). TOO tested good. 850 bbls 3% KC tail gas blow on	5 w/ 10 sxs cmt (35') on top. The CONFIDION CO	
Atoka South was perf'd @ 14,320 - 14,340 1/5/10: MIRU Lucky Loaded casing 265 1/6/10. Finished displacing hole w/600 b/ 1/7/10: Set 7" CIBP @ 14,525'. Capped 1/8/10. Replaced csg valves. Pressured 1/9 - 1/11/10: SD due to weather. 1/12/10: RIH w/tubing assembly. 1/13/10: RU Weatherford, ran depth con 1/14/10: Perforate 14,320 - 14,340', 6 sp 1/15/10: Well static upon arrival. Recove 1/16/10 SITP 350 psi. RU HES to acidi: 14	ff w/permanent 6-1/4" bridged. Plugback operations a bbls. 3% KCL fluid. bls fluid. Released packer CIBP w/ 10 sxs CI H cemel up on casing to 5,000 # - a bridged by the complete of 60 deg. ered 42 bbls water Small ze Atoka perfs 14,320' - 14 cemel a bridged.	re as follows: ent (35' fill). TOO tested good. 850 bbls 3% KC tail gas blow on 340'. Acidized egulatory Clerk	CONFIDE CONFID	
Atoka South was perf'd @ 14,320 - 14,34 1/5/10: MIRU Lucky Loaded casing 265 1/6/10. Finished displacing hole w/600 b/ 1/7/10: Set 7" CIBP @ 14,525'. Capped 1/8/10. Replaced csg valves. Pressured 1/9 - 1/11/10: SD due to weather. 1/12/10: RIH w/tubing assembly. 1/13/10: RU Weatherford, ran depth con 1/14/10: Perforate 14,320 - 14,340', 6 sp 1/15/10: Well static upon arrival. Recove 1/16/10: SITP 350 psi. RU HES to acidi: 14	ff w/permanent 6-1/4" bridg 10'. Plugback operations a 5 bbls. 3% KCL fluid. bls fluid. Released packer CIBP w/ 10 sxs CI H cemer I up on casing to 5,000 # - 1 btrol log. Displaced hole w/of 60 deg. ered 42 bbls water Small ze Atoka perfs 14,320' - 14 ct Title Research	re as follows: ent (35' fill). TOO tested good. 850 bbls 3% KC tail gas blow on 1,340'. Acidized egulatory Clerk 1/05/2010 TE OFFICE US	C@ 14,490'. C@ 14,490'. Confidence of the conf	

Attachment to Form 3160-5 Sundry Notice Poker Lake Unit #67 Item 13 3/5/10

1/16/10 (cont.)

Displaced to bottom perf w/57 bbls 3% KCL mixed w/ HES gas

perm & Cla Sta

1/17/10 - 1/18/10:

Repairing separator and dump valve.

1/19/10:

Moved in completion equipment. RU Fesco.

1/20/10 - 1/24/10:

Loading hole w/packer fluid, pressure testing and getting ready to

frac.

1/25/10:

Shut down.

1/26/10:

Testing frac equipment.

1/27/10

RU Schlumberger. Frac Atoka perfs 14,320 - 14,340 w/3,738

gals WF30 prepad, 41,268 gals YF130 RGD and 45,495 lbs

20/40 Bauxite. RD Schlumberger

1/28/10:

Flow test.

1/29/10:

RU Fesco. Set 2-3/8" CIBP @ 14,250. Test CIBP to 5,000 psi

1/30/10 - 1/31/10:

Set CIBP @ 14,260 CIBP is leaking.

RU Fesco. Plug valve on frac stack leaking. Made repairs.

Knocked out plug.

2/1/10:

Well shut-in.

2/2/10:

Laid down tubing

2/3/10 - 2/6/10:

Installation of production facilities.

2/7/10:

Shut down.

2/8/10 - 2/9/10:

Continue w/installation of production facilities.

2/10/10

Finished installing & hydrotesting production equipment.

Preheating heater.

2/11/10:

Flow testing into sales. SITP 8350, 4636 MCFD: 140 bbls water

on 10/64 choke. Well on production.