01110 Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OMB NO. 1004-0135

Expires: July 31, 2010

6. If Indian, Allottee or Tribe Name

Lease Serial No. NMLC029395A

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well . Use form 3160-3 (APD) for such proposals

If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on reverse side. Type of Well Well Name and No TURNER "A" 11 Oil Well Gas Well M Other INJECTION

2. Name of Operator Contact NANCY FITZWATER LINN OPERATING INC E-Mail: nfitzwater@linnenergy.com			30	9. API Well No 30-015-05215	
600 TRAVIS, STE 5100		3b Phone No. (include area code Ph: 281-840-4266 Fx: 281-840-4006		10 Field and Pool, or Exploratory GRAYBURG JACKSON	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, and State	
Sec 19 T17S R31E 975FNL 1450FWL				EDDY COUNTY COUNTY, NM	
· · · · · · · · · · · · · · · · · · ·					
12. CHECK APPR	ROPRIATE BOX(ES) TO	INDICATE NATURE OF I	NOTICE, REPORT	Γ, OR OTHER	R DATA
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	☐ Acidize	□ Deepen	Production (Start/Resume)		☐ Water Shut-Off
_	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation		☐ Well Integrity
Subsequent Report	Casing Repair	☐ New Construction	☐ Temporarily Abandon ☐ Water Disposal		□ Other
Final Abandonment Notice	Change Plans	Plug and Abandon			
	Convert to Injection	☐ Plug Back			
13. Describe Proposed or Completed Op If the proposal is to deepen direction. Attach the Bond under which the wor following completion of the involved testing has been completed. Final Al determined that the site is ready for f	ally or recomplete horizontally, rk will be performed or provide I operations. If the operation respondented by file	give subsurface locations and meas the Bond No on file with BLM/BI sults in a multiple completion or rec	ured and true vertical d A Required subsequer completion in a new int ding reclamation, have	depths of all perting the reports shall be derival, a Form 310 been completed,	nent markers and zones e filed within 30 days 60-4 shall be filed once and the operator has
Redelivery Sundry:				epted for re NMO CD	^
6-7-11 - RTI @ 150 BWPD w/	1300 PSI injection pressui	re.		7/2	Tu
6-3-11 Pumped 4000 gals 15% 6-1-11 Begin flowback	6 Hcl ACC	FPTFD FOR REC	ORD A	for the	y i

SEE ATTACHED FOR CONDITIONS OF APPROVAL

(Electronic Submission)

which would entitle the applicant to conduct operations thereon.

Signature

with conditions of approval

14 Thereby certify that the foregoing is true and correct

Electronic Submission #11இஷ்டு ழிர்நின் நிருநிக்கு Well Information System

Name (Printed/Typed) TAMMY SCARBOROUGH FIELD ADMIN III Title

NMOCD ARTESIA

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

06/23/2011

Approved By Title Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Office

Conditions of Approval: Wells with Packers*

Linn Operating Inc Turner A 11

July 08, 2011

- Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
 - a. The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
 - b. Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
 - c. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - d. Submit a subsequent Sundry Form 3160-5 relating the MIT activity. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
 - e. Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore work.
 - f. Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2. Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
 - a. Approved injection pressure compliance is required.
 - b. If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
 - c. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
 - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment.
 - e. Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.

- 3: The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
 - a. The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
 - b. Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
 - c. Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - d. Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for approval by BLM and NMOCD with a detailed plan for correction and the anticipated date of correction. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days.
 - e. After the repairs submit a (Sundry Form 3160-5) Subsequent report, describing the repair(s) and Mechanical Integrity Test as per item 1 above.
 - f. The operator shall keep accurate and current records documenting that the casing annulus is fluid filled. A suggested format for these records is available from the BLM Carlsbad Field Office. Copies of those records shall be furnished at the request of a BLM authorized officer.

*COA's prepared by Paul R. Swartz