

Office

Energy, Minerals and Natural Resources

June 19, 2008

District I

1625 N. French Dr., Hobbs, NM 88241

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87401

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO. 30-015-38472

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Limousine 15 ML ✓

8. Well Number 1H ✓

9. OGRID Number

14744 ✓

10. Pool name or Wildcat

N Seven Rivers; Glorieta Yeso

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Mewbourne Oil Company

3. Address of Operator PO Box 5270

Hobbs, NM 88241

4. Well Location

Unit Letter D : 245 feet from the North line and 370 feet from the West lineSection 22 Township 20S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3450'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☒

OTHER: ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

07/08/11...MI & spud 12 1/4" hole. TD'd hole @ 725'. Ran 460' 9 5/8" 36# J55 ST&C csg. Could not go up or down, continue working pipe w/no success. Called Paul Kautz & Randy Dade w/NMOCD & explained situation. Received verbal approval from Paul & Randy to cmt casing @ 460' as follows. Cemented with 180 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/1.49 yd. Tail with 400 sks Class C w/2% CaCl2. Mixed @ 14.8 /g w/1.34 yd. Plug down @ 7:00 pm 07/09/11. Did not circ cmt. Slow rate lift pressure @ 40# @ 2.5 BPM. WOC. Ran temp survey indication TOC @ 340'. RIH with 1" pipe. Tag at 288'. Cmt in 8 stages with 240 sks Class C with additives. Mixed @ 14.8 #/g w/ 1.34 yd. Circ 10 sks to pit. WOC 18 hrs. At 9:15 am 07/11/11 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

Spud Date: 07/08/11

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 07/11/11Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 7-28-11

Conditions of Approval (if any):