

Submit 3 Copies To Appropriate District Office

State of New Mexico

Form C-103

June 19, 2008

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM

87505

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-015-38586

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

D STATE

8. Well Number 054

9. OGRID Number

873

10. Pool name or Wildcat

ARTESIA;GLORIETA-YESO (O) 96830

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other:

2. Name of Operator

APACHE CORPORATION

3. Address of Operator

303 VETERANS AIRPARK LANE, STE 3000; MIDLAND, TX 79705

4. Well Location

Unit Letter D : 990 feet from the NORTH line and 990 feet from the WEST line

Section 36 Township 17S Range 28E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3675' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: COMPLETION ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

06-13-2011: RIH W/GR/CCL/CBL; RIH W/3 1/8" SLICK GUN & PERF PADDOCK @ 4062', 4068', 4078', 4088', 4106', 4115', 4123', 4130', 4140', 4155', 4163', 4171', 4180', 4192', 4200', 4214', 4226', 4239', 4252', 4262', 4272', 4287', 4297', 4306', 4316', 4324', 4330', 4338', 4345', 4360', 4371', 4380', 4396', 4410', 4428', 4448', W/ 1 JSPF 120 DEG PHASING. 36 HOLES.

06-14-2011: ACIDIZE PADDOCK W/4000 GALS 15% NEFE ACID.

06-21-2011: FRAC PADDOCK: W/174358 20# W/164000# 20/40 OTTAWA SD, 36,000# 16/30 SIBERPROP; 3948g 20# LINEAR GEL FLUSH.

06-23-2011: WASHED SD DWN TO PBD 4580'. CIRC CLEAN.

06-24-2011: RIH W/ 2-7/8" TBG & RODS; ETD 4561.17; SN 4473.57; TAC 3969.08.

07-06-2011: PUT ON PUMP, PRODUCING FROM THE PADDOCK.

Spud Date:

05/24/2011

Rig Release Date:

05/31/2011

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Bev Hatfield

TITLE SR STAFF ENGR TECH

DATE 07/15/2011

Type or print name BEV HATFIELD

E-mail address: beverly.hatfield@apachecorp.com

PHONE: 432-818-1906

For State Use Only

APPROVED BY:

David Gray

TITLE

Field Supervisor

DATE

8-2-11

Conditions of Approval (if any):