UNITED STATES ' DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO 1004-0135 Expires Jüly 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

OCD Artesia

5. Lease Serial No. NMLC068545

abandoned well. Use form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side.				7. If Unit or CA/Agreement, Name and/or No. NMNM71016X		
Type of Well Gas Well				8 Well Name and No POKER LAKE UNIT 151		
2 Name of Operator Contact: SANDRA BELT BOPCO LP E-Mail: sjbelt@basspet.com				9 API Well No 30-015-31595		
P O BOX 2760 Ph: 432-		3b. Phone No (include area code Ph: 432-683-2277 Ext: 14 Fx: 432-687-0329	e) 9	10 Field and Pool, or Exploratory NASH DRAW (DEL,BS,AVA SD)		
4. Location of Well (Footage, Sec., 7			11 County or Parish,	and State		
Sec 6 T24S R30E 510FNL 19			EDDY COUNTY	Y, NM		
UL B						
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	NOTICE, RE	EPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	□ Acidize -	Deepen	Producti	ion (Start/Resume) -	☐ Water Shut-Off	
_	☐ Alter Casing	☐ Fracture Treat	□ Reclama	ntion	☐ Well Integrity	
☐ Subsequent Report	☐ Casing Repair	☐ New Construction	□ Recomp		Other	
Final Abandonment Notice	Change Plans	Plug and Abandon		arıly Abandon		
	Convert to Injection	□ Plug Back	□ Water D	isposal		
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) BOPCO, L.P. respectfully wishes to convert this well to a injection well. Approval of a waterflood project in the Poker Lake Unit was approved January 12, 2011 for 4 wells. R153 A Production tubing will be pulled, the wellbore will be circulated out with produced water, and a packer will be run on a 27/8" injection string and subsequently placed on injection, injecting int to Lower Brushy Canyon formation from 7,226' - 7,236 Accepted for record NACCONDITIONS OF APPROVAL 14. Thereby certify that the foregoing is true and correct.						
, , ,	Electronic Submission #1	06154 verified by the BLM Wo DPCO LP,sent to the Carlsb	eli Informatior ad	System		
Name(Printed/Typed) SANDRA	Title AUTHO	Title AUTHORIZED REPRESENTATIVE				
Signature (Electronic Submission) Da			2011	=		
	THIS SPACE FO	R FEDERAL OR STATE	OFFICE US	SE		
Approved By Aught	the	Title	AP	PROVED	Date	
Conditions of approval, if any, are attache certify that the applicant(holds legal or equivalent would entitle the applicant to condition	not warrant or subject lease Office	JU	L 2 1 2011			
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U S.C. Section 1212, make it a statements or representations as	crime for any person knowingly in to any matter within its jurisdiction	n RUREAU OF	LAND MANAGEMEN	- 1	
** OPERAT	OR-SUBMITTED ** OF	PERATOR-SUBMITTED	CARLSI OPERAT	BAD FIELD OFFICE OR-SUBMITTED	**	

Poker Lake Unit 151 30-015-31595 BOPCO LP July 21, 2011 Conditions of Approval

- Approval is granted for disposal of water being produced on the same lease/communitization agreement/unit agreement only. If additional sources of water from off the lease/communitization agreement/unit agreement are to be disposed of in this well, prior approval is required. The approval request must include proper authorization from the surface owner.
- 2. After tubing is pulled, test the casing to 1440 psi. Conduct a Mechanical Integrity Test of the tubing/casing annulus when the packer or tubing is pulled and any time more than five barrels of packer fluid is replaced.
 - a. The test pressure should be 500 psig, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). Trap that pressure and record it on a chart for 30 minutes. Document the MIT on a calibrated recorder chart within 25 to 85 per cent of its full range.
 - b. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - c. Less than a 10% leakoff may not restrict injection approval. Any leak-off will be evaluated.
 - d. Submit the recorded MIT chart with a subsequent Sundry Form 3160-5 relating the MIT activity. List the name of the BLM witness, or the notified person and date of notification.
 - e. Use of internal protected tubing, on/off equipment, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore work.
 - f. Include the original and three copies of the recorded chart and Sundry (the original will be returned to the operator).

- 3. Compliance with the NMOCD permit is required.
 - g. Approved injection pressure compliance is required.
 - h. Display real time tubing pressure values onsite. A bourdon tube gauge registering 25% to 85% of its full range is acceptable.
 - i. If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
 - j. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
 - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment.
 - k. Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.
- 4. The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
 - a. The annulus is to be maintained full of packer fluid at atmosphere pressure.

 Installation of equipment that will display on site, open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
 - b. The use of automation equipment that will monitor packer fluid level and alarm is required because the wellbore competence is questionable (does not meet standards for Sec Potash).
 - c. Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
 - d. Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of 0psia. Notify the BLMs authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - e. Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for approval by BLM and NMOCD a plan for correction and the anticipated date of correction. The lack of records documenting a continuous fluid packed casing will require rapid correction. Verbal approval for the plan may be given from a BLM authorized officer, with the NOI filed soon after.
 - f. After the repairs submit a (Sundry Form 3160-5) Subsequent report, describing the repair(s) and Mechanical Integrity Test as per item 1 above.