## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

FORM APPROVED OMB NO. 1004-0135 Expires. July 31, 2010

5. Lease Serial No NMNM27486. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No

1. Type of Well Gas Well Goth	8. Well Name and No GISSLER B 81	8. Well Name and No. GISSLER B 81			
2. Name of Operator	9. API Well No.				
BURNETT OIL COMPANY IN	30-019-	39218			
		Phone No. (include area code h: 817-332-5108	No. (include area code) 10. Field and Pool, or E		
4. Location of Well (Footage, Sec., 7		11. County or Parish, and State			
Sec 8 T17S R30E NESE Lot T1650FSL 990FEL			EDDY COUNTY, NM		
12. CHECK APPI	ROPRIATE BOX(ES) TO IT	NDICATE NATURE OF 1	NOTICE, REPORT, OR OTHI	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
Nation of Intent	☐ Acidize	Deepen	Production (Start/Resume)	☐ Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	elamation Well Integrity	
☐ Subsequent Report	Casing Repair	☐ New Construction	Recomplete	Other	
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporarily Abandon	Change to Original A	
_	☐ Convert to Injection	Plug Back	☐ Water Disposal	10	
Burnett Oil Co., Inc. respectfu TO AMEND APPROVED CAS We will set 8 5/8" casing appr We will isolate the oil zones b surface.  Surface hole size will be 12 1/ approximatley 400 fett (per Co for tension.	SING PROGRAM FOR THIS  ox. +/- 400' in ANhydrite abo y running 5.5" casing to tota  '4". Surface casing will be 8 DA)Surface casing design wi	ove Salt and circulate ceme I depth and circulate ceme 5/8" 24# J55 ST&C. Depth	ent to surdace. ent to  n will be Burst and 1.80	ARCH RE	
14 I hereby certify that the foregoing is	Electronic Submission #113	362 verified by the BLM We L COMPANY INC, sent to th	ell Information System	V	
	itted to AFMSS for processing	B by DEBORAH MCKINNEY	on 07/20/2011 (11DLM1100SE)		
Name (Printed/Typed) MARY ST	ARKEY	Title REGUL	ATORY COORDINATOR		
Signature (Electronic Submission)		Date 07/20/2	2011		
	THIS SPACE FOR	FEDERAL OR STATE	OFFICE USE		
Approved By TREY MITCHELL		TitlePETROI F	EUM ENGINEER	Date 07/21/2011	
Conditions of approval, if any, are attached the certify that the applicant holds legal or equivalent would entitle the applicant to conditions.	uitable title to those rights in the su	t warrant or			
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a cristatements or representations as to	me for any person knowingly an	d willfully to make to any department	or agency of the United	

## Additional data for EC transaction #113362 that would not fit on the form

## 32. Additional remarks, continued

Cement to Surface: 150 sx Thixotropic + CaCl 2%, yeild 1.64,tail w/ 250 sx Class C  $\,$  + 2% CaCl yeild 1.35, 14,8 ppg TOC Surface. 100% Excess Cement.

Production casing hole size will be 7 7/8". Production casing will be 5.5" 17# J55 LT&C . Depth will be appox. 4500 feet. Production design will be 1.125 Collapse, 1.00 for Burst and 1.8 for Tension.

Cement to Surface: Single stage job 1500 sx Class C w/ additives, yeild 1.97, 12.9 ppg Circulate to Surface. 50% excess cement.

500' of fresh water gradient (.433 psi/ft.) fluid will be maintained inside casing to keep SF 1.125. If fluid is not at the surface, the fluid level inside 5.5" casing will be determined by wireline to ensure a 500' minimum standing fluid.