OCD-ARTESIA

Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

BUREAU OF LAND MANAGEMENT			5. Lease Serial No.		
SUNDRY NOTICES AND REPORTS ON WELLS				ttee or Tribe Name	
	form for proposals to dr Use Form 3160-3 (APD)				
SUBMIT IN TRIPLICATE – Other instructions on page 2.			7. If Unit of CA/	Agreement, Name and/or No.	
1. Type of Well				d No.	
Oil Well Gas Well X Other 2. Name of Operator				O FEDERAL #002	
SM ENĖRGY COMPANY			30-015-25	30-015-25244 10. Field and Pool or Exploratory Area	
3a. Address 3b. Phone No. (include area code)				•	
3300 N "A" ST BLDG 7-200 MIDLAND TX 79705 (432)688-1709 4 Location of Well (Footage, Sec., TR., M., or Survey Description)				T;YATES-7RS-QU-GRAYBURG	
(B) SEC 24-T18S-R31E 950' FNL & 2310' FEL			EDDY CO	UNTY NM	
	K, THE APPROPRIATE BOX(ES) TO INDICATE NATUR	E OF NOTICE, REPORT OR	OTHER DATA	
TYPE OF SUBMISSION TYPE OF ACTION					
X Notice of Intent	Acidize	Deepen	Production (Start/Resum	ne) Water Shut-Off	
	Alter Casing	Fracture Treat	Reclamation	Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete	Other	
Final Abandonment Notice	Change Plans Convert to Injection	X Plug and Abandon Plug Back	Temporarily Abandon Water Disposal		
following completion of the involve testing has been completed. Final determined that the site is ready for 1. RIH TBG TO 3743' TAC 2. PUH TO 1600' SPOT 25	red operations. If the operation res Abandonment Notices must be file r final inspection.) G CIBP CIRCULATE HOL 5 SX CMT AT THE BASE SX CMT WOC & TAG	ults in a multiple completion only after all requirement. E 9.5 MUD CAP C	on or recompletion in a new int ts, including reclamation, have IBP 25 SX CMT	nt reports must be filed within 30 days terval, a Form 3160-4 must be filed once been completed and the operator has	
4. PUHTO 60' SPOT 15 SX CMT TO SURFACE Add T/salt plug from/110-1610 (255x min) wocktag					
RECEIVED					
			FEB 29	1	
			NMOCD A	RTESIA	
14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)					
VICKIE MARTINEZ		Title ENGI	NEER TECH II		
Signature V LULL	Martina	Date 01/26/	2012		
	THIS SPACE FOR	R FEDERAL OR ST	ATE OFFICE USE		
Approved by		· L	SEPS	7-17-12	
Title Date Conduttons of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.					
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictions or fraudulent statements or representations as to any matter within its jurisdiction					

(Instructions on page 2)

Al 3/1/2012

Accepted for record NMOCD

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13 - Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment.

NOTICES

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seg., 351 et seg., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and grantingapproval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

WELLBORE DIAGRAM

Geronimo[#]2 Federal

LEASE:

GERONIMO

950' FNL & 2310' FEL

WELL NO. : SEC: 24

2

API#

30-015-25244

LOCATION: FIELD: SHUGART

> CURRENT ... WELLBORE .

AGL: 8'

T:18S R:31 CT/ST: EDDY, NM SPUD: COMP: 4/3/85

INITIAL FROM:

4/16/85

Greyburg

INJECTOR

KB: 4694'

DF:

TOPS 1. QUEEN - 3512'

2. PENROSE-3759'

3. GRAYBURG -4072'

4. GRAYBURG-4264'

RAN 10 JTS. 13 3/8" 48# J-55 @ 346' K.B.

CMTD W/ 400 sx "C" 2% CalCl2

CIRC 50 SX TO Surface- PRESSURE TEST TO 1000 PSI HELD, O K.

CIBP @ 3743'

3770'-3782' Penrose (13 perfs) 8/8/90 SAND FRACED

GRAYBURG PERF:

4264'4277.5' (10 SHOTS-180°) (4/14/85)ACID w/1000 GAL. 15%HCL FRAC W/20000 GALS YF3 PSD, 47000# 12/20 SAND

ACID & FRAC EXISTING PERFS (4/3/87) W/500 gals acid. FRAC W/27000 GAL 30# X-LINK, 6400 100#mesh, 38000# 20/40 & 37000# 12/20 SAND. ACID SAND FRACED AGAIN 8/10/90

4300'-4306' (21 perfs) (8/10/90) SAND FRACED

PBTD: 4691' 4702 TD:

RAN 118 JTS. 4 1/2" 10.5# J55 @4700' K.B.- SHOE @ 4701'-FLOAT @4691' CEMTD W/ 1730 SKS LITE LLL and trailed w/ 460sxs 50/50 POZ CLASS C CIRC 50sxs to SURF- TESTED SYSTEM TO 1000 PSI FOR 30 MIN. -TEST-OK


WELLBORE DIAGRAM Geronimo 2 Federal **GERONIMO** WELL NO. : API# 30-015-25244 LEASE: 950' FNL & 2310' FEL SEC: 24 SPUD: 4/3/85 LOCATION: T:18S R:31 4/16/85 AGL: 8' CT/ST: EDDY, NM COMP: FIELD: SHUGART INJECTOR KB: 4694' INITIAL FROM: Greyburg Fed CURRENT 1545 Cm 7 60 To 3 TOPS WELLBORE 1. QUEEN - 3512' 2. PENROSE-3759 3. GRAYBURG -4072' 4. GRAYBURG-4264' MINE RAN 10 JTS, 13 3/8" 48# J-55 @ 346' K.B. CMTD W/ 400 sx "C" 2% CalCl2 CIRC 50 SX TO Surface- PRESSURE TEST TO 1000 PSI HELD, O.K.

258454MT. 396 To 246 WOCY TAS 9,5 Mass 255x5CmT 1600' Total Was + The 9,5 Mud 265KSCMJ 3745 TO 3645 CIBP @ 3743' 3770'-3782' Penrose (13 perfs) 8/8/90 SAND FRACED GRAYBURG PERF: 4264'4277.5' (10 SHOTS-180*) (4/14/85)ACID w/1000 GAL, 15%HCL FRAC W/20000 GALS YF3 PSD, 47000# 12/20 SAND ACID & FRAC EXISTING PERFS (4/3/87) W/500 gals acid. FRAC W/27000 GAL 30# X-LINK, 6400 100#mesh, 38000# 20/40 & 37000# 12/20 SAND. ACID SAND FRACED AGAIN 8/10/90

PBTD: 4691'

RAN 118 JTS. 4 1/2" 10.5# J55 @4700' K.B.- SHOE @ 4701'-FLOAT @4691'
CEMTD W/ 1730 SKS LITE LLL and trailed w/ 460sxs 50/50 POZ CLASS C
CIRC 50sxs to SURF- TESTED SYSTEM TO 1000 PSI FOR 30 MIN. -TEST-OK

4300'-4306' (21 perfs) (8/10/90) SAND FRACED



BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>minety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

J. Amos 3/6/11

)

Requirements for ground level dry hole markers <u>Well Identification Markers</u> Conditions of Approval (COA)

The BLM Carlsbad Field Office (CFO) Conditions of Approval (COA) Requires that ground level dry hole markers be placed on well within the Lesser Prairie Chicken habitat area. The dry hole markers will be to the following specifications. The operator will construct the markers as follows:

- 1. An 8 inch X 8 inch steel plate 1/8 to 3/16 of an inch thick is to be placed on the old dry hole marker stand pipe 2 inches from ground level, in the Lesser Prairie Chicken habitat area.
- 2. Steel plate may be welded or bolted approximately 2 inches from ground level on the stand pipes. If plates are bolted to the stand pipe, the person installing the plate will be required to weld a pipe collar on the plate and place a minimum of two set screws/bolt on each collar. Aluminum data plates may be bolted with minimum ¼ inch bolt and locking nuts or self tapping fine threaded screws. A minimum of one in each corner is to be installed on each plate.
- 3. An 8 inch x 8 inch aluminum plate, which is 12 gauge or .080 sign material (1/8 inch aluminum plate may be used in place of the .080 plate) with the required information for that well stamped or engraved in a minimum 3/8 inch tall letter or number.
- 4. The following information will be stamped or engraved on the 8 inch X 8 inch aluminum plate in the following order.
 - a. First row: Operators name
 - b. Second row: Well name and number
 - c. Third row: Legal location to include ¼ ¼, Section, Township, and range. If the legal location cannot be placed on one row it can be split into two rows with the ¼ ¼ (example: 1980 FNL 1980 FWL) being on the top row.
 - d. Fourth row: Lease Number and API number.
 - i. Example marker plate: (attached)

NMOCD Order No. R-12965 also required the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a ground level dry hole marker was installed as required in the COA's from the BLM.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1 The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston Environmental Protection Specialist 575-234-5958

Bobby Ballard Environmental Protection Specialist 575-234-2230

Randy Rust Environmental Protection Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922 Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Doug Hoag Civil Engineering Technician 575-234-5979