

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-39454
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name STIRLING 6M
8. Well Number #2
9. OGRID Number 255333
10. Pool name or Wildcat Red Lake: Glorieta-Yeso (51120)

4. Well Location Unit Letter <u>M (Lot 7)</u> : <u>660</u> feet from the <u>SOUTH</u> line and <u>330</u> feet from the <u>WEST</u> line Section <u>6</u> Township <u>18-S</u> Range <u>27-E</u> NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3335' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

LIME ROCK RESOURCES A, L.P.

3. Address of Operator

c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: Spud & Surface Casings ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spud well on 12/13/11. Drilled 17-1/2" hole to 273'. Landed 13-3/8" 48# H-40 csg @ 257'. Cmted w/360 sx (482 cf) "C" cmt w/2% Cacl2, & 0.25# CF. Circ 137 sx cmt to surface. On 12/14/11, PT 13-3/8" csg to 600 psi for 30 min - OK.

Drilled 12-1/4" deviated hole to MD1635'. Landed 8-5/8" 24# J-55 csg @ MD1619'. Cmted lead w/155 sx (287 cf) 65/35 "C" cmt w/2% Cacl2, 0.3% SMS, & 5# LCM. Tailed w/655 sx (878 cf) "C" cmt w/1% Cacl2 & 1/4# cello flake. Circ 152 sx cmt to surface. On 12/19/11, PT 8-5/8" csg to 1500 psi for 30 min - OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.


SIGNATURE *Mike Pippin* TITLE Petroleum Engineer - Agent DATE 12/20/11

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: *T. C. Shumard* TITLE *Geologist* DATE 12/21/2011

Conditions of Approval (if any):



dm