

OPERATOR'S COPY

Form 3160-5
(April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
NADEL AND GUSMAN HEYCO, LLC

3a. Address
PO BOX 1936 ~ ROSWELL NM 88202-1936

3b. Phone No. (include area code)
575/623/6601

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

400' FNL & 380' FEL Sec. 12; T18S, R31E

FORM APPROVED
OMB No. 1034-0137
Expires March 31, 2007

5. Lease Serial No.
NMNM-106718

6. If Indian, Allottee or Tribe Name

7. If Unit or C/A Agreement, Name and/or No

8. Well Name and No
TAYLOR DEEP 12 FED #10

9. API Well No
30-025-39468

10. Field and Pool, or Exploratory Area

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- | | | | |
|---|---|--|--|
| <input type="checkbox"/> Acidize | <input type="checkbox"/> Deepen | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off |
| <input type="checkbox"/> Alter Casing | <input type="checkbox"/> Fracture Treat | <input type="checkbox"/> Reclamation | <input type="checkbox"/> Well Integrity |
| <input type="checkbox"/> Casing Repair | <input type="checkbox"/> New Construction | <input type="checkbox"/> Recomplete | <input checked="" type="checkbox"/> Other Surface Casing and |
| <input type="checkbox"/> Change Plans | <input type="checkbox"/> Plug and Abandon | <input type="checkbox"/> Temporarily Abandon | Ent Sundry |
| <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back | <input type="checkbox"/> Water Disposal | |

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

BLM Bond No. NMB00520
Surety Bond No. R004230

10/18/11 Spud Well 3 30 pm.

10/21/11 Surface, Hole Size 11", run 24 Jts 3 5/8" J-55 32# . Depth 1010'. Lead-150 sks Class "C"-4% Bentonite+1% Cacl2+.25% celloflake +.25% R-38. 5% Salt, cnt wt 13.80, Yield 1.70, gal/sk 8.72 Tail-200 sks Class "C"-2% Cacl2+.25% R-38 Wt. 14.80 Yield 1.35 Gal/Sk 6.34 No problems w/csg or cnt job Plug dn @ 2.20 pm 10/21/11. Circ 53 sks (16 bbls) to pit Called Carlshad BLM F/csg & cnt job, talked to Richard Carrasco.

ROUTED FOR RECORD

NOV 16 2011

14. I hereby certify that the foregoing is true and correct.
Name (Printed/Typed)

Tammy R. Lunk

Title Production Tech

Signature

Date

10/24/2011

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

SUMMARY CASING AND CEMENTING REPORT

STRING: SURFACE DATE: 10/21/2011
OPERATOR: NADEL & GUSSMAN HEYCO WELL: TAYLOR 12 Federal #10
CONTRACTOR: PATRIOT RIG: #1
REP: KEITH CANNON

CASING DETAIL

HOLE SIZE:	11	DEPTH:	1010	
11" HOLE				1010.00
8 5/8 FLOAT SHOE				<u>1.55</u>
				1008.45
1 JT. 8 5/8 J-55 32# CSG				<u>42.19</u>
				966.26
8 5/8 FLOAT COLLAR				<u>1.30</u>
				964.96
23- JTS. 8 5/8 J-55 32# CSG				<u>970.27</u>
				-5.31
KB TO GL				<u>18.00</u>

CENTRALIZERS PLACED @ 295.92', 256.60', 219.11', 181.75', 106.32'

REMARKS:

TOTAL CASING DELIVERED... 26 JTS. 32# J-55 8 5/8 LT&C (1105.80')
ALL CASING WAS DRIFTED, CLEANED, & VISUALLY INSPECTED ON LOCATION
ELECT WELD SHOE TOP AND BOTTOM OF 1ST COLLAR AND BTM OF 2ND COLLAR UP
TAGGED BOTTOM NO FILL. CIRCULATED CAPACITY & ANNULAR VOLUME

EXCESS CASING

CASING NOT USED ... 2 JTS. NOT USED J-55 36# LTC (84.40')
DISPOSITION ... GYS, 2 JTS

CEMENTING DATA

COMPANY: RISING STAR

DISTRICT. HOBBS

1ST STAGE:

PREFLUSH: 20bbls F/W SPACER

LEAD:

150 SKS. CLASS "C"+4%BENTONITE+1%CaCl₂+.25%CELLOFLAKE+.25%R-38, 5%SALT,
CMT WT 13.80, YIELD 1.70, GAL/SK 8.72

TAIL:

200 SKS. CLASS "C"+ 2% CaCl₂+ 25%R-38 WT. 14.80 YIELD 1.35 GAL/SK 6.34

SUMMARY CASING AND CEMENTING REPORT

NOTE: NO PROBLEMS W/ CSG OR CMT JOB PLUG DN @ 2.20PM 10/21/2011. CIRC 53SKS (16BBLs) TO PIT. CALL CARSBAD BLM F/ CSG & CMT JOB, TALK TO RICHARD CARRASCO, NO BLM REP ON LOCATION