Form 3160-5 (April 2004)

UNITED STATES OCD-ARTESIA

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM APPROVED OM B No 1004-0137 Expires. March 31; 2007

Lease Serial No.

(SHL) NM 120897, (BHL) LC 68905

6. If Indian, Allottee or Tribe Name

abandoned well. Use Form \$160.5 (AFD) for such proposals.	
SUBMIT IN TRIPLICATE- Other instructions on reverse side.	7. If Unit or CA/Agreement, Name and/or No. Poker Lake Unit NMNM 71016X
1. Type of Well ☐ ☐ Gas Well ☐ ☐ Other	8. Well Name and No.
2. Name of Operator BOPCO, L. P.	Poker Lake Unit 333H 9. API Well No.
3a. Address 3b. Phone No. (include area code) P. O. Box 2760 Midland, TX 79702 432-683-2277	30-015 - 3-9294 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec , T , R., M., or Survey Description)	Poker Lake NW (Delaware)
NWSW, UL L, 2295' FSL, 325' FWL, Sec 13, T24S-R30E, LT:N32.216822, Lg:W103.841425 2280' FSL, 330' FWL, Sec 11, T24S-R30E, LT:N32.231250, Lg:W103.858689	11. County or Parish, State Eddy, New Mexico
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	
Acidize	Well Integrity Other
Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) BOPCO L.P. respectfully requests to make the following changes listed below for the above captioned well: Change the 4-1/2" liner to a 4-1/2" Baker Hughes completion system utilizing hydraulic set packers for zone isolation. The top of the completion system will be set with a Baker B3 packer, 50' (8,474') into the 7" 26 ppf, N-80, LT&C casing shoe which will be set at 8,524'. The 7" casing will be cemented 500' into the 9-5/8" intermediate casing. The liner packer will be isolating the 4-1/2" casing and 20 Baker open hole packers.	
Casing Specs: 7" 26 ppf, N-80, LT&C set at 8,524' 4-1/2" 11.6 ppf, HCP-110, LT&C set at 15,095' ACCEPTED JAN 18 2012 NMOCD JC JG WA	JAN 1 3 2012 JS/ Chris Walls BUREAU OF LAND MANAGEMENT CARLSBAD FIELD OFFICE
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Christopher Giese Title Drilling Engineer	OMICODIO TREED OFFICE
Signature (Municiples Pero Date 12/28/11	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE	
Approved by Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully states any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	Date to make to any department or agency of the United