

Submit 1 Copy To Appropriate District
Office
District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV --
1220 S St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-39773
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-7377
7. Lease Name or Unit Agreement Name Skeen 21 State Com
8. Well Number 2H
9. OGRID Number 14744
10. Pool name or Wildcat Turkey Track Bone Spring 60660
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3017' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>
2. Name of Operator Mewbourne Oil Company
3. Address of Operator PO Box 5270, Hobbs, NM 88241
4. Well Location Unit Letter B : 330' feet from the North line and 1980' feet from the East line Section 21 Township 26S Range 28E NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3017' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01/08/12...MI & spud 17 1/2" hole. Ran 570' 13 3/8" 48# H40 ST&C Csg. Cemented with 600 sks Class "C" w/2% CaCl2. Mixed @ 14.8 /g w/ 1.35 yd. Circulated 137 sks to pit. At 12:45 PM 01/10/12 tested BOPE & csg to 1250# for 30 minutes, held OK. Drilled out with 12 1/4" bit.

01/15/12...TD 12 1/4" hole. Ran 2474' 9 5/8" 36# J55 ST&C Csg. Cemented with 700 sks Class "C" (35:65:6) w/additives. Mixed @ 12.6 /g w/ 2.00 yd. Tail w/200 sks Class "C" w/2% CaCl2. . Mixed @ 14.8 /g w/ 1.34 yd. Plug down @ 5:45 P.M. 01/15/12. Circulated 143 sks to pit. At 2:30 PM 01/16/12 tested BOPE & csg to 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

Spud Date: 01/08/2012

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 01/23/12

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: T. C. Shepard TITLE Geologist DATE 1/25/2012

Conditions of Approval (if any):

