

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-005-64150
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-1234
7. Lease Name or Unit Agreement Name Easy State
8. Well Number 1
9. OGRID Number 248481
10. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Ponderosa Petroleum Corporation

3. Address of Operator
P.O. Box 132, Roswell, NM 88202

4. Well Location
Unit Letter C : 330 feet from the North line and 1650 feet from the West line
Section 22 Township 11S Range 27E NMPMChaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3727 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:


REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Drilled 6 1/8" hole to 1007 feet. Ran 1011 feet of 4 1/2", 10.5#, J-55 casing. Cemented with 320 sx. "C" with 2% CaCl. Plug down at 1:40 p.m. on 12/17/11. TOC @ 86 feet from surface. Tested casing to 1000 psi for 30 minutes. Held okay.



Spud Date: 10/12/11

Rig Release Date: 12/20/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE F. Pool, III TITLE President DATE 12/27/11

Type or print name Fred F. Pool, III E-mail address: sspool@cableone.net PHONE: 575-623-4667
For State Use Only

APPROVED BY: T. L. Shepard TITLE Geologist DATE 1/9/2012
Conditions of Approval (if any):