

Submit To Appropriate District Office

Two Copies

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division

220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-105

July 17, 2008

1. WELL API NO.

30-015-39407

2. Type of Lease

☐ STATE ☒ FEE ☐ FED/INDIAN

3. State Oil & Gas Lease No.

5. Lease Name or Unit Agreement Name

Devon 8 Fee

6. Well Number:

14

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

4. Reason for filing:

☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only)☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)

7. Type of Completion:

☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER

8. Name of Operator

Occidental Permian Ltd.

9. OGRID

157984

10. Address of Operator

P.O. Box 50250 Midland, TX 79710

11. Pool name or Wildcat

Hay Hollow Bone Spring, N.

12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	A	8	25S	28E		990	north	330	east	Eddy
BH:	D	8	25S	28E		571	north	342	west	Eddy

13. Date Spudded

14. Date T.D. Reached

15. Date Rig Released

16. Date Completed (Ready to Produce)

17. Elevations (DF and RKB, RT, GR, etc.)

11/10/11

12/12/11

12/16/11

11/30/12

3009' GR

18. Total Measured Depth of Well

19. Plug Back Measured Depth

20. Was Directional Survey Made?

21. Type Electric and Other Logs Run

12387' M 7967' V

12350' M 7970' V

YES

TDL/HRLA/KCL/CN/GR

22. Producing Interval(s), of this completion - Top, Bottom, Name

8355-12151 Bone Springs

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13 3/8"	48	455'	17 1/2"	590	N/A
9 5/8"	40	2535'	12 1/4"	800	N/A
5 1/2 - 7"	17 - 26	12387'	8 1/2"	1780	N/A

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					27 1/8"	7239'	

25. TUBING RECORD

26. Perforation record (interval, size, and number)

42 holes @ 12155-11655, 11491-10995, 10831-10335, 10711-9675, 9511-9015, 8851-8355' Total 252 holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
8355-12151'	325751g WFGRB + 20000g 15% HCl Acid
	999505g DF200 R17 w/54556# 2.

28. PRODUCTION

Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod. or Shut-in)	
3/11/12		Pumping ESP				Prod. Frac Tanks	
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
3/22/12	24	—		292	50	460	
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
			292	50	460	40.0	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold

30. Test Witnessed By

31. List Attachments

C102, C104, C103, Directional Surveys, Logs

32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.

33. If an on-site burial was used at the well, report the exact location of the on-site burial:

Latitude

Longitude

NAD 1927 1983

I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature *David Stewart* Printed Name David Stewart Title Reg. Advisor Date 4/5/12

E-mail Address david.stewart@oxy.com

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinberry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand 2471	T. Morrison	
T. Drinkard	T. Bone Springs 6041	T. Todilto	
T. Abo	T. 1312 Bone Springs 7074	T. Entrada	
T. Wolfcamp	T. 2017 Bone Springs 7928	T. Wingate	
T. Penn	T. Cherry Canyon 3331	T. Chinle	
T. Cisco (Bough C)	T. Brushy Canyon 7928	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 1, from 1944 to 1945
No. 2, from 1946 to 1947

No. 3, from: to:
No. 4, from: to:

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0.0	0.5	0.5	Gravelly sand	0.0	0.5	0.5	Gravelly sand
0.5	1.0	0.5	Gravelly sand	0.5	1.0	0.5	Gravelly sand
1.0	1.5	0.5	Gravelly sand	1.0	1.5	0.5	Gravelly sand
1.5	2.0	0.5	Gravelly sand	1.5	2.0	0.5	Gravelly sand
2.0	2.5	0.5	Gravelly sand	2.0	2.5	0.5	Gravelly sand
2.5	3.0	0.5	Gravelly sand	2.5	3.0	0.5	Gravelly sand
3.0	3.5	0.5	Gravelly sand	3.0	3.5	0.5	Gravelly sand
3.5	4.0	0.5	Gravelly sand	3.5	4.0	0.5	Gravelly sand
4.0	4.5	0.5	Gravelly sand	4.0	4.5	0.5	Gravelly sand
4.5	5.0	0.5	Gravelly sand	4.5	5.0	0.5	Gravelly sand
5.0	5.5	0.5	Gravelly sand	5.0	5.5	0.5	Gravelly sand
5.5	6.0	0.5	Gravelly sand	5.5	6.0	0.5	Gravelly sand
6.0	6.5	0.5	Gravelly sand	6.0	6.5	0.5	Gravelly sand
6.5	7.0	0.5	Gravelly sand	6.5	7.0	0.5	Gravelly sand
7.0	7.5	0.5	Gravelly sand	7.0	7.5	0.5	Gravelly sand
7.5	8.0	0.5	Gravelly sand	7.5	8.0	0.5	Gravelly sand
8.0	8.5	0.5	Gravelly sand	8.0	8.5	0.5	Gravelly sand
8.5	9.0	0.5	Gravelly sand	8.5	9.0	0.5	Gravelly sand
9.0	9.5	0.5	Gravelly sand	9.0	9.5	0.5	Gravelly sand
9.5	10.0	0.5	Gravelly sand	9.5	10.0	0.5	Gravelly sand