

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-39507
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: Parkway 23 State
8. Well Number 7H
9. OGRID Number 7377
10. Pool name or Wildcat Turkey Track; Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other
2. Name of Operator EOG Resources, Inc.
3. Address of Operator P.O. Box 2267 Midland, TX 79702
4. Well Location Unit Letter M : 520 feet from the South line and 200 feet from the West line Section 23 Township 19S Range 29E NMPM County Eddy
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3279' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

RECEIVED

APR 18 2012

NMOCD ARTESIA

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/11/12 Spud 14-3/4" hole.

4/12/12 Ran 9 jts 11-3/4", 42#, H40 STC casing set at 380'.

Cemented w/ 400 sx Class C, 14.8 ppg, 1.346 yield. Did not circulate.

Lost circulation at 153'. NMOCD-Randy Dade gave permission to top out cement without running a temperature survey. Tagged TOC at 97' with 1" pipe. Pumped 35 bbls Class C cement.

Circulated 54 sx cement to surface. WOC 30 hrs.

4/13/12 Tested casing to 1000 psi for 30 minutes. Test good.

Resumed drilling 11" hole.

Spud Date:

4/11/12

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Stan Wagner

TITLE

Regulatory Analyst

DATE 4/16/12

Type or print name Stan Wagner

E-mail address:

PHONE 432-686-3689

For State Use Only

APPROVED BY

L R Dade

TITLE

Dist. Rep.

DATE 04/19/2012

Conditions of Approval (if any):