

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-39454 ✓
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name STIRLING 6M ✓
8. Well Number #2 ✓
9. OGRID Number 255333 277558
10. Pool name or Wildcat Red Lake: Glorieta-Yeso (51120)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
LIME ROCK RESOURCES A, L.P.

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location

Unit Letter M (Lot 7) : 660 feet from the SOUTH line and 330 feet from the WEST line
Section 6 Township 18-S Range 27-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3335' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: 5-1/2" Casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Drilled 7-7/8" deviated hole to MD4229'. Ran open hole logs. Landed 5-1/2" 17# J-55 csg @ MD4212'. Cmted lead w/240 sx (479 cf) 65/35 "C" cmt w/FL-52, 5% salt, 5# LCM-1, & 1/8# cf. Tailed w/500 sx (683 cf) 50/50 "C" cmt w/1% FL-25, 1% BA-58, 0.4% SMS, 5% salt, 3# LCM-1, & 1/8# cf. Circ 112 sx cmt to surface. Released drilling rig on 12/27/11. Plan to pressure test 5-1/2" csg before completion operations.


Bottom Hole @ 975' FSL 341' FWL Sec. 6 T18S R27E

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 12/28/11

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573
For State Use Only

APPROVED BY: T. C. Shepard TITLE Geologist DATE 1/11/2012
Conditions of Approval (if any):



dm