

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-39960
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 648
7. Lease Name or Unit Agreement Name: East Millman Unit
8. Well Number 241
9. OGRID Number 019958
10. Pool name or Wildcat Millman-Yates-SR-QN-GB-SA East
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3430' KB, 3418' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Stephens & Johnson Operating Co

3. Address of Operator
P O Box 2249, Wichita Falls, TX 76307

4. Well Location
Unit Letter B : 597 feet from the North line and 1919 feet from the East line
Section 14 Township 19S Range 28E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3430' KB, 3418' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC.. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See Attached Detail



Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William M. Kincaid TITLE Petroleum Engineer DATE 6/5/12
mkincaid@sjoc.net

Type or print name William M. Kincaid E-mail address: mkincaid@sjoc.net PHONE 940-723-2166

For State Use Only

APPROVED BY J. C. Shepherd TITLE Geologist DATE 6/15/2012
Conditions of Approval (if any):

Page 2 (C-103)
Stephens & Johnson Operating Co.
East Millman Unit No. 241
API No. 30-015-39960
Eddy County, New Mexico

Well Data:

Total Depth: 2747' KB
PBSD: 2718' KB
Surface Casg: 8 5/8" 24# set @ 300' KB, cement w/200 sx, cement
circulated to surface.
Prod. Csg: 5 1/2" 15.50# set @ 2734' KB, cement w/600 sx,
cement circulated to surface.

Completion Information:

04/17/2012: Pressure tested 5 1/2" casing to 1500 psi for 30
minutes. Held OK. Perforated one shot at each of
the following depths: 2211', 2213', 2215', 2217',
2255', 2260', 2268', 2273', 2277', 2305', 2308',
2311', 2314', 2317', 2320', 2323', 2382', 2418',
2433', 2435', 2437', 2449', 2455', 2475' KB.

04/17/2012: Acidized perforations with 2500 gals 15% NEFE acid.

05/07/2012: Frac perforations with 108,909 gals 10# brine, 1000
lbs 20/40 sand, 11,410 lbs LiteProp 108 (14/40),
4,000 lbs Resin coated Super LC 20/40 sand.

05/09/2012: Run downhole equipment as follows:
Tubing: 82 jts, 2 7/8", 6.5 lb/ft, J-55, SN @ 2518' KB
Rods: 1-2', 1-4', 1-6', 1-8' x 7/8" Grade D rod subs
40 - 7/8" Grade D rods
54 - 3/4" Grade D rods
4 - 1 1/2" Grade D Sinker Bars
Pump: 2 1/2" x 2" x 16' pump w/1' lift sub

05/09/2012: Install electricity, turn well on production.