Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Artesia

FORM APPROVED OMB NO 1004-0135 Expires: July 31, 2010

	Expires:		
ase Seri	al No		•

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use form 3160-3 (APD) for such proposals

	Ν	MN	M1	00	558				
6.	If	Indi	an,	Allo	ottee	or	Tribe	Nan	ne

abandoneg wei									
SUBMIT IN TRIF		7 If Unit or CA/Agreen	nent, Namo	and/or	No				
1. Type of Well Soli Well ☐ Gas Well ☐ Oth	er			8. Well Name and No RDX 15 11					
2. Name of Operator RKI EXPLORATION & PROD	Contact:	CHARLES K p.com	AHN		9. API Well No. 30-015-37093-00	D-X1		**	
3a Address 3817 NW EXPRESSWAY SUI OKLAHOMA CITY, OK 73112		3b. Phone No Ph: 405-99 Fx: 405-996		de)	10. Field and Pool, or Exploratory BRUSHY DRAW				
4. Location of Well (Footage, Sec., T.	., R., M., or Survey Description	i)			11. County or Parish, a	nd State			
Sec 15 T26S R30E SENW 22 32.043879 N Lat, 103.872857					EDDY COUNTY	, NM			
12. CHECK APPR	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF	F NOTICE, R	EPORT, OR OTHER	RDATA		,	
TYPE OF SUBMISSION			ТҮРЕ	OF ACTION					
Notice of Intent	☐ Acidize	□ Dee	pen	□ Product	ion (Start/Resume)	□ Wate	r Shut-	Off	
	☐ Alter Casing	□ Frac	ture Treat	□ Reclam	ation	□ Well	Integri	ty	
Subsequent Report Subsequent Re	☐ Casing Repair	□ New	Construction	□ Recomp	olete	Othe	r		
Final Abandonment Notice	☐ Change Plans	□ Plug	g and Abandon	□ Tempor	arily Abandon	Drilling Operations			
	☐ Convert to Injection	□ Plug	g Back	□ Water I	Disposal				
RIG UP AND SPUD ON 1-08-2012. DRILLED 17 1/2 INCH HOLE TO 884 FEET. RAN 22 JOINTS OF 13 3/8 INCH 54.5#, J55, LT&C CASING WITH SHOE @ 884 FEET, FLOAT COLLAR @ 846 FEET CALLED BLM @ 6:00AM TO NOTIFY INTENT TO CEMENT 13 3/8 INCH CASING Cementing: LEAD: PUMP 20 BBLS FW AHEAD, PUMP LEAD SLURRY 530 SKS/ 165 BBLS CLASS C+4%PF20+2% PF1+0.25#/SKPF29. 13/5 PPG, 1 75 YIELD TAIL: SLURRY 200SKS/ 47 BBLS C+1%PF1 14.8 PPG, 1.34 YIELD, DROP TOP PLUG, BUMP PLUG @ 161.56 BBLS TO 800 PSI. FLOATS HELD, PLUG DOWN @ 23:00, CIRCULATED 90 BBLS CEMENT TO SURFACE, FULL RETURNS, R/D CEMENTERS ACCOPIED for record AUXIL 456/12 WHOCD 14. Thereby certify that the foregoing is true and correct/ Electronic Submission #138618 verified by the BLM Well Information System For RKI EXPLORATION & PROD LLC, sent to the Carlsbad									
Name (Printed/Typed) CHARLES	nmitted to AFMSS for proc S K AHN			•	RY MANAGER	ART	5 2012	EV	
Signature (Electronic S	·			1/2012		ESIA	12	D	
	THIS SPACE F	OR FEDERA	L OR STAT	E OFFICE U	SE				
Approved By ACCEPT		A AMOS VISOR EPS		Da	ite 06/(03/2012			
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conditions to the conditions of the condition	uitable title to those rights in thuct operations thereon.	ne subject lease	Office Carls						
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U S.C. Section 1212, make it statements or representations a	a crime for any p is to any matter v	erson knowingly vithin its jurisdict	and willfully to r	nake to any department or	agency of	the Uni	ted	

'Additional data for EC transaction #138618 that would not fit on the form

32. Additional remarks, continued

Drilled out cement 38 hours after cement in place.