

Submit 1 Copy To Appropriate District Office
District I – (575) 393-6161
1625 N French Dr, Hobbs, NM 88240
District II – (575) 748-1283
811 S First St, Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd, Aztec, NM 87410
District IV – (505) 476-3460
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-38675
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Layla 35
8. Well Number 2H
9. OGRID Number 14744
10. Pool name or Wildcat Culebra Bluff; Bone Spring, South

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270, Hobbs, New Mexico

4. Well Location

Unit Letter C : 185 feet from the North line and 2150 feet from the West line
Section 35 Township 23S Range 28E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3018' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:


REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

06/06/12...TD 12 1/4" hole at 2525'. Ran 2525' of 9 5/8" 36# J55 ST csg. Cemented with 650 sks BJ Lite Class C (35:65:4) w/additives. Mixed @ 12.5 #/g w/ 2.02 yd. Tail w/200 sks Class C w/1% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 7:00 AM 06/06/12. Circulated 61 sks of cmt to the pit. Drilled out with 8 3/4" bit.



Spud Date: 06/02/2012

Rig Release Date:

Report csg pressure test

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 06/12/12

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: DR Dade TITLE Dist AP Supervisor DATE 6/26/12

Conditions of Approval (if any):