Form 3160-5 (April 2004)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS
one not use this form for proposals to drill or to re-enter an

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

WMOLL65
If Indian, Allottee or Tribe Name

SUBMIT IN TR	7. If Unit or CA/Agreement, Name and/or No.  8. Well Name and No.  Yutes Tedera ( ## ID)  9. API Well No.						
1. Type of Well Oil Well.							
2. Name of Operator OXY USA W							
3a. Address P.O. Box 50250 Midland, TX	3b. Phone No. (include 432-685-5717	area code)	30-O15- 26255  10. Field and Pool, or Exploratory Area				
4 Location of Well (Footage, Sec., 1650 FNL 660 FE	Avalor Delawere  11. County or Parish, State  Eddy WM						
TYPE OF SUBMISSION	PPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATE TYPE OF ACTION						
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize  Alter Casing  Casing Repair  Change Plans  Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Standard Reclamation Recomplete Temporarily Ab	Well Integrity Other Dandon			
If the proposal is to deepen due Attach the Bond under which t	ectionally or recomplete horizontall he work will be performed or provi	y, give subsurface location ide the Bond No. on file w	ns and measured and tru vith BLM/BIA.  Require	ny proposed work and approximate duration thereof. ne vertical depths of all pertinent markers and zones, red subsequent reports shall be filed within 30 days in a new interval, a Form 3160-4 shall be filed once			

TD-3404' PBTD-3349' Perfs - 3216-3226'

RECLAMATION PROCEDURE
ATTACHED

JUL 16 2012

NMOCD ARTESIA

determined that the site is ready for final inspection.)

13-3/8" 48# csg @ 238' w/ 280sx, 17-1/2" hole, TOC-Surf-Circ 9-5/8" 36# csg @ 1217' w/ 900sx, 12-1/4" hole, TOC-Surf-Circ 7" 23# csg @ 3107' w/ 600sx, 8-3/4" hole, TOC-Surf-Circ 4-1/2" 10.5# csg @ 3404' w/ 100sx, 6-1/4" hole, TOC-2400'-TS

testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has

- 1. RIH & set CIBP @ 3166' M&P 25sx cmt to 2965' WOC-Tag
- 2. Perf @ 1267', sqz 75sx cmt to 925' WOC-Tag
- 3. Perf @ 288', sqz 65sx cmt to surface 10# MLF between plugs

SEE ATTACHED FOR CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)		-						
David Stewart		Title Regulatory Advisor						
Signature du fili	Date	(	elarlia					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Approved by James ac Comes		Title	SEPS	Date	7-11-12			
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			CAO					
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a clime for any states any false, fictitious or fraudulent statements or representations as to any matter	person l	nowingl ts jurisd	y and willfully to make to	any depar	tment or agency of the United			

(Instructions on page 2)

Al 1/17/2012

Accepted for record

OXY USA WTP LP - Proposed Yates Federal #10 API No. 30-015-26255

65sx @ 288'-Surface

17-1/2" hole @ 238' 13-3/8" csg @ 238' w/ 280sx-TOC-Surf-Circ

Perf @ 288'

75sx @ 1267-925' WOC-Tag

12-1/4" hole @ 1217' 9-5/8" csg @ 1217' w/ 900sx-TOC-Surf-Circ

Perf @ 1267'

CIBP @ 3166' w/ 25sx to 2965' WOC-Tag

Perfs @ 3216-3226'

6-1/4" hole @ 3404' 4-1/2" csg @ 3404' w/ 100sx-TOC-2400'-TS

w/ 600sx-TOC-Surf-Circ

8-3/4" hole @ 3107' 7" csg @ 3107'

PB-3349'

TD-3404'

OXY USA WTP LP - Current Yates Federal #10 API No. 30-015-26255

PB-3349'

\_17-1/2"\_hole\_@\_283' 13-3/8" csg @ 238' w/ 280sx-TOC-Surf-Circ 12-1/4" hole @ 1217' 9-5/8" csg @ 1217' w/ 900sx-TOC-Surf-Circ 8-3/4" hole @ 3107' 7" csg @ 3107' w/ 600sx-TOC-Surf-Circ Perfs @ 3216-3226' 6-1/4" hole @ 3404' 4-1/2" csg @ 3404' w/ 100sx-TOC-2400'-TS