Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OMB NO 1004-0135 Expires July 31, 2010

Expires July 31
Lease Serial No
NMNM2748

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals

6 If Indian, Allottee or Tribe Name

abandonea wen. Ose form 0100-0 (Al D) for such proposals.								
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7 If Unit or CA/Agreement, Name and/or No.			
Type of Well ☐ Gas Well ☐ Other					8. Well Name and No GISSLER B 86			
2 Name of Operator BURNETT OIL COMPANY INC	ARVIS		9 API Well No 30-015-40530-00-X1					
3a Address 801 CHERRY STREET UNIT FORT WORTH, TX 76102-68	3b. Phone No (include area code) Ph: 817-332-5108 Ext: 6326			10 Field and Pool, or Exploratory LOCO HILLS				
4 Location of Well (Footage, Sec., T			11 County	y or Parish,	and State			
Sec 11 T17S R30E NWNE 31		EDDY COUNTY, NM						
12. CHECK APPE	ROPRIATE BOX(ES) TO	INDICATE	NATURE OF N	OTICE, RI	EPORT, O	R OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION							
Nation of Intent	☐ Acidize	pen	ion (Start/R	☐ Water Shut-Off				
Notice of Intent			ture Treat	_	Reclamation		☐ Well Integrity	
Subsequent Report Casing Repair		☐ New Construction		_	Recomplete		Other	
Final Abandonment Notice	Change Plans	. \square Plug	g and Abandon	☐ Tempor	arily Aband	lon	Change to Original A PD	
	Convert to Injection	— Plug	Back	□ Water □	r Disposal			
Attach the Bond under which the worfollowing completion of the involved testing has been completed. Final Abdetermined that the site is ready for fit. Burnett Oil is requesting to low to 3100?. This request is due and gas from a drilling break a with volumes adjusted according. Cement Program, as stated in 1. NOTE ** - No change in the 2. 7? Production Casing. Stage 1 Cement. 550 sks VE. Original COA still applies.	operations of the operation resolution ment Notices shall be fill in all inspection of the operation of the	sults in a multipled only after all epth from the ed at 1660?as ogram stated	APD approved on the APD will refer to the AP	depth of 260 influx of wa emain the s	new interval, n, have been no? ter ame Of fector of the control o	REC	60-4 shall be filed once	
Electronic Submission #147658 verified by the BLM Well Informa For BURNETT OIL COMPANY INC, sent to the Carlsba Committed to AFMSS for processing by KURT SIMMONS on 08/28/2012 Name (Printed/Typed) LESLIE M GARVIS Title REGULATORY (2KMS2920	•		
						SAM		
Signature (Electronic Submission)			Date 08/28/2012					
	THIS SPACE FO	OR FEDERA	L OR STATE (OFFICE U	\	2,	8 5015	
Approved By EDWARD FERNANDEZ Conditions of approval, if any, are attached Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject least			Office Carlsbad TitlePETROLEUM ENGINEER BUREAU OF LAND FIELU OF 108/28/2012 PERSON knowingly and willfully to make to any throughout or agency of the United					
which would entitle the applicant to conduct operations thereon.			Office Carlsbac		/ 80	REARL SE		
Title 18 U.S C Section 1001 and Title 43 States any false, fictitious or fraudulent	USC Section 1212, make it a statements or representations as	crime for any pe to any matter w	erson knowingly and ithin its jurisdiction	l willfully to m	ake to any d	Epartment o	or agency of the United	

- Additional data for EC transaction #147658 that would not fit on the form

32. Additional remarks, continued

LAP-1 (FLC) + 0.3 % CFR-3 (Disp) + .025 lb/sk D-Air 5000 + 3 lb/sx Kol-Seal (LC) + 0.125 lb/sk Poly-E-Flake (LC) . 14.2 ppg, Yield 1.28 CF/Sx. DV @ approx. 3200? (adjusted due to Water Flows). 30% excess cement.

Stage 2 Cement. Lead with 525 sks/ ECONOCEM (35.65) Poz (Fly Ash).Class C cement + 6% Bentonite) + .125 lbs/sx Poly-E-Flake (LC) + 2% CaCl, , 12.7 ppg, Yield 1 87 CF/Sx Tail with 100 sx Class C + 2% CaCl. 14 8 ppg, Yield 1.62 CF/sx, TOC Surface 140% excess cement.

The above cement volumes may be revised pending the caliper measurement from the open hole logs. Casing/cementing design is to bring cement to the surface. We will have open hole log caliper volumes to determine cement volumes as accurately as possible.