

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-01199
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator OXY USA Inc.		6. State Oil & Gas Lease No. B-10456
3. Address of Operator P.O. Box 50250 Midland, TX 79710		7. Lease Name or Unit Agreement Name M Y M
4. Well Location Unit Letter <u>N</u> : <u>990</u> feet from the <u>south</u> line and <u>1650</u> feet from the <u>west</u> line Section <u>13</u> Township <u>18S</u> Range <u>27E</u> NMPM County <u>Eddy</u>		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3567'		9. OGRID Number 16696
		10. Pool name or Wildcat Artesia Qn GB SA

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD-2009' OpenHole-1875-2009'

8-5/8" 23# csg @ 385' w/ cmt unknown, 10" hole - Verify Casing in hole
7" 20# csg @ 1875' w/ 50sx, 8" hole, TOC-1541'-Calc

1. Verify 8-5/8" casing in hole
 2. RIH & set CIBP @ 1825' M&P 25sx cmt
 3. Perf @ 1340' sqz 40sx cmt to 1240' WOC-Tag
 3. Perf @ 435' sqz 40sx cmt to 335' WOC-Tag
 4. Perf 7" & 8-5/8" @ 300' sqz 150sx cmt to surface
- 10# MLF between plugs

Notify OCD 24 hrs. prior
To any work done.



Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Regulatory Advisor

DATE

Type or print name

E-mail address: david.stewart@oxy.com

PHONE: 432-685-5717

For State Use Only

APPROVED BY:

TITLE

DATE 10/15/2012

Conditions of Approval (if any):

Approval Granted providing work
is complete by 1/15/2013


OXY USA Inc. - Proposed
M Y M #1
API No. 30-015-01199

150sx @ 300'-Surface

40sx @ 435-335' WOC-Tag

40sx @ 1340-1240' WOC-Tag

CIBP @ 1825' w/ 25sx



10" hole @ 385'
8-5/8" csg @ 385'
Cement Unknown
*Verify csg in hole or cmt surf

Perf 7" & 8-5/8" @ 300'

Perf @ 435'

Perf @ 1340'


8" hole @ 2009'
7" csg @ 1875'
w/ 50sx-TOC-1541'-Calc

OH @ 1875-2009'

TD-2009'

OXY USA, Inc. - Current
M Y/M #1
API No. 30-015-01199

10" hole @ 385'
8-5/8" csg @ 385'
Cement Unknown
*Verify csg in hole or cmt surf



8" hole @ 2009'
7" csg @ 1875'
w/ 50sx-TOC-1541'-Calc

OH @ 1875-2009'

TD-2009'

NEW MEXICO OIL CONSERVATION DIVISION
DISTRICT 2 OFFICE
811 S. FIRST STREET
ARTESIA, NM 88210
(575)748-1283

CONDITIONS OF APPROVAL FOR PLUGGING & ABANDONMENT

Operator: OXY USA Inc.

Well Name & Number: MYM #1

API #: 30-015-01199

1. Produced water **will not** be used during any part of the plugging & abandonment operation.
2. Notify NMOCD Dist. 2 office at least 24 hrs before beginning work.
3. Closed Loop System is to be used for entire plugging operation. Upon completion, contents of steel pit are to be hauled to a permitted disposal location.
4. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator, as well as the contractor, to verify that this permit is place prior to performing work. Drivers shall produce a copy upon request of NMOCD Field Inspectors.
5. A subsequent C-103 will serve as notification that the well bore has been plugged ONLY. A C-103 FINAL shall be filed before any bonding can be released on the well. Upon receipt of the Final, an inspection will be performed to verify that the location has been satisfactorily cleaned to NMOCD standards.
6. If work has not begun within 90 days of the approval of this procedure, an extension request must be filed, stating reason that well has not been plugged.
7. Every attempt must be made to clean the well bore out to below the perms, before any plugs can be set, by whatever means possible.

8. Cement Retainers may not be used.

9. Squeeze pressures not to exceed 500 psi., unless approval is given by NMOCD Plugging Supervisor.

10. Plugs may be combined after consulting with NMOCD P & A Supervisor.

11. Minimum WOC time for tag plugs will be 4 hrs.

DG

Date: 10/15/12