

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-39153
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VO-0228
7. Lease Name or Unit Agreement Name Gopher BRG State
8. Well Number 2
9. OGRID Number 025575
10. Pool name or Wildcat Empire; Glorieta-Yeso

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
Unit Letter N : 330 feet from the South line and 2100 feet from the West line
Section 13 Township 17S Range 28E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3702' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:


REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Production casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/9/12 - Reached TD 7-7/8" hole to 5210' at 2:00 PM. Set 5-1/2" 17# J-55 LT&C casing at 5210'. Float collar at 5166'. Cemented with 590 sx 35:65:6 Poz "C" + 6% bentonite + 0.125#/sx cellophane flakes + 5% salt + 0.25#/sx D46 + 0.2% R1 (yld 2.04, wt 12.6). Tailed in with 350 sx PVL + 5% expanding agent + 0.5% FL control + 1.3% salt + 0.25% D46 + 0.1% D153 + 0.2% D13 (yld 1.48, wt 13). Circulated 165 sx to pit.



Please submit amended with signature 8/10/12

Spud Date:

7/27/12

Rig Release Date:

8/11/12

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Regulatory Reporting Supervisor DATE August 20, 2012

Type or print name Tina Huerta

E-mail address: tinah@yatespetroleum.com

PHONE: 575-748-4168

For State Use Only

APPROVED BY:

TITLE

Dis. Supervisor

DATE

10/12/12

Conditions of Approval (if any):