

Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87401

District IV

1220 S. St. Francis Dr., Santa Fe, NM

87505

Minerals and Natural Resources

June 19, 2008

**RECEIVED**

OCT 05 2012

CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

NM OGD ARTESIA

WELL API NO.

30-015-40553

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name

EDDY-HUMBLE 4 STATE

8. Well Number #1 SWD

9. OGRID Number 281994

10. Pool name or Wildcat

Red Lake, Glorieta-Yeso NE (96836)

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other **SWD-1345**

2. Name of Operator

LRE OPERATING, LLC

3. Address of Operator

c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location

Unit Letter P : 540 feet from the SOUTH line and 837 feet from the EAST lineSection 30 Township 17-S Range 28-E NMPM Eddy County11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3643' GL

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☐CASING/CEMENT JOB ☒OTHER: Intermediate & Production Casings ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Drilled 8-3/4" hole to 6805' on 9/18/12. Ran open hole logs. Landed 7" 26# L-80 csg @ 6804'. Cmted lead w/310 sx (654 cf) "H" cmt w/0.2% FL52, 5% MPA-5, 0.1% SMS, 5% salt, 5# LCM-1 & 0.125# CF. Tailed w/500 sx (590 cf) "H" w/0.2% FL52 & 1% salt. Did not Circ cmt to surface. Temp survey indicated TOC @ 1300'. On 9/21/12, PT 7" csg to 864 psi for 30 min-OK.

Drilled 6-1/8" hole to 9000' on 9/28/12. Ran open hole logs. Landed 4-1/2" 11.6# L-80 csg @ 8996' w/liner hanger @ 6692'. Cmted lead w/300 sx (399 cf) "H" cmt w/0.5% FL-52, 0.2% CD-32, 0.3% SMS, 3% salt, & 0.35% R-3. Did not Circ cmt to surface. On 10/2/12, ran temp survey which indicated TOC @ 500'.

Spud Date: 8/23/12

Drilling Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 10/3/12Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: AL Wade TITLE District Supervisor DATE 10/16/12

Conditions of Approval (if any):