

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-40572
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Zircon 2 EH State
8. Well Number 1H
9. OGRID Number 14744
10. Pool name or Wildcat Santo Nino; Bone Spring 54600

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Mewbourne Oil Company	
3. Address of Operator PO Box 5270 Hobbs, NM 88241	
4. Well Location Unit Letter <u>E</u> : 1980 feet from the <u>North</u> line and <u>150</u> feet from the <u>West</u> line Section <u>2</u> Township <u>19S</u> Range <u>29E</u> NMPM Eddy County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3403 GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐


OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/11/12..TD'ed 12 1/4" hole @ 1304'. Ran 1304' 9 3/8" 36# J55 LT&C Csg. Cemented with 350 sks BJ Lite Class C (35:65:6) w/additives. Mixed @ 12.5 /g w/ 2.10 yd. Plug down @ 6:30 P.M. 10/11/12. Had full returns. Did not circ cmt. Ran in hole & tagged TOC @ 1210'. 1" in 2 stages w/200 sks Class C w/1% CaCl2 & 168 sks Class C Neat. Mixed @ 14.8/g w/1.34 yd. Circ 15 sks of cmt to the pit. WOC 18 hrs. At 12:15 A.M. 10/13/12, tested BOPE & csg to 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

Spud Date: 10/07/2012

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 10/15/12

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: RP Dade TITLE Dist # Supervisor DATE 10/30/12

Conditions of Approval (if any):