Form 3160-5 (April 2004)

N.M. Oli Cons. DIV-Dist. 2 united states 1301 VV. Grand Avenue

FORM APPROVED OMB No. 1004-0135

BUREAU OF LAND MANAGEMENT AMESIA, NM 8821	Expires March 31, 2007
SUNDRY NOTICES AND REPORTS ON WELLS **********************************	5. Lease Serial No. NM-53219 and the new powerfalseform the progress
abandoned well. Use Form 3160-3 (APD) for such proposals.	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE - Other instructions on reverse side	7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well	NM-112743
Oil Well X Gas Well Other	8. Well Name and No.
2. Name of Operator	Whitbread BFG Federal Com #1
Yates Petroleum Corporation	9. API Well No.
3b. Phone No. (include area code) 105 S. 4th Str., Artesia, NM 88210 3b. Phone No. (include area code) 505-748-RECEIVED	30-015-33932
	10. Field and Pool, or Exploratory Area
4. Location of Well (Pootage, Sec., T.,R.,M., OR Survey Description)	Indian Basin Upper Penn Assoc. 11. County or Parish, State
ACCOLENIA & COOLENIA - & Continue A TOOC POAR (LISTER CLAVALIA)	
1980'FNL & 660'FWL of Section 1-T22S-R24E (Unit E, SWNW)	Eddy County, New Mexico
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, R	CEPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	1
Acidize Deepen Production	n (Start/Resume) Water Shut-Off
Notice of Intent Alter Casing Fracture Treat Reclamatic	on Well Integrity
Casing Repair New Construction Recomple	X Other Intermediate
X Subsequent Report Recomple	Other Intermediate
Change Plans Plug and Abandon Temporar	rly Abandon Casing
Final Abandonment Notice Convert to Injection Plug Back Water Dis	
	approximate duration thereof. I pertinent markers and zones.
13. Describe Proposed of Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and if the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports of following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a For testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been condetermined that the site is ready for final inspection.) 4/17/05 Set 7" 26# L-80 J-55 casing at 8800'. Float collar at 8756'. Cemented Stage + 10% A10B + 1/4# sx Celloflake + 5#/sx Gilsonite. Tailed in with 250 sx Su + 6/10% FL-25 + 6/10% FL-52 + 5/10% BA-10 (yld 1.61, wt 13.2). Stage 2 v + 1/4#/sx Celloflake + 5#/sx Gilsonite + 5/10% FL-52 (yld 1.97, wt 12.5). Ta 1.18, wt 15.6). Tested casing to 1500 psi for 30 min. WOC 59 hrs 30 min. resumed drilling. ACCEF	approximate duration thereof. I pertinent markers and zones. shall be filled within 30 days. m 3160-4 shall be filed once mpleted, and the operator has e 1 with 100 sx Thixad Class "H" uper "C" 15:61:11 + 5#/sx Gilsonite with 1175 sx 35:65:6 "C" + 1% Salt illed in with 100 sx "H" Neat (yld Reduced hole to 6-1/8" and PTED FOR RECORD APR 2 8 2005
13. Describe Proposed of Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports s following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a For testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been condetermined that the site is ready for final inspection.) 4/17/05 Set 7" 26# L-80 J-55 casing at 8800'. Float collar at 8756'. Cemented Stage + 10% A10B + 1/4# sx Celloflake + 5#/sx Gilsonite. Tailed in with 250 sx Su + 6/10% FL-25 + 6/10% FL-52 + 5/10% BA-10 (yld 1.61, wt 13.2). Stage 2 v + 1/4#/sx Celloflake + 5#/sx Gilsonite + 5/10% FL-52 (yld 1.97, wt 12.5). Ta 1.18, wt 15.6). Tested casing to 1500 psi for 30 min. WOC 59 hrs 30 min. resumed drilling. ACCEF	approximate duration thereof. I pertinent markers and zones. shall be filed within 30 days. m 3160-4 shall be filed once mpleted, and the operator has e 1 with 100 sx Thixad Class "H" uper "C" 15:61:11 + 5#/sx Gilsonite with 1175 sx 35:65:6 "C" + 1% Salt illed in with 100 sx "H" Neat (yld Reduced hole to 6-1/8" and PTED FOR RECORD APR 2 8 2005 EXIS C. SWOBODA
13. Describe Proposed of Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports s following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a For testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been condetermined that the site is ready for final inspection.) 4/17/05 Set 7" 26# L-80 J-55 casing at 8800'. Float collar at 8756'. Cemented Stage + 10% A10B + 1/4# sx Celloflake + 5#/sx Gilsonite. Tailed in with 250 sx Su + 6/10% FL-25 + 6/10% FL-52 + 5/10% BA-10 (yld 1.61, wt 13.2). Stage 2 v + 1/4#/sx Celloflake + 5#/sx Gilsonite + 5/10% FL-52 (yld 1.97, wt 12.5). Ta 1.18, wt 15.6). Tested casing to 1500 psi for 30 min. WOC 59 hrs 30 min. resumed drilling. ACCEF Name (Printed/Typed)	approximate duration thereof. Il pertinent markers and zones. shall be filed within 30 days. m 3160-4 shall be filed once mpleted, and the operator has e 1 with 100 sx Thixad Class "H" uper "C" 15:61:11 + 5#/sx Gilsonite with 1175 sx 35:65:6 "C" + 1% Salt iiled in with 100 sx "H" Neat (yld Reduced hole to 6-1/8" and PTED FOR RECORD APR 2 8 2005 EXIS C. SWOBODA ROLEUM ENGINEER
13. Describe Proposed of Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports s following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a For testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been condetermined that the site is ready for final inspection.) 4/17/05 Set 7" 26# L-80 J-55 casing at 8800'. Float collar at 8756'. Cemented Stage + 10% A10B + 1/4# sx Celloflake + 5#/sx Gilsonite. Tailed in with 250 sx Su + 6/10% FL-25 + 6/10% FL-52 + 5/10% BA-10 (yld 1.61, wt 13.2). Stage 2 v + 1/4#/sx Celloflake + 5#/sx Gilsonite + 5/10% FL-52 (yld 1.97, wt 12.5). Ta 1.18, wt 15.6). Tested casing to 1500 psi for 30 min. WOC 59 hrs 30 min. resumed drilling. ACCEF	approximate duration thereof. Il pertinent markers and zones. shall be filed within 30 days. m 3160-4 shall be filed once mpleted, and the operator has e 1 with 100 sx Thixad Class "H" uper "C" 15:61:11 + 5#/sx Gilsonite with 1175 sx 35:65:6 "C" + 1% Salt iiled in with 100 sx "H" Neat (yld Reduced hole to 6-1/8" and PTED FOR RECORD APR 2 8 2005 EXIS C. SWOBODA ROLEUM ENGINEER
13. Describe Proposed of Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports s following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a For testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been condetermined that the site is ready for final inspection.) 4/17/05 Set 7" 26# L-80 J-55 casing at 8800'. Float collar at 8756'. Cemented Stage + 10% A10B + 1/4# sx Celloflake + 5#/sx Gilsonite. Tailed in with 250 sx Su + 6/10% FL-25 + 6/10% FL-52 + 5/10% BA-10 (yld 1.61, wt 13.2). Stage 2 v + 1/4#/sx Celloflake + 5#/sx Gilsonite + 5/10% FL-52 (yld 1.97, wt 12.5). Ta 1.18, wt 15.6). Tested casing to 1500 psi for 30 min. WOC 59 hrs 30 min. resumed drilling. ACCEF Name (Printed/Typed)	approximate duration thereof. Il pertinent markers and zones. shall be filed within 30 days. m 3160-4 shall be filed once mpleted, and the operator has e 1 with 100 sx Thixad Class "H" uper "C" 15:61:11 + 5#/sx Gilsonite with 1175 sx 35:65:6 "C" + 1% Salt iiled in with 100 sx "H" Neat (yld Reduced hole to 6-1/8" and PTED FOR RECORD APR 2 8 2005 EXIS C. SWOBODA ROLEUM ENGINEER
I3. Describe Proposed of Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all Attach the Bond under which the work will be performed or provide the Bond No. on file with BLMBIA. Required subsequent reports of following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a For testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been condetermined that the site is ready for final inspection.) 4/17/05 Set 7" 26# L-80 J-55 casing at 8800'. Float collar at 8756'. Cemented Stage + 10% A10B + 1/4# sx Celloflake + 5#/sx Gilsonite. Tailed in with 250 sx Su + 6/10% FL-25 + 6/10% FL-52 + 5/10% BA-10 (yld 1.61, wt 13.2). Stage 2 v + 1/4#/sx Celloflake + 5#/sx Gilsonite + 5/10% FL-52 (yld 1.97, wt 12.5). Ta 1.18, wt 15.6). Tested casing to 1500 psi for 30 min. WOC 59 hrs 30 min. resumed drilling. ACCEF Title Regulatory Complete	approximate duration thereof. Il pertinent markers and zones. shall be filed within 30 days. m 3160-4 shall be filed once mpleted, and the operator has e 1 with 100 sx Thixad Class "H" uper "C" 15:61:11 + 5#/sx Gilsonite with 1175 sx 35:65:6 "C" + 1% Salt iiled in with 100 sx "H" Neat (yld Reduced hole to 6-1/8" and PTED FOR RECORD APR 2 8 2005 EXIS C. SWOBODA ROLEUM ENGINEER
13. Describe Proposed of Completed Operation (clearly state all perlinent details, including estimated starting date of any proposed work and if the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports of following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a For testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been condetermined that the site is ready for final inspection.) 4/17/05 Set 7" 26# L-80 J-55 casing at 8800'. Float collar at 8756'. Cemented Stage + 10% A10B + 1/4# sx Celloflake + 5#/sx Gilsonite. Tailed in with 250 sx Su + 6/10% FL-25 + 6/10% FL-52 + 5/10% BA-10 (yld 1.61, wt 13.2). Stage 2 v + 1/4#/sx Celloflake + 5#/sx Gilsonite + 5/10% FL-52 (yld 1.97, wt 12.5). Ta 1.18, wt 15.6). Tested casing to 1500 psi for 30 min. WOC 59 hrs 30 min. resumed drilling. ACCEF 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Tina Huerta Title Regulatory Compile Pate April 5, 2005	approximate duration thereof. Il pertinent markers and zones. shall be filed within 30 days. m 3160-4 shall be filed once mpleted, and the operator has e 1 with 100 sx Thixad Class "H" uper "C" 15:61:11 + 5#/sx Gilsonite with 1175 sx 35:65:6 "C" + 1% Salt iiled in with 100 sx "H" Neat (yld Reduced hole to 6-1/8" and PTED FOR RECORD APR 2 8 2005 EXIS C. SWOBODA ROLEUM ENGINEER

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willbully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction