

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS FOR WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM APPROVED
Budget Bureau No. 1004-0135
Expires November 30 2000

5. Lease Serial No.

NMWL01108

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.

WEST BRUSHY 8 FED 2

9. API Well No.

30-015-31866

10. Field and Pool, or Exploratory Area

BRUSHY DRAW (DELAWARE)

11. County or Parish, State

EDDY NM

SUBMIT IN TRIPLICATE - Other instructions on reverse side

RECEIVED

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

BP AMERICA PRODUCTION COMPANY

3a. Address

P.O. BOX 3092, RM 6.115, HOUSTON, TX 77253

3b. Phone No. (include area code)

281-366-2052

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

S8-26S-29E; 1750' FNL & 990' FEL; NW-SE-NE

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Acidize ☐ Deepen ☐ Production (Start/Resume) ☐ Water Shut-Off
☐ Alter Casing ☐ Fracture Treat ☐ Reclamation ☐ Well Integrity
☐ Casing Repair ☐ New Construction ☐ Recomplete ☐ Other
☐ Change Plans ☒ Plug and Abandon ☐ Temporarily Abandon
☐ Convert to Injection ☐ Plug Back ☐ Water Disposal

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

MAY 20 - JUNE 3, 2005 - PLUG AND ABANDON WELLBORE - SET CIBP @ 5160' APPROX, DUMP 10 SKS OF CEMENT ON TOP; CIRCULATE THE HOLE WITH 9.5# P&A MUD; PULL OUT OF HOLE LD TUBING TO 2850'; PERFORATE 5 1/2" CASING @ 2950'; SET TREATING PACKER @ 2600', ESTABLISH INJECTION RATE INTO PERFS; PUMP 50 SKS CEMENT AND DISPLACE TO 2800'; TAG CEMENT @ 2850'; PULL OUT OF HOLE LD TUBING TO 531'; PERFORATE 5 1/2" CASING @ 631, ESTABLISH INJECTION RATE INTO PERFS; PUMP 50 SKS CEMENT DOWN THE 5 1/2" CASING; DISPLACE CEMENT TO 480'; TAG CEMENT @ 531'; PULL OUT OF HOLE LD TUBING; PUMP 25 SKS CEMENT DOWN 5 1/2" TAKING RETURNS FROM THE 8 5/8" CASING, DISPLACE CEMENT TILL GET RETURNS FROM 8 5/8" AT THE SURFACE, LEAVE CEMENT INSIDE 5 1/2" AT THE SURFACE; INSTALL SURFACE MARKER, REMOVE FLOWLINE CONNECTIONS, PUMPING TEE, TUBING ANCHOR, & WELLHEAD; FILL CELLAR AND CLEAN LOCATION.

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS ATTACHED

Accepted for record - NMOCD

APPROVED

MAY 18 2005

LES BABYAK
PETROLEUM ENGINEER14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

SUE SELLERS

Title

REGULATORY STAFF ASSISTANT

Date MAY 5, 2005

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

RKB 2938'
GL 2927'

API # 30 015 31866

Spud: 7/10/01
Comp 10/1/01

WEST BRUSHY FEDERAL "8" # 2
Brushy Draw (Delaware)
1750' FNL & 990' FEL, Sect 8
T-26-S, R-29E
Eddy County, New Mexico

Top squeezed 5 1/2" x 8 5/8" w/ 100 sx
TOC @ 210' by CBL

8 5/8", 24#, J-55, ST&C @ 581'
Cmt w/ 470 sx to surface

WELLBORE INFO CURRENT AS OF 10/1/01

TOC @ 3870'

2 7/8", 6.5#, J-55 EUE 8rd tbg @ 5330'
76 rod string

TAC @ 5175'

5212-5310' 30 shots

5486-5514' 29 shots

5 1/2", 15.5#, J-55 LT&C @ 5575'
Cmt w/ 1250 sx
TOC @ 3870' by CBL

TD: 5575'
PBD: 5567'

DLT 4/20/05