Form 3160-5 (September 2001)

UNITED STATES. N. OII CONS. DIV-DISI 2 FORM OMB N Expires: J

FORM APPROVED OMB No. 1004-0135 Expires: January 31, 2004

SUNDRY NOTICES AND REPORTS OF DELLS NOTICES A

NM-89880 6. If Indian, Allottee or Tribe Name

Title

Date

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 08/12/05MI & spud 17 ½" hole. TD'd hole @ 721'. Ran 735' 13 3/8" 48# H40 ST&C csg. Cemented with 400 sks BJ Lite Class C with additives. Mixed @ 12.5 #/g w/ 1.98 yd. Tail with 200 sks Class C with 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circ 117 sks to pit. WOC 18 hrs. At 11:30 pm on 08/13/05, tested BOPE and casing to 1250# for 30 minutes, held OK. Drilled out with 12 ½" bit. 08/16/05TD'ed 12 ½" hole @ 2172'. Ran 2172' 8 5/8" 32# J55 ST&C Csg. Cemented with 600 sks BJ Lite C with additives. Mixed @ 12.5 /g w/ 1.96 yd. Tail with 400 sks Class "C" with 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circ 89 sks to pit. WOC 18 hrs. At 3:00 am on 08/17/05, tested BOPE and casing to 2000# for 30 minutes, held OK. Drilled out with 7 7/8" bit. ACCEPTED FOR RECORD AUG 2 3 2005 ALEXIS C. SWOBODA PETROLEUM ENGINEER Title Hobbs Regulatory									
2. Name of Operator 2. Name of Operator 3. Address 3. Address 3. Address 405-24-2005 3. Address 505-393-5905 41. Location of Well (Pootage, Sec., T. R. M., or Survey Description) 660° FSL & 1175′ FWL Unit M Sec 10-T18S-R31E 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION 13. Address 14. In Production (Start/Resume) 14. In Abandonment Notice 15. In Computer of Notice of Intent 15. Subsequent Report 16. Change Plans 17. Plug and Abandon Temporarity Abandon 17. Computed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof the proposed is to depen directionally or recomplete horizontally, give absurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLMBIA. Required subsequent reports and before the proposed is to depen directionally or recomplete horizontally is recomplete borizontally in compute borizontally is use absurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLMBIA. Required subsequent reports shall be filled only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 08/12/05MI & spud 17 ½″ hole. DTd hole @ 721′. Ran 735′ 13 3/8″ 48# H40 ST&C csg. Cemented with 400 sks BJ Lite Class C with additives. Mixed @ 12.5 ½g wl 1.98 yd. Tail with 400 sks Class "C" with 2% CaCl2. Mixed @ 14.8 ½g wl 1.34 yd. Circ 117 sks to pit. WOC 18 hrs. At 11:30 pm on 08/13/05, tested BOPE and casing to 1250# for 30 minutes, held OK. Drilled out with 12 ½″ bit. ALEXIS C. SWOSGODA PETROLEUM ENGINEER 16. Helbobs Regulatory	SUBMIT IN TRIPLICATE - Other Instructions on reverse side					7. If Unit or CA/Agreement, Name and/or No.			
2. Name of Operator 2. Name of Operator 3. Address 3. Address 3. Address 3. Address 405-24-2005 3. Address 505-393-5905 505-393-5905 505-393-5905 11. County of Parish, State 660' FSL & 1175' FWL Unit M Sec 10-T18S-R31E 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION 13. Address 14. Address 15. Subsequent Report 16. Change Plans 17. Final Abandonment Notice 19. Deepen Production (Start/Resume) 19. Back 10. Back 1	1. Type of Well					34108			
2. Name of Operator Mewbourne Oil Company 14744 3a. Address 3b. Phone No. (In Control 14 Control 1	**	F							
3a. Address Sh. Phone No. (Interpretable) 30-015-34239			Tamano 10 Fed Com #5						
Does 5270 Hobbs, NM 88240 505-393-5905 10. Field and Pool, or Exploratory Area Book Spring 11. County or Parish, State Eddy County, NM 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Walt Integrity New Construction Recomplete Walt Integrity Other Spud & Csg	Mewbourne Oil Company 14744				9. API Well No.				
Bone Spring 11. Country or Parish, State Good FSL & 1175 FWL Unit M Sec 10-T18S-R31E Eddy Country, NM	3a. Address								
11. County or Parish, State Eddy County, NM 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent	PO Box 5270 Hobbs, NM 88240				10. Field and Pool, or Exploratory Area				
Eddy County, NM									
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Acidize	660' FSL & 1175' FWL Unit I								
TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent	12 CHECK ADDDODDIATE DOV(ES) TO INDICATE NATIDE OF NOTICE I								
Acidize Deepen Production (Start/Resume) Water Shut-Off Notice of Intent Alter Casing Fracture Treat Reclamation Well Integrity Other Spud & Csg Other Spud & Csg Pinal Abandonment Notice Casing Repair New Construction Recomplete Temporarily Abandon Temporarily Aband		PROPRIATE BOX(ES) TO			SFORT, C	K OIIIL	IN DATA		
Notice of Intent	TYPE OF SUBMISSION								
Subsequent Report Casing Repair New Construction Recomplete Other Spud & Csg		Acidize [Deepen	Production (Start	/Resume)	☐ Wa	ter Shut-Off		
Subsequent Report Change Plans Plug and Abandon Temporarily	Notice of Intent	Alter Casing	Fracture Treat	Reclamation		☐ We	ll Integrity		
Change Plans Plug and Abandon Temporarily Abandon Convert to Injection Plug Back Water Disposal	Subsequent Penest	Casing Repair	New Construction	Recomplete		☑ Oth	er Spud & Csg		
3. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof if the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLMBIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 08/12/05MI & spud 17 ½" hole. TD'd hole @ 721. Ran 735' 13 3/8" 48# H40 ST&C csg. Cemented with 400 sks BJ Lite Class C with additives. Mixed @ 12.5 ½g w/ 1.98 yd. Tail with 200 sks Class C with 2% CaCl2. Mixed @ 14.8 ½g w/ 1.34 yd. Circ 117 sks to pit. WOC 18 hrs. At 11:30 pm on 08/13/05, tested BOPE and casing to 1250# for 30 minutes, held OK. Drilled out with 12 ½" bit. 08/16/05TD'ed 12 ½" hole @ 2172'. Ran 2172' 8 5/8" 32# J55 ST&C Csg. Cemented with 600 sks BJ Lite C with additives. Mixed @ 12.5 /g w/ 1.96 yd. Tail with 400 sks Class "C" with 2% CaCl2. Mixed @ 14.8 #g w/ 1.34 yd. Circ 89 sks to pit. WOC 18 hrs. At 3:00 am on 08/17/05, tested BOPE and casing to 2000# for 30 minutes, held OK. Drilled out with 7 7/8" bit. ACCEPTED FOR RECORD ALEXIS C. SWOBODA PETROLEUM ENGINEER Title Hobbs Regulatory		Change Plans	Plug and Abandon	Temporarily Aba					
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 08/12/05MI & spud 17 ½" hole. TD'd hole @ 721'. Ran 735' 13 3/8" 48# H40 ST&C csg. Cemented with 400 sks BJ Lite Class C with additives. Mixed @ 12.5 #g w/ 1.98 yd. Tail with 200 sks Class C with 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circ 117 sks to pit. WOC 18 hrs. At 11:30 pm on 08/13/05, tested BOPE and casing to 1250# for 30 minutes, held OK. Drilled out with 12 ½" bit. 08/16/05TD'ed 12 ½" hole @ 2172'. Ran 2172' 8 5/8" 32# J55 ST&C Csg. Cemented with 600 sks BJ Lite C with additives. Mixed @ 12.5 /g w/ 1.96 yd. Tail with 400 sks Class "C" with 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circ 89 sks to pit. WOC 18 hrs. At 3:00 am on 08/17/05, tested BOPE and casing to 2000# for 30 minutes, held OK. Drilled out with 7 7/8" bit. ACCEPTED FOR RECORD ALEXIS C. SWOBODA PETROLEUM ENGINEER Title Hobbs Regulatory Title Hobbs Regulatory	Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal					
14. 1 hereby certify that the foregoing is true and correct Name (PrintedITyped) Kristi Green Title Hobbs Regulatory	08/12/05MI & spud 17 ½" hole Mixed @ 12.5 #/g w/ At 11:30 pm on 08/13 08/16/05TD'ed 12 ¼" hole @ 2 yd. Tail with 400 sks of	for final inspection.) e. TD'd hole @ 721'. Ran 735' 1.98 yd. Tail with 200 sks Clas /05, tested BOPE and casing to 172'. Ran 2172' 8 5/8" 32# J55 Class "C" with 2% CaCl2. Mix	13 3/8" 48# H40 ST&6 s C with 2% CaCl2. M 1250# for 30 minutes, ST&C Csg. Cemented @ 14.8 #/g w/ 1.34	C csg. Cemented with fixed @ 14.8 #/g w/ 1 held OK. Drilled out with 600 sks BJ Lite yd. Circ 89 sks to pit. 7 7/8" bit.	400 sks B. 34 yd. Cir with 12 ¼" C with add WOC 18	J Lite Classe 117 sks bit. litives. Mhrs. At 3:	is C with additive to pit. WOC 18 ixed @ 12.5 /g v 00 am on 08/17/0	es. hrs. w/ 1.96	
Signature Duite: along	Name (PrintedlTyped)	ig is true and correct	Title Hol	bbs Regulatory	ALEX	IS C. SW	OBODA		
V 2/4/1/A-4 V 1/24 - 1 Daw 10/17/105	Signature Sujt	Green	Date on	17/05					

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Name

(Printed/Typed) Office

Approved by (Signature)

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.