




Job Number: S12-127
 Company: Burnett Oil & Gas
 Lease/Well: Gissler B # 86
 Location: Eddy County
 Rig Name: United Drilling # 29
 RKB: N/A
 G.L. or M.S.L.: N/A

State/Country: New Mexico / USA
 Declination: 7.45° Corrected To Grid
 Grid: 7.45°
 File name: C:\WINSERVE\DOCS\S12-127.SVY
 Date/Time: 14-Sep-12 / 08:01
 Curve Name: MWD SERVICES RAN ON 8-27-12

Stryker Energy Directional Services, LLC.

WINSERVE SURVEY CALCULATIONS
 Minimum Curvature Method
 Vertical Section Plane 95.25
 Vertical Section Referenced to Wellhead
 Rectangular Coordinates Referenced to Wellhead



Need Certification

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE Distance FT	Direction Deg	Dogleg Severity Deg/100
Tie-In Data Provided by Customer									
4182.00	.40	178.60	4181.63	-22.95	39.45	41.38	45.64	120.19	.00
4257.00	1.30	95.60	4256.62	-23.29	40.30	42.27	46.55	120.03	1.75
4320.00	3.10	87.50	4319.57	-23.29	42.72	44.67	48.65	118.60	2.89
4383.00	4.60	90.90	4382.43	-23.26	46.94	48.88	52.39	116.35	2.41
4446.00	4.90	91.70	4445.21	-23.38	52.16	54.08	57.16	114.14	.49
4509.00	5.00	90.90	4507.98	-23.50	57.59	59.50	62.20	112.20	.19
4572.00	5.30	96.60	4570.72	-23.88	63.23	65.15	67.59	110.69	.94
4635.00	5.20	98.20	4633.46	-24.62	68.95	70.91	73.21	109.65	.28
4705.00	4.60	88.10	4703.21	-24.98	74.89	76.86	78.95	108.44	1.50
4800.00	4.70	87.10	4797.89	-24.65	82.59	84.50	86.19	106.62	.14
4862.00	4.40	89.50	4859.70	-24.50	87.50	89.38	90.87	105.64	.57
4957.00	4.50	91.70	4954.41	-24.58	94.87	96.72	98.00	104.53	.21
5020.00	4.20	90.30	5017.23	-24.67	99.65	101.49	102.66	103.90	.51
5115.00	4.10	88.30	5111.98	-24.59	106.52	108.32	109.32	103.00	.19
5210.00	4.30	89.60	5206.73	-24.46	113.48	115.24	116.08	102.16	.23
5302.00	4.10	80.00	5298.48	-23.86	120.16	121.84	122.51	101.23	.79
5397.00	4.10	82.90	5393.24	-22.86	126.88	128.44	128.92	100.21	.22
5492.00	4.20	83.30	5487.99	-22.03	133.70	135.16	135.51	99.36	.11
5586.00	4.10	85.10	5581.74	-21.34	140.47	141.83	142.08	98.64	.17
5680.00	4.10	86.40	5675.50	-20.84	147.17	148.46	148.64	98.06	.10
5775.00	4.10	82.20	5770.26	-20.17	153.93	155.13	155.24	97.46	.32
5869.00	4.20	83.50	5864.01	-19.32	160.68	161.77	161.83	96.86	.15
5964.00	4.00	84.70	5958.77	-18.62	167.43	168.43	168.47	96.35	.23
6041.00	3.90	86.80	6035.58	-18.23	172.72	173.66	173.68	96.02	.23

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
Projection to Bit									
6088.00	3.90	86.80	6082.48	-18.05	175.91	176.83	176.84	95.86	.00