

Submit 1 Copy To Appropriate District Office  
 District I - (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II - (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III - (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV - (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 Revised August 1, 2011

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO. 30-015-38292
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name RDX 16
8. Well Number 10H
9. OGRID Number 246289
10. Pool name or Wildcat Wildcat (Bone Spring)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3094 feet GR

SUNDRY NOTICES AND REPORTS ON WELLS  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well  Gas Well  Other

2. Name of Operator  
RKI Exploration & Production, LLC

3. Address of Operator  
210 Park Avenue, Suite 900, Oklahoma City, OK 73102

4. Well Location  
 Unit Letter B : 330 feet from the North line and 2110 feet from the East line  
 Section 16 Township 26S Range 30E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK  PLUG AND ABANDON   
 TEMPORARILY ABANDON  CHANGE PLANS   
 PULL OR ALTER CASING  MULTIPLE COMPL   
 DOWNHOLE COMMINGLE

SUBSEQUENT REPORT OF:

REMEDIAL WORK  ALTERING CASING   
 COMMENCE DRILLING OPNS.  P AND A   
 CASING/CEMENT JOB

OTHER:

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 9/22/2012, drilled 12-1/4 inch hole to 3,520 feet. Ran 83 joints of 9-5/8 inch 40# J-55 LTC casing with FS @ 3,520 feet. FC @ 3,435 feet.

Cementing:

Lead: 850 sks of Pozmix (35/65 POZ/C+5%PF44(BWOW)+6%PF42+0.125#/SKPF29+0.25#/SKPF46+1%PF1) Yield = 2.07, Density = 12.6 ppg.


Tail: 200 sks of Class C (C+0.2%PF13) Density = 14.8 ppg, yield = 1.33

Circulated 100 bbls/271 sks to surface. On 9/23/2012, tested intermediate casing to 1500 psi = OK

Drilled out cement 21.5 hours after cementing

Spud Date: 9/17/2012

Rig Release Date: 10/09/2012



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Charles K. Ahn TITLE EH&S/Regulatory Manager DATE 2/12/2013

Type or print name Charles K. Ahn E-mail address: cahn@rkixp.com PHONE: 405-996-5771

For State Use Only

APPROVED BY: [Signature] TITLE Dir. of SEP DATE 2/14/13

Conditions of Approval (if any):