

Reservoir Development
Drilling & Measurements (Extreme Engineering)
6724 Corporation Pkwy Suite 100
Fort Worth, TX 76126
Phone: (817) 717-1820
Fax: (817) 546-7551

June 18, 2013

Occidental Permian Ltd
5 Greenway Plaza Suite 110
Houston, Texas 77046

Attention: Anthony Tschacher

Re:

CLIENT: OXY
WELL: Roo 22 State 15
FIELD: YESO
RIG: Savanna 415
COUNTY: Eddy
API NO: 30-015-40856
JOB NO: Nm-OXY-0074

Enclosed, please find the original copy of the survey performed on the referenced well by Drilling & Measurements (formerly Extreme), a division of Schlumberger Technology Corporation (P-5 No. 754900). Other information required by your office is as follows.


<u>Name & Title of Surveyor</u>	<u>Drainhole Number</u>	<u>Surveyed Depths</u>	<u>Dates Performed</u>	<u>Type of Survey</u>
Troy Miller FST-1	Roo 22 State 15 Original Hole	170.00 Ft to 4903.00 Ft	June 14, 2013 to June 17, 2013	SlimPulse

A plat of the bottom hole location is oriented both to the surface location and to the lease lines (or until line in case of pooling), is attached to the survey report.

If any other information is required, please contact the undersigned at the above letterhead and phone number.
Sincerely,

Joseph Stewart
Field Service Manager

CC: OXY
Enclosures: [2]
County of Eddy
State of New Mexico



Reservoir Development

Drilling & Measurements (Extreme Engineering)

6724 Corporation Pkwy Suite 100

Fort Worth, TX 76126

Phone: (817) 717-1820


Fax: (817) 546-7551


I, Troy Miller certify that, I am employed by Drilling & Measurements (formerly Extreme), a division of Schlumberger Technology Corporation; that I did on the day(s) of June 14, 2013 through June 17, 2013, conduct or supervise the taking of the SlimPulse surveys from a depth of 170.00 feet to a depth of 4903.00 feet; that the data is true, correct, complete and within the limitations of the tool as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I am authorized and qualified to report; that this survey was conducted at the request of OXY for the Roo 22 State 15 Well (Original Hole) API No. 50-015-40030 in New Mexico; and that I have reviewed this report and find that it conforms to the principals and procedures as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation.


Troy Miller
FST-1

Before me, Jaclyn D. Fre on this day personally appeared Troy Diane Miller known to me to be the person whose name is subscribed to the foregoing instrument and acknowledged to me that he/she executed the same for the purposes and consideration therein expressed.

Given under my hand and seal of office this 19th day of June, 2013 (year)


Notary Public
my Commission expires
July 18, 2015



Roo 22 State 15 MWD 0' to 4903' Survey Report

(Def. Survey)

Report Date: June 17, 2013 - 04:51 PM
 Client: OXY
 Field: NM, Eddy (NAD27) 2011
 Structure / Slot: OXY (Roo 22 State 15) Savanna 415 / Roo 22 State 15
 Well: Roo 22 State 15
 Borehole: Original Hole
 UWI / API#: Unknown / 30-015-40896
 Survey Name: Roo 22 State 15 MWD 0' to 4903'
 Survey Date: June 17, 2013
 Tool / AHD / DDI / ERD Ratio: 15.675 / 55.671 R / 2.941 / 0.011
 Coordinate Reference System: NAD27 New Mexico State Plane, Eastern Zone, US Feet
 Location Lat / Long: N 32° 49' 14.16000", W 104° 10' 11.64000"
 Location Grid N/E Y/X: N 662284.179 RUS, E 550207.106 IUS
 CRS Grid Convergence Angle: 0.08858274°
 Grid Scale Factor: 0.99991198

Survey / DLS Computation: Minimum Curvature / Lubinski
 Vertical Section Azimuth: 0.000° (Grid North)
 Vertical Section Origin: 0.000 R, 0.000 I
 TVD Reference Datum: RKB
 TVD Reference Elevation: 3593.000 ft above MSL
 Seabed / Ground Elevation: 3579.000 ft above MSL
 Magnetic Declination: 7.854°
 Total Field Strength: 48707.897 nT
 Magnetic Dip Angle: 60.585°
 Declination Date: June 17, 2013
 Magnetic Declination Model: IGRF2010/GRF-11
 North Reference: Grid North
 Grid Convergence Used: 0.089°
 Total Corr Mag North-Grid North: 7.765°
 Local Coord Referenced To: Well Head

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (ft/100ft)	Northing (RUS)	Easting (IUS)	Latitude (N/S)	Longitude (E/W)
Surface	0.00	0.00	0.00	0.00	0.00	0.00	0.00	N/A	662284.18	550207.11	N 32° 49' 14.16"	W 104° 10' 11.64"
Begin MWD Surveys	170.00	0.62	345.20	170.00	0.89	0.89	-0.22	0.38	662285.07	550208.89	N 32° 49' 14.17"	W 104° 10' 11.64"
	304.00	1.10	20.94	303.98	2.80	2.80	0.07	0.51	662286.98	550207.17	N 32° 49' 14.19"	W 104° 10' 11.64"
	410.00	1.49	84.75	409.96	3.88	3.88	1.80	1.33	662288.05	550208.01	N 32° 49' 14.20"	W 104° 10' 11.62"
	497.00	1.19	87.34	496.94	4.02	4.02	3.83	0.35	662288.20	550210.94	N 32° 49' 14.20"	W 104° 10' 11.60"
	527.00	1.01	79.87	526.93	4.08	4.08	-4.40	0.77	662288.26	550211.51	N 32° 49' 14.20"	W 104° 10' 11.59"
	617.00	0.88	82.55	616.92	4.31	4.31	5.87	0.15	662288.49	550212.98	N 32° 49' 14.20"	W 104° 10' 11.57"
	742.00	0.70	114.15	741.91	4.12	4.12	7.52	0.37	662288.30	550214.62	N 32° 49' 14.20"	W 104° 10' 11.55"
	896.00	0.62	160.18	895.90	2.85	2.85	8.66	0.34	662287.13	550215.76	N 32° 49' 14.19"	W 104° 10' 11.54"
	1018.00	0.70	6.76	1017.89	3.07	3.07	8.97	-1.05	662287.25	550216.08	N 32° 49' 14.19"	W 104° 10' 11.53"
	1114.00	0.40	114.50	1113.89	3.52	3.52	9.35	0.94	662287.69	550216.45	N 32° 49' 14.19"	W 104° 10' 11.53"
	1245.00	0.79	137.44	1244.88	2.66	2.66	10.37	0.34	662288.84	550217.48	N 32° 49' 14.19"	W 104° 10' 11.52"
	1375.00	0.79	171.15	1374.87	1.12	1.12	11.12	0.35	662288.29	550218.22	N 32° 49' 14.17"	W 104° 10' 11.51"
	1495.00	0.79	213.16	1494.86	-0.39	-0.39	10.79	0.47	662283.78	550217.90	N 32° 49' 14.16"	W 104° 10' 11.51"
	1673.00	1.01	162.36	1672.84	-2.92	-2.92	10.60	0.45	662281.26	550217.70	N 32° 49' 14.13"	W 104° 10' 11.52"
	1838.00	0.88	212.76	1837.82	-5.37	-5.37	10.35	0.49	662278.81	550217.46	N 32° 49' 14.11"	W 104° 10' 11.52"
	2021.00	1.01	208.15	2020.80	-7.97	-7.97	8.83	-0.08	662278.21	550215.93	N 32° 49' 14.08"	W 104° 10' 11.54"
	2195.00	1.10	210.50	2194.77	-10.70	-10.70	7.26	0.06	662273.42	550214.36	N 32° 49' 14.05"	W 104° 10' 11.56"
	2369.00	1.01	162.36	2368.74	-13.66	-13.66	6.87	0.50	662270.52	550213.68	N 32° 49' 14.02"	W 104° 10' 11.56"
	2543.00	1.01	212.76	2542.72	-16.41	-16.41	6.51	0.49	662267.77	550213.61	N 32° 49' 14.00"	W 104° 10' 11.56"
	2745.00	0.62	221.64	2744.70	-18.73	-18.73	4.82	0.20	662265.45	550211.93	N 32° 49' 13.97"	W 104° 10' 11.58"
	2877.00	0.46	185.17	2876.59	-19.81	-19.81	4.30	0.28	662264.37	550211.40	N 32° 49' 13.96"	W 104° 10' 11.59"
	2972.00	0.48	210.66	2971.69	-20.55	-20.55	4.06	0.22	662263.83	550211.16	N 32° 49' 13.96"	W 104° 10' 11.59"
	3148.00	0.46	210.50	3147.68	-21.81	-21.81	3.32	0.00	662262.37	550210.42	N 32° 49' 13.94"	W 104° 10' 11.60"
	3315.00	0.62	200.15	3314.68	-23.27	-23.27	2.64	0.10	662260.91	550209.75	N 32° 49' 13.93"	W 104° 10' 11.61"
	3436.00	0.62	247.87	3435.07	-24.13	-24.13	1.81	0.42	662260.05	550209.91	N 32° 49' 13.92"	W 104° 10' 11.62"
	3574.00	0.70	201.78	3573.96	-25.20	-25.20	0.80	0.38	662258.98	550207.91	N 32° 49' 13.91"	W 104° 10' 11.63"
	3791.00	0.40	205.95	3790.85	-27.11	-27.11	-0.02	0.14	662257.07	550207.09	N 32° 49' 13.89"	W 104° 10' 11.64"
	3955.00	0.22	183.88	3954.65	-27.94	-27.94	-0.29	0.13	662256.24	550206.81	N 32° 49' 13.88"	W 104° 10' 11.64"
	4169.00	0.40	186.86	4168.64	-28.06	-28.06	-0.54	0.09	662255.12	550206.57	N 32° 49' 13.87"	W 104° 10' 11.65"
	4343.00	0.62	226.96	4342.64	-30.29	-30.29	-1.40	0.20	662253.89	550205.70	N 32° 49' 13.86"	W 104° 10' 11.66"
	4580.00	0.31	190.57	4559.63	-31.67	-31.67	2.37	0.19	662252.52	550204.74	N 32° 49' 13.85"	W 104° 10' 11.67"
	4691.00	0.31	184.46	4690.63	-32.37	-32.37	2.46	0.03	662251.81	550204.65	N 32° 49' 13.84"	W 104° 10' 11.67"
	4787.00	0.31	201.78	4786.63	-32.87	-32.87	2.58	0.10	662251.31	550204.53	N 32° 49' 13.83"	W 104° 10' 11.67"
End MWD Surveys	4903.00	0.22	141.44	4902.63	-33.33	-33.33	2.55	0.24	662250.85	550204.55	N 32° 49' 13.83"	W 104° 10' 11.67"

Survey Type: Def Survey

Survey Error Model: ISCWSA Rev 0 *** 3-D 95.000% Confidence 2.7955 sigma
 Survey Program:

Description	MD From (ft)	MD To (ft)	EOU From (ft)	Survey Tool Type	Borehole / Survey
	0.000	14.000		SLB MWD-STD-Depth Only	Original Hole / Roo 22 State 15 MWD 0' to 4903'
	14.000	14.000		SLB MWD-STD-Depth Only	Original Hole / Roo 22 State 15 MWD 0' to 4903'
	14.000	4903.000		SLB MWD-STD	Original Hole / Roo 22 State 15 MWD 0' to 4903'