Office	Form C-103
Office District I – (575) 393-6161 1625 N French Dr. Hobbs NM 88240 RECEPTATION and Natural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283	WELL API NO. 30-015-10340
811 S. First St., Artesia, NM 88210 AUG 940 2043NSEKVATION DIVISION	5. Indicate Type of Lease
District III - (505) 334-6178 1220 South St. Francis Dr.	STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87 NMOCD ARTEST Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	ROW-NM-29683
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	Monsanto Foster SWD
PROPOSALS.)	8. Well Number
1. Type of Well: Oil Well Gas Well Other SWD	
2. Name of Operator Yates Petroleum Corporation	9. OGRID Number 025575
3. Address of Operator	10. Pool name or Wildcat
105 South Fourth Street, Artesia, NM 88210	SWD; Devonian
4. Well Location	
Unit Letter D: 660 feet from the North line and	660 feet from the West line
Section 5 Township 20S Range 25E	NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, et	c.)
3531'GR	
12. Check Appropriate Box to Indicate Nature of Notice	e, Report or Other Data
NOTICE OF INTENTION TO:	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WO	
	RILLING OPNS. P AND A
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME	NT JOB L
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM	
OTHER: OTHER: MIT	
13. Describe proposed or completed operations. (Clearly state all pertinent details, a	and give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C	ompletions: Attach wellbore diagram of
proposed completion or recompletion.	
8/12/13 - NU BOP.	•
8/13/13 - Opened up well, had no pressure.	
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wa	
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wa 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m	nin. Released tools and TIH to 9295 ft, set RBP.
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wa 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to load	nin. Released tools and TIH to 9295 ft, set RBP.
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lost 260 psi in 30 min. Released packer.	nin. Released tools and TIH to 9295 ft, set RBP.
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lot to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips.	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wa 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lot to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips.	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lot to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips.	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to load to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122'. NOTE: Randy Dadies 10,122'.	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wa 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lot to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above sl25 bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test.
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to load to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122'. NOTE: Randy Dadies 10,122'.	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to load to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122'. NOTE: Randy Dadies 10,122'.	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test.
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to load to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122'. NOTE: Randy Dad Original chart attached	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test. RECEIVED AUG 3 0 2013
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lost to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above sl25 bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122'. NOTE: Randy Dad Original chart attached Spud Date: Rig Release Date:	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test. RECEIVED AUG 3 0 2013 NMOCD ARTESIA
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to load to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122'. NOTE: Randy Dad Original chart attached	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test. RECEIVED AUG 3 0 2013 NMOCD ARTESIA
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lost to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122'. NOTE: Randy Dac Original chart attached Spud Date: Rig Release Date:	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test. RECEIVED AUG 3 0 2013 NMOCD ARTESIA
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lost to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122'. NOTE: Randy Dad Original chart attached Spud Date: Rig Release Date: TITLE Regulatory Reporting	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test. RECEIVED AUG 3 0 2013 NMOCD ARTESIA dge and belief.
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lost to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122. NOTE: Randy Dac Original chart attached Spud Date: Rig Release Date: TITLE Regulatory Reporting Type or print name Tina Huerta E-mail address: tinah@yatespetrole	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test. RECEIVED AUG 3 0 2013 NMOCD ARTESIA dge and belief. Supervisor DATE August 26, 2013
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lost to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bbls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122'. NOTE: Randy Dad Original chart attached Spud Date: Rig Release Date: TITLE Regulatory Reporting	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test. RECEIVED AUG 3 0 2013 NMOCD ARTESIA lge and belief. Supervisor DATE August 26, 2013
8/13/13 - Opened up well, had no pressure. 8/14/13 - Opened up well, had no pressure. Set RBP at 5009 ft. Loaded hole with 30 bbls brine wad 450 psi for 15 min, held good. Pressure tested casing from 5009 ft to surface, held 400 psi for 15 m Loaded hole with 30 bbls brine water. Pressure tested casing to 420 psi, bled down to 375 psi in 30 8/16/13 - Opened up well, had no pressure. Set packer at 10,122 ft. Took 25 bbls brine water to lost to 260 psi in 30 min. Released packer. 8/18/13 - Start in hole with packer, hydrotest tubing to 5000 psi above slips. 8/19/13 - Opened up well, had no pressure. Continued testing 3-1/2 inch tubing to 5000 psi above slips bls packer fluid. ND BOP. Tested casing to 300 psi. 8/21/13 - Opened up well, had 50 psi on casing. Bled down all air. Pressure tested casing to 480 psi nickel plated packer and 3-1/2 inch 9.2Lb J-55 plastic coated tubing at 10,122. NOTE: Randy Dac Original chart attached Spud Date: Rig Release Date: TITLE Regulatory Reporting Type or print name Tina Huerta E-mail address: tinah@yatespetrole	nin. Released tools and TIH to 9295 ft, set RBP. min. ad hole. Pressure tested casing to 290 psi, bled down slips. Leave packer swinging at 10,122 ft. Circulated si, in 30 min pressure bled down to 455 psi. ASI-X de with NMOCD-Artesia witnessed test. RECEIVED AUG 3 0 2013 NMOCD ARTESIA lge and belief. Supervisor DATE August 26, 2013 um.com PHONE: 575-748-4168

