

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-015-25267
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG3215
7. Lease Name or Unit Agreement Name Mesa 20-1 State
8. Well Number 4
9. OGRID Number 16696
10. Pool name or Wildcat Artesia Qn GBSA
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3592'

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
OXY USA Inc.

3. Address of Operator
P.O. Box 50250 Midland, TX 79710

4. Well Location
 Unit Letter M : 990 feet from the South line and 330 feet from the West line
 Section 20 Township 18S Range 28E NMPM County Edley

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE
 CLOSED-LOOP SYSTEM
 OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD-2350' PBD-2347' Perfs-2101-2171'
 8-5/8" 24# csg @ 351' w/ 250sx, 12-1/4" hole, TOC-Surf-Circ
 5-1/2" 14# csg @ 2349' w/ 320sx, 7-7/8" hole, TOC-501'-Calc

- RIH & set CIBP @ 2051', M&P 25sx cmt to 1900'
 - M&P 25sx cmt @ 1550-1400' WOC-Tag
 - Perf @ 900', sqz 50sx cmt to 750' WOC-Tag
 - Perf @ 401' sqz 135sx cmt to surface
10# MLF between plugs
- Above ground steel tanks will be utilized.

Approved for plugging of well bore only.
 Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.

RECEIVED
 OCT 03 2013
 NMOCD ARTESIA

CONDITIONS OF APPROVAL ATTACHED

Spud Date:

Rig Release Date:

Approval Granted providing work is Completed by Oct 8, 2014

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Sr. Regulatory Advisor DATE 9/30/13

Type or print name David Stewart E-mail address: david_stewart@oxy.com PHONE: 432-685-5717

For State Use Only


APPROVED BY: [Signature] TITLE Dist. Reg. Supervisor DATE 10/8/2013

Conditions of Approval (if any):
 * See Attached COA's

OXY USA Inc. - Proposed
Meas 20-1 State #4
API No. 30-015-25267

135sx @ 401'-Surface


12-1/4" hole @ 351'
8-5/8" csg @ 351'
w/ 250sx-TOC-Surf-Circ




Perf @ 401'

50sx @ 900-750' WOC-Tag

Perf @ 900'




25sx @ 1550-1400' WOC-Tag



CIBP @ 2051' w/ 25sx to 1900'

Perfs @ 2101-2171'




7-7/8" hole @ 2350'
5-1/2" csg @ 2349'
w/ 250sx-TOC-501'-Calc

TD-2350'

OXY USA Inc. - Current
Meas 20-1 State #4
API No. 30-015-25267

12-1/4" hole @ 351'
8-5/8" csg @ 351'
w/ 250sx-TOC-Surf-Circ



Perfs @ 2101-2171'

7-7/8" hole @ 2350'
5-1/2" csg @ 2349'
w/ 250sx-TOC-501'-Calc

TD-2350'

NEW MEXICO OIL CONSERVATION DIVISION
DISTRICT 2 OFFICE
811 S. FIRST STREET
ARTESIA, NM 88210
(575)748-1283

CONDITIONS OF APPROVAL FOR PLUGGING & ABANDONMENT

Operator: Oxy USA

Well Name & Number: Mesa 20-1 State 4

API #: 30-015-25267

1. Produced water **will not** be used during any part of the plugging & abandonment operation.
2. Notify NMOCD Dist. 2 office at least 24 hrs before beginning work.
3. Closed Loop System is to be used for entire plugging operation. Upon completion, contents of steel pit are to be hauled to a permitted disposal location.
4. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator, as well as the contractor, to verify that this permit is place prior to performing work. Drivers shall produce a copy upon request of NMOCD Field Inspectors.
5. A subsequent C-103 will serve as notification that the well bore has been plugged **ONLY**. A C-103 FINAL shall be filed before any bonding can be released on the well. Upon receipt of the Final, an inspection will be performed to verify that the location has been satisfactorily cleaned to NMOCD standards.
6. If work has not begun within 90 days of the approval of this procedure, an extension request must be filed, stating reason that well has not been plugged.
7. Every attempt must be made to clean the well bore out to below the perms, before any plugs can be set, by whatever means possible.
8. **Cement Retainers may not be used.**

9. Squeeze pressures are not to exceed 500 PSI, unless approval is given by NMOCD.

10. Plugs may be combined after consulting with and getting approval from NMOCD.

11. Minimum WOC time for tag plugs will be 4 Hrs.

DATE: 10/8/2013

APPROVED BY:

AK Wade

GUIDELINES FOR PLUGGING AND ABANDONMENT

DISTRICT II / ARTESIA

- All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater.
- Mud laden fluids must be placed between all cement plugs.
- Mud laden fluids must be mixed at 25 sacks of gel per 100 bbls of water.
- A cement plug is required to be set 50' below and 50' above all casing shoes and casing stub plugs. These plugs must be tagged.
- A CIBP with 35' of cement on top may be set in lieu of 100' cement plug.
- A plug as indicated above must be placed within 100' of top perforation. This plug must be tagged.
- Plugs set below and above salt zones must be tagged.
- No more than 2000' is to be allowed between cement plugs in open hole and no more than 3000' in cased hole.
- DV tools are required to have a 100' cement plug set 50' above and below the tool and must be tagged.

- Formations to be isolated with plugs placed at the top of each formation are:
 - Fusselman
 - Devonian
 - Morrow
 - Wolfcamp
 - Bone Spring
 - Delaware
 - Any Salt Section (Plug at top and bottom)
 - Abo
 - Glorieta
 - Yates (this plus is usually at base of salt section)

- If cement does not exist behind casing strings at recommended formation depths, the casing must be cut and pulled with plugs set at these depths or casing must be perforated and cement squeezed behind casing at the formation depths.
- In the R-111-P area (Potash Mine area) a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts common to the section penetrated and in suitable proportions, but not more than a 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible (50' below and 50' above).