





End of Well Report for Devon Energy


Rig : H&P223
Well Name : Peridot 13 State 7H-ST01
Field Name : Permian Basin
Country : USA
Job Number : OK-XX-0900441634
Job Start Date : 09-Jul-13
API Number : 30-015-40781-01





GENERAL INFORMATION

Company	: Devon Energy
Rig	: H&P223
Well	: Peridot 13 State 7H-ST01
Field	: Permian Basin
State	: New Mexico
County	: Eddy
Country	: USA
API Number	: 30-015-40781-01
Sperry Drilling Job Number	: OK-XX-0900441634
Job Start Date	: 09-Jul-13
Job End Date	: 07-Aug-13
North Reference	: Grid
Total Correction (deg)	: 7.523
Dip Angle (deg)	: 60.467
Total Magnetic Field (nT)	: 48645
Date of Magnetic Data	: 09 July, 2013
Well Head coordinates N	: 32 deg. 40 min 39.8 sec North
Well Head coordinates E	: 104 deg. 1 min 24.96 sec West
Vertical section direction (deg)	: 187.02
Unit Number	: PP40
MWD Engineers	: Mark Mendez
Company Representatives	: John Holmquist
Company Geologist:	:



OPERATIONAL OVERVIEW

SPERRY DRILLING WAS CONTRACTED TO DRILL THE PERIDOT 13 STATE 7H WELL FOR DEVON ENERGY PROVIDED WERE REAL TIME AND RECORDED GAMMA AS WELL AS DIRECTIONAL DRILLING SERVICES. CREWS ARRIVED ON 7/09/13 AND RIGGED UP ACCORDINGLY.

RUN 100: GOOD MWD RUN FROM 3656'MD TO 5065'MD. MWD TOOL WAS USED TO SURVEY AND TRACK ANTI COLLISION.

RUN 200: GOOD MWD RUN FROM 5065'MD TO 6076'MD. MWD TOOL WAS USED TO SURVEY AND TRACK ANTI COLLISION.

RUN 300: GOOD MWD RUN FROM 6076'MD TO 6787'MD. MWD TOOL WAS USED TO SURVEY AND TRACK ANTI COLLISION.

RUN 400: GOOD MWD RUN FROM 6787'MD TO KOP AT 7523'MD. POOH TO LAY DOWN CURVE ASSEMBLY AND PICK UP LATERAL ASSEMBLY.

RUN 500: GOOD MWD RUN FROM 7523' MD TO 10566' MD. POOH TO MOVE HEAVY WEIGHT PIPE.

RUN 600: GOOD MWD RUN FROM 10566' MD TO 4902' MD. POOH TO SIDE TRACK AND BEGIN PERIDOT 13 STATE 7H-01

RUN 700: GOOD MWD RUN. START DRILLING PERIDOT 13 STATE 7H ST01 (SIDE TRACK). DRILLED FROM 11320'MD TO 11340'MD. POOH TO CHANGE MOTOR AND MWD TOOL.

RUN 800: GOOD MWD RUN. CONTINUED DRILLING PERIDOT 13 STATE 7H-ST01 (SIDE TRACK) FROM 11340'MD TO 13147'MD. POOH TO CHANGE OUT MOTOR AND MWD TOOL.

RUN 900: MWD FAILURE AT 13445'MD. POOH TO CHANGE OUT MWD AND CHECK MWD TOOL STRING TO EXAMINE AND READ PROBES.

RUN 1000: GOOD MWD RUN. CONTINUED DRILLING PERIDOT 13 STATE 7H-ST01 (SIDE TRACK) FROM 113445'MD TO 14960'MD. POOH TO CHANGE OUT MOTOR AND MWD TOOL DUE TO A WASH OUT IN THE PIPE.

RUN 1100: GOOD MWD RUN. CONTINUED DRILLING PERIDOT 13 STATE 7H-ST01 (SIDE TRACK) FROM 114960'MD TO 15730' MD. TD WELL..



SURVEY HEADER

SURVEYS FROM 304' MD TO 3590' MD ARE PROVIDED BY DEVON DIRECTIONAL SURVEY.
SURVEYS FROM 3726' MD TO 15673' MD PROVIDED BY HALLIBURTON SPERRY SERVICES. FINAL SURVEY AT
15730' MD IS A STRAIGHT LINE PROJECTION TO THE BIT.

DIRECTIONAL SURVEY DATA

Tie-in							
0.00	0.00	0.00	0.00	0.00 N	0.00 E		
Measured Depth (ft)	Inclination (deg)	Direction (deg)	Vertical Depth (ft)	Latitude (ft)	Departure (ft)	Vertical Section (ft)	Dogleg (%/100')
304.00	2.10	0.00	303.93	5.57 N	0.00 E	-5.53	0.69
465.00	2.10	315.00	464.83	10.61 N	2.09 W	-10.27	1.00
549.00	1.80	331.00	548.79	12.85 N	3.81 W	-12.29	0.74
641.00	1.90	358.00	640.74	15.64 N	4.57 W	-14.96	0.94
824.00	1.50	360.00	823.66	21.06 N	4.67 W	-20.33	0.22
1007.00	1.50	8.00	1,006.60	25.83 N	4.34 W	-25.11	0.11
1268.00	1.40	67.00	1,267.53	30.46 N	0.93 W	-30.12	0.55
1379.00	1.10	36.00	1,378.50	31.85 N	0.94 E	-31.73	0.66
1567.00	0.90	6.00	1,566.47	34.78 N	2.16 E	-34.78	0.29
1756.00	1.30	351.00	1,755.44	38.37 N	1.98 E	-38.33	0.26
1869.00	1.00	348.00	1,868.42	40.60 N	1.57 E	-40.49	0.27
2109.00	1.50	342.00	2,108.36	45.64 N	0.17 E	-45.32	0.22
2162.00	1.30	320.00	2,161.34	46.76 N	0.43 W	-46.36	1.07
2256.00	1.20	327.00	2,255.32	48.40 N	1.65 W	-47.84	0.19
2342.00	1.00	320.00	2,341.31	49.73 N	2.63 W	-49.04	0.28
2437.00	1.40	345.00	2,436.28	51.49 N	3.46 W	-50.68	0.68
2529.00	1.50	321.00	2,528.26	53.51 N	4.51 W	-52.56	0.66
2627.00	1.40	312.00	2,626.22	55.31 N	6.21 W	-54.14	0.25
2722.00	1.20	306.00	2,721.20	56.67 N	7.87 W	-55.28	0.25
2816.00	1.00	318.00	2,815.18	57.86 N	9.22 W	-56.30	0.32
2911.00	1.60	336.00	2,910.16	59.69 N	10.31 W	-57.98	0.76
3005.00	1.50	312.00	3,004.13	61.71 N	11.76 W	-59.81	0.69
3108.00	1.20	336.70	3,107.10	63.60 N	13.19 W	-61.51	0.63
3203.00	1.40	339.70	3,202.07	65.60 N	13.99 W	-63.40	0.22
3392.00	0.60	312.00	3,391.04	68.43 N	15.52 W	-66.02	0.48
3486.00	0.80	352.70	3,485.04	69.41 N	15.97 W	-66.94	0.56
3590.00	1.20	351.00	3,589.02	71.21 N	16.23 W	-68.69	0.39
3726.00	1.03	331.05	3,725.00	73.68 N	17.05 W	-71.04	0.31
3915.00	1.31	335.87	3,913.96	77.13 N	18.75 W	-74.26	0.16
4104.00	1.64	322.48	4,102.89	81.24 N	21.28 W	-78.03	0.25
4294.00	1.86	8.22	4,292.81	86.45 N	22.49 W	-83.05	0.72
4388.00	2.30	22.32	4,386.75	89.71 N	21.56 W	-86.40	0.71
4577.00	3.19	13.39	4,575.54	98.32 N	18.90 W	-95.28	0.52
4672.00	3.43	9.54	4,670.38	103.70 N	17.82 W	-100.74	0.35
4767.00	3.24	2.03	4,765.22	109.18 N	17.25 W	-106.26	0.50
4861.00	3.05	349.57	4,859.08	114.30 N	17.61 W	-111.29	0.75
4956.00	3.14	344.19	4,953.94	119.29 N	18.78 W	-116.10	0.32
5051.00	3.56	338.53	5,048.77	124.55 N	20.57 W	-121.10	0.56



DIRECTIONAL SURVEY DATA

Measured Depth (ft)	Inclination (deg)	Direction (deg)	Vertical Depth (ft)	Latitude (ft)	Departure (ft)	Vertical Section (ft)	Dogleg (%/100')
5145.00	2.25	276.59	5,142.67	127.47 N	23.47 W	-123.65	3.40
5240.00	3.24	238.21	5,237.57	126.27 N	27.61 W	-121.95	2.14
5335.00	4.15	203.45	5,332.38	121.70 N	31.27 W	-116.97	2.49
5429.00	4.64	199.87	5,426.11	115.01 N	33.91 W	-110.00	0.60
5524.00	4.68	200.07	5,520.79	107.76 N	36.55 W	-102.48	0.04
5618.00	6.21	197.01	5,614.37	99.30 N	39.35 W	-93.74	1.66
5713.00	3.56	211.55	5,709.02	91.87 N	42.39 W	-86.00	3.05
5807.00	2.50	226.78	5,802.88	87.98 N	45.41 W	-81.77	1.41
5902.00	3.30	196.91	5,897.77	83.95 N	47.71 W	-77.49	1.77
5996.00	4.07	179.75	5,991.58	78.03 N	48.49 W	-71.51	1.42
6090.00	4.23	182.26	6,085.33	71.23 N	48.61 W	-64.75	0.26
6185.00	2.71	184.90	6,180.15	65.49 N	48.94 W	-59.02	1.61
6279.00	2.11	193.00	6,274.07	61.59 N	49.52 W	-55.08	0.73
6374.00	2.07	201.84	6,369.01	58.29 N	50.55 W	-51.68	0.34
6469.00	2.15	211.67	6,463.94	55.19 N	52.12 W	-48.41	0.39
6563.00	1.85	210.86	6,557.88	52.39 N	53.82 W	-45.42	0.32
6658.00	1.40	225.22	6,652.85	50.26 N	55.43 W	-43.11	0.64
6727.00	1.11	216.27	6,721.83	49.13 N	56.42 W	-41.87	0.51
6757.00	1.06	220.38	6,751.82	48.68 N	56.77 W	-41.38	0.30
6788.00	2.36	173.82	6,782.81	47.83 N	56.89 W	-40.52	5.82
6820.00	6.56	172.80	6,814.71	45.36 N	56.59 W	-38.10	13.13
6851.00	10.35	168.60	6,845.37	40.87 N	55.82 W	-33.74	12.36
6882.00	13.77	165.27	6,875.68	34.57 N	54.33 W	-27.67	11.28
6914.00	18.22	162.10	6,906.43	26.12 N	51.82 W	-19.59	14.16
6946.00	22.97	163.54	6,936.38	15.37 N	48.51 W	-9.32	14.91
6977.00	26.11	166.72	6,964.57	2.92 N	45.23 W	2.63	11.00
7009.00	29.00	169.53	6,992.94	11.56 S	42.20 W	16.63	9.89
7040.00	32.49	171.84	7,019.58	27.20 S	39.66 W	31.84	11.89
7072.00	35.80	172.60	7,046.07	44.99 S	37.23 W	49.20	10.42
7103.00	39.22	177.96	7,070.66	63.78 S	35.71 W	67.67	15.23
7135.00	41.23	180.20	7,095.09	84.44 S	35.39 W	88.13	7.76
7166.00	43.88	184.46	7,117.93	105.38 S	36.26 W	109.02	12.61
7198.00	46.92	185.44	7,140.40	128.07 S	38.23 W	131.79	9.76
7229.00	50.92	185.97	7,160.76	151.32 S	40.56 W	155.14	12.97
7261.00	54.72	185.63	7,180.10	176.68 S	43.13 W	180.63	11.89
7292.00	57.75	184.16	7,197.33	202.36 S	45.33 W	206.38	10.53
7324.00	61.65	183.48	7,213.47	229.92 S	47.16 W	233.96	12.33
7356.00	66.30	185.28	7,227.51	258.58 S	49.37 W	262.67	15.38
7387.00	70.51	186.66	7,238.91	287.24 S	52.37 W	291.49	14.21
7419.00	74.17	187.62	7,248.62	317.49 S	56.16 W	321.97	11.77
7450.00	78.02	187.25	7,256.07	347.32 S	60.06 W	352.06	12.47
7468.00	80.16	187.32	7,259.47	364.85 S	62.30 W	369.73	11.89
7481.00	80.85	189.06	7,261.62	377.54 S	64.12 W	382.55	14.22
7512.00	85.71	185.81	7,265.24	408.06 S	68.10 W	413.32	18.79
7544.00	87.03	184.96	7,267.27	439.85 S	71.10 W	445.24	4.90



DIRECTIONAL SURVEY DATA

Measured Depth (ft)	Inclination (deg)	Direction (deg)	Vertical Depth (ft)	Latitude (ft)	Departure (ft)	Vertical Section (ft)	Dogleg (%/100')
7575.00	87.38	183.61	7,268.78	470.73 S	73.42 W	476.17	4.50
7607.00	88.49	185.37	7,269.94	502.61 S	75.92 W	508.12	6.48
7638.00	89.57	185.91	7,270.46	533.45 S	78.97 W	539.10	3.90
7670.00	90.37	185.12	7,270.48	565.30 S	82.05 W	571.09	3.51
7701.00	89.85	185.41	7,270.42	596.17 S	84.89 W	602.08	1.92
7733.00	89.05	185.12	7,270.73	628.03 S	87.83 W	634.06	2.65
7764.00	88.10	185.38	7,271.50	658.89 S	90.67 W	665.04	3.15
7796.00	88.71	184.81	7,272.39	690.76 S	93.51 W	697.01	2.58
7827.00	89.35	185.33	7,272.92	721.63 S	96.25 W	727.98	2.67
7859.00	88.86	185.19	7,273.41	753.49 S	99.18 W	759.96	1.60
7890.00	87.93	184.71	7,274.28	784.36 S	101.85 W	790.93	3.37
7985.00	87.25	187.20	7,278.28	878.76 S	111.70 W	885.82	2.71
8079.00	90.28	187.09	7,280.30	972.00 S	123.38 W	979.79	3.22
8174.00	90.03	187.42	7,280.05	1,066.24 S	135.37 W	1074.79	0.43
8268.00	92.29	185.87	7,278.15	1,159.58 S	146.24 W	1168.76	2.91
8362.00	92.32	186.12	7,274.37	1,252.99 S	156.05 W	1262.67	0.27
8457.00	90.86	186.71	7,271.73	1,347.35 S	166.67 W	1357.62	1.65
8552.00	90.09	185.50	7,270.94	1,441.81 S	176.78 W	1452.60	1.51
8646.00	90.28	184.47	7,270.64	1,535.45 S	184.95 W	1546.54	1.11
8741.00	89.97	185.67	7,270.43	1,630.08 S	193.35 W	1641.49	1.30
8836.00	89.88	184.73	7,270.56	1,724.68 S	201.96 W	1736.44	1.00
8930.00	90.00	186.16	7,270.66	1,818.26 S	210.88 W	1830.40	1.52
9025.00	89.29	186.16	7,271.25	1,912.71 S	221.07 W	1925.39	0.75
9120.00	89.94	185.60	7,271.89	2,007.20 S	230.79 W	2020.36	0.90
9214.00	90.06	187.37	7,271.89	2,100.60 S	241.41 W	2114.36	1.89
9309.00	89.57	186.84	7,272.20	2,194.87 S	253.16 W	2209.36	0.76
9404.00	89.60	188.06	7,272.89	2,289.06 S	265.48 W	2304.35	1.28
9498.00	88.83	188.32	7,274.18	2,382.09 S	278.87 W	2398.32	0.87
9593.00	89.23	188.75	7,275.80	2,476.03 S	292.96 W	2493.27	0.62
9687.00	89.29	188.86	7,277.01	2,568.91 S	307.35 W	2587.22	0.14
9782.00	89.48	189.51	7,278.03	2,662.69 S	322.51 W	2682.14	0.71
9877.00	89.54	188.02	7,278.85	2,756.57 S	336.99 W	2777.09	1.56
9971.00	89.29	189.01	7,279.81	2,849.53 S	350.91 W	2871.06	1.08
10066.00	89.88	187.95	7,280.50	2,943.49 S	364.93 W	2966.02	1.27
10161.00	89.47	187.65	7,281.05	3,037.60 S	377.82 W	3061.01	0.54
10255.00	88.99	187.45	7,282.32	3,130.78 S	390.17 W	3155.00	0.55
10350.00	88.49	186.14	7,284.41	3,225.09 S	401.41 W	3249.97	1.47
10445.00	90.65	185.84	7,285.13	3,319.56 S	411.33 W	3344.95	2.29
10500.00	92.25	185.22	7,283.74	3,374.29 S	416.62 W	3399.91	3.12
10595.00	92.01	185.38	7,280.21	3,468.81 S	425.39 W	3494.80	0.30
10658.00	90.12	185.21	7,279.04	3,531.53 S	431.20 W	3557.76	3.00
10753.00	89.51	187.31	7,279.35	3,625.96 S	441.56 W	3652.74	2.30
10847.00	90.74	187.00	7,279.14	3,719.22 S	453.27 W	3746.74	1.35
10942.00	89.75	186.90	7,278.73	3,813.52 S	464.77 W	3841.74	1.05
11037.00	89.97	187.45	7,278.96	3,907.78 S	476.63 W	3936.74	0.62



DIRECTIONAL SURVEY DATA

Measured Depth (ft)	Inclination (deg)	Direction (deg)	Vertical Depth (ft)	Latitude (ft)	Departure (ft)	Vertical Section (ft)	Dogleg (°/100)
11131.00	88.68	187.74	7,280.06	4,000.95 S	489.06 W	4030.72	1.40
11226.00	89.54	188.03	7,281.54	4,095.04 S	502.10 W	4125.70	0.95
11320.00	89.85	188.18	7,282.04	4,188.09 S	515.35 W	4219.68	0.36
11339.00	86.97	189.09	7,282.57	4,206.87 S	518.20 W	4238.67	15.87
11371.00	86.26	188.82	7,284.46	4,238.42 S	523.17 W	4270.59	2.37
11403.00	86.09	188.83	7,286.59	4,269.97 S	528.07 W	4302.50	0.54
11434.00	86.17	189.28	7,288.69	4,300.52 S	532.94 W	4333.41	1.49
11497.00	85.45	189.07	7,293.29	4,362.55 S	542.96 W	4396.20	1.18
11592.00	85.93	189.20	7,300.43	4,456.07 S	558.00 W	4490.87	0.52
11686.00	86.42	189.24	7,306.70	4,548.65 S	573.03 W	4584.59	0.52
11781.00	87.04	189.19	7,312.12	4,642.27 S	588.23 W	4679.36	0.66
11876.00	87.41	189.39	7,316.72	4,735.92 S	603.55 W	4774.18	0.44
11970.00	87.50	187.86	7,320.90	4,828.76 S	617.63 W	4868.04	1.63
12065.00	87.44	187.64	7,325.10	4,922.80 S	630.42 W	4962.94	0.24
12159.00	87.84	187.46	7,328.97	5,015.91 S	642.76 W	5056.86	0.47
12254.00	88.15	187.17	7,332.29	5,110.07 S	654.86 W	5151.80	0.44
12349.00	88.17	187.20	7,335.34	5,204.28 S	666.74 W	5246.75	0.04
12443.00	88.49	186.73	7,338.08	5,297.54 S	678.13 W	5340.71	0.61
12538.00	88.77	186.71	7,340.35	5,391.87 S	689.24 W	5435.68	0.29
12632.00	88.40	187.53	7,342.68	5,485.11 S	700.89 W	5529.65	0.96
12727.00	88.27	187.24	7,345.44	5,579.28 S	713.09 W	5624.61	0.34
12821.00	88.40	187.82	7,348.17	5,672.43 S	725.40 W	5718.57	0.63
12916.00	88.86	186.78	7,350.45	5,766.63 S	737.47 W	5813.54	1.20
13010.00	89.01	185.73	7,352.19	5,860.06 S	747.71 W	5907.51	1.13
13104.00	89.17	185.56	7,353.69	5,953.59 S	756.95 W	6001.47	0.24
13198.00	89.88	185.38	7,354.47	6,047.16 S	765.91 W	6095.43	0.78
13293.00	88.64	184.08	7,355.70	6,141.82 S	773.74 W	6190.35	1.88
13388.00	90.12	185.73	7,356.73	6,236.46 S	781.87 W	6285.27	2.33
13482.00	90.19	185.88	7,356.47	6,329.98 S	791.37 W	6379.25	0.17
13577.00	89.72	186.24	7,356.55	6,424.45 S	801.40 W	6474.23	0.62
13672.00	89.57	186.48	7,357.14	6,518.86 S	811.92 W	6569.23	0.30
13767.00	90.25	186.64	7,357.29	6,613.24 S	822.78 W	6664.22	0.73
13861.00	90.25	186.49	7,356.88	6,706.62 S	833.52 W	6758.22	0.16
13956.00	90.09	186.82	7,356.60	6,800.98 S	844.53 W	6853.22	0.38
14051.00	88.64	186.68	7,357.65	6,895.32 S	855.69 W	6948.21	1.53
14145.00	88.33	187.59	7,360.13	6,988.56 S	867.36 W	7042.17	1.02
14240.00	89.35	188.15	7,362.04	7,082.64 S	880.36 W	7137.14	1.22
14335.00	89.29	188.07	7,363.17	7,176.68 S	893.76 W	7232.12	0.11
14429.00	90.00	187.75	7,363.75	7,269.79 S	906.70 W	7326.10	0.83
14524.00	89.97	186.60	7,363.78	7,364.04 S	918.57 W	7421.10	1.21
14619.00	90.12	185.77	7,363.70	7,458.49 S	928.81 W	7516.09	0.89
14713.00	90.28	185.50	7,363.37	7,552.03 S	938.04 W	7610.06	0.34
14807.00	90.68	186.26	7,362.58	7,645.53 S	947.67 W	7704.04	0.91
14904.00	91.63	187.86	7,360.62	7,741.77 S	959.58 W	7801.02	1.92
14997.00	90.40	186.87	7,358.98	7,833.99 S	971.50 W	7894.00	1.70

**DIRECTIONAL SURVEY DATA**

Measured Depth (ft)	Inclination (deg)	Direction (deg)	Vertical Depth (ft)	Latitude (ft)	Departure (ft)	Vertical Section (ft)	Dogleg (%/100')
15092.00	89.54	186.85	7,359.03	7,928.31 S	982.85 W	7988.99	0.91
15186.00	89.08	186.48	7,360.17	8,021.67 S	993.76 W	8082.99	0.63
15281.00	90.53	187.01	7,360.50	8,116.00 S	1,004.93 W	8177.98	1.63
15375.00	90.65	187.66	7,359.54	8,209.23 S	1,016.93 W	8271.97	0.70
15470.00	89.48	187.75	7,359.43	8,303.37 S	1,029.67 W	8366.97	1.24
15565.00	89.54	188.05	7,360.25	8,397.46 S	1,042.72 W	8461.95	0.32
15659.00	89.28	187.39	7,361.23	8,490.61 S	1,055.35 W	8555.94	0.76
15673.00	89.04	187.15	7,361.43	8,504.49 S	1,057.12 W	8569.94	2.38
15730.00	89.04	187.15	7,362.38	8,561.04 S	1,064.21 W	8626.93	0.01

DIRECTIONAL SURVEY DATA NOTES

- Calculation based on minimum curvature method.
- Survey coordinates relative to well system reference point.
- TVD values given relative to drilling measurement point.
- Vertical section relative to well head.
- Vertical section is computed along a direction of 187.02 degrees (Grid)
- A total correction of 7.52 deg from Magnetic north to Grid north has been applied
- Horizontal displacement is relative to the well head.
- Horizontal displacement (closure) at 15,730.00 feet is 8,626.93 feet along 187.09 degrees (Grid)

WARRANTY

HALLIBURTON ENERGY SERVICES, INC. WILL USE ITS BEST EFFORTS TO FURNISH CUSTOMERS WITH ACCURATE INFORMATION AND INTERPRETATIONS THAT ARE PART OF, AND INCIDENT TO, THE SERVICES PROVIDED. HOWEVER, HALLIBURTON ENERGY SERVICES, INC. CANNOT AND DOES NOT WARRANT THE ACCURACY OR CORRECTNESS OF SUCH INFORMATION AND INTERPRETATIONS. UNDER NO CIRCUMSTANCES SHOULD ANY SUCH INFORMATION OR INTERPRETATION BE RELIED UPON AS THE SOLE BASIS FOR ANY DRILLING, COMPLETION, PRODUCTION, OR FINANCIAL DECISION OR ANY PROCEDURE INVOLVING ANY RISK TO THE SAFETY OF ANY DRILLING VENTURE, DRILLING RIG OR ITS CREW OR ANY THIRD PARTY. THE CUSTOMER HAS FULL RESPONSIBILITY FOR ALL DRILLING, COMPLETION, AND PRODUCTION OPERATION. HALLIBURTON ENERGY SERVICES, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO THE SERVICES RENDERED. IN NO EVENT WILL HALLIBURTON ENERGY SERVICES, INC. SERVICES BE LIABLE FOR FAILURE TO OBTAIN ANY PARTICULAR RESULTS OR FOR ANY DAMAGES, INCLUDING, BUT NOT LIMITED TO, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES, RESULTING FROM THE USE OF ANY INFORMATION OR INTERPRETATION PROVIDED BY HALLIBURTON ENERGY SERVICES, INC.