


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**
*Do not use this form for proposals to drill or to re-enter and Abandoned well. Use Form 3160-3 (APD) for such proposals*5. Lease Serial No.
NMLC-029426B

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

APACHE CORPORATION <873>

3. Address

**303 VETERANS AIRPARK LN, #3000
MIDLAND, TX 79705**

3b. Phone No. (include area Code)

432-818-1000 / 432-818-1168

7. If Unit of CA/Agreement, Name and/or No.

8. Well Name and No.

CROW FEDERAL 18H <308711>

9. API Well No.

30-015-41143-40992

10. Field and Pool or Exploratory Area

FREN; GLORIETA-YESO <26770>

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

UL L, SEC 9, T17S, R31E, 1805' FSL & 110' FWL

11. County or Parish, State

EDDY COUNTY, NM**12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA**

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Fracture Treat☐ New Construction☐ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☒ Other**DRILLING OPS:****CASING & CEMENT****REPORT**

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directional or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attached the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Bond No: **BLM-CO-1463**10/24/2013 **SPUD****10/25/2013 Surface Csg 13 3/8, Hole 17.5", H-40, 48# set @ 470' Cmt with:**


520 sx Class C (14.8 wt 1.34 yld)

CIRC 134 SX To Surface.

WOC.

Surface Csg Pressure Test: 1200 PSI/30 min

REPORT CONTINUED ON PAGE 2.



14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)

MICHELLE COOPER

Title

DRILLING TECH

Signature

Date

1/28/2014BUREAU OF LAND MANAGEMENT
CARLSBAD FIELD OFFICE**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

CROW FEDERAL 18H - Csg & Cmt End of Well Sundry

10/28/2013 Drl F/2588' – T/3515' TD.

10/29/2013 Intermediate Csg 8 5/8, Hole 11", J-55, 32# SET @ 3515'. Circ and Clean Hole.

Lead: 940 sx Class C (12.9 wt, 1.92 yld)

Tail: 500 sx Class C (14.8 wt, 1.33 yld)
Circ 278 sx to surface.

Csg Pressure Test: 2000 PSI/30 min

11/7/2013 Drl F/10,740' – T/10,795' TD. Circ and Cond Hole.

11/8/2013 Production Csg 5.5, Hole 7.875, L-80, 17# set @ 10,795' Cmt with:

Lead: 380 sx Class C (12.6 wt, 2.06 yld)

Tail: 1270 sx Class C (13.0 wt, 1.48 yld)

Circ 219 sx to surface.

Prod Csg pressure test 2500 PSI/30 min-OK.

11/9/2013- RR