

UNITED STATES **OCD Artesia**
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

5. Lease Serial No.
SL:NMLC 063875;BHL:NMLC 063875A
6. If Indian, Allottee or Tribe Name

tes
6-30-2014

1a. Type of work: DRILL REENTER
1b. Type of Well: Oil Well Gas Well Other Single Zone Multiple Zone

7. If Unit or CA Agreement, Name and No.
Poker Lake Unit NMMN 71016X

8. Lease Name and Well No.
Poker Lake Unit #455H *<306402>*

2. Name of Operator BOPCO, L.P.
3a. Address P.O. Box 2760
Midland, TX 79702
3b. Phone No. (incl. area code)
432-683-2277

9. API Well No.
30-015-42470

10. Field and Pool, or Exploratory
Poker Lake, ~~SW (Delaware)~~ *South*

4. Location of Well (Report location clearly and in accordance with any State requirements.)*
At surface NWSE, ULJ, 1890' FSL & 1670' FEL, Lat:N32.113561,Long:W103.865314
At proposed prod. zone 1890' FSL,2090'FWL, Sec21,T25S-R30E,Lat:N32.1113,Long:W103.8875

11. Sec., T. R. M. or Blk. and Survey or Area
Sec 22, T25S-R30E *<503806>*

14. Distance in miles and direction from nearest town or post office*
15 miles southeast of Mataga, NM

12. County or Parish
Eddy County
13. State
NM

15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 1670'
16. No. of acres in lease 2560

17. Spacing Unit dedicated to this well
240 acres

18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 40'
19. Proposed Depth 14,267 MD / 7,565 TVD

20. BLM/BIA Bond No. on file
COB 000050

21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3,297 GL
22. Approximate date work will start* 09/12/2014

23. Estimated duration
36 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- 1. Well plat certified by a registered surveyor.
- 2. A Drilling Plan.
- 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
- 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- 5. Operator certification
- 6. Such other site specific information and/or plans as may be required by the BLM.

25. Signature *Courtney Lockhart* Name (Printed/Typed) Courtney Lockhart Date *3-12-14*

Title Regulatory Analyst

Approved by (Signature) *[Signature]* Name (Printed/Typed) **STEPHEN J. CAFFEY** Date *6-23-14*

Title FIELD MANAGER Office CARLSBAD FIELD OFFICE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2) *(Instructions on page 2)

CARLSBAD CONTROLLED WATER BASIN

NM OIL CONSERVATION
ARTESIA DISTRICT
JUN 30 2014

RECEIVED

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

Approval Subject to General Requirements
& Special Stipulations Attached

OPERATOR'S CERTIFICATION

APPLICATION FOR PERMIT TO DRILL
POKER LAKE UNIT #455H
1890' FSL, 1670' FEL, Section 22, T25S, R30E, Eddy County, NM.

In reference to the above captioned well, I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in the APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

Executed this 12th day of March, 2014.

If you have any questions regarding the accuracy of the plan provided herein, please do not hesitate to contact me at (432) 683-2277.



Courtney Lockhart
Regulatory Analyst

Form NM 8140-9
(March 2008)

United States Department of the Interior
Bureau of Land Management
New Mexico State Office

Permian Basin Cultural Resource Mitigation Fund

The company shown below has agreed to contribute funding to the Permian Basin Cultural Resource Fund in lieu of being required to conduct a Class III survey for cultural resources associated with their project. This form verifies that the company has elected to have the Bureau of Land Management (BLM) follow the procedures specified within the Memorandum of Agreement (MOA) concerning improved strategies for managing historic properties within the Permian Basin, New Mexico, for the undertaking rather than the Protocol to meet the agency's Section 106 obligations.

Company Name: BOPCO, L.P.

Address: P. O. Box 2760

Midland, Texas 79702

Project description: Poker Lake Unit #455H

T, 25S, R 30E, Section 22 NMPM, Eddy County, New Mexico

Amount of contribution: \$ 1,688.00

DISTRICT I
16100 N. French Dr., Hobbs, NM 88240
Phone (575) 393-6161 Fax: (575) 393-0720

DISTRICT II
811 S. First St., Artesia, NM 88210
Phone (575) 746-1263 Fax: (575) 748-9720

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV
1225 S. St. Francis Dr., Santa Fe, NM 87505
Phone (505) 476-3480 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised August 1, 2011

Submit one copy to appropriate
District Office

OIL CONSERVATION DIVISION
1225 South St. Francis Dr.
Santa Fe, New Mexico 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

AMENDED REPORT

API Number 30-015-42470	Pool Code 96047 503806	Pool Name POKER LAKE SW (DELAWARE) South
Property Code 306402	Property Name POKER LAKE UNIT	Well Number 455H
OGRID No. 260737	Operator Name BOPCO, L.P.	Elevation 3297

Surface Location


UL or lot No.	Section	Township	Range	Lot Idn	FEET from the	North/SOUTH LINE	FEET from the	East/EAST LINE	County
J	22	25 S	30 E		1890	SOUTH	1670	EAST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	FEET from the	North/SOUTH LINE	FEET from the	East/EAST LINE	County
K	21	25 S	30 E		1890	SOUTH	2090	WEST	EDDY

Dedicated Acres 240	Joint or Infill	Consolidation Code	Order No.
------------------------	-----------------	--------------------	-----------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Courtney Lockhart 3-12-14
Signature Date

Courtney Lockhart
Printed Name
cjlockhart@basspet.com
Email Address

SURVEYOR CERTIFICATION
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

FEBRUARY 13 2014
Date Surveyed

[Signature]
Signature of Professional Surveyor

7977
Professional Surveyor


Certified by Gary Jones 7977
BASIC SURVEYS

0' 1000' 2000' 3000' 4000'
SCALE: 1" = 2000'
WO Num.: 30051

PROPOSED BOTTOM HOLE LOCATION
Lat - N 32°06'48.43"
Long - W 103°53'15.22"
NMSPC - N 405282.4
E 638016.9
(NAD-27)


SURFACE LOCATION
Lat - N 32°06'48.82"
Long - W 103°51'55.13"
NMSPC - N 405350.8
E 644904.9
(NAD-27)

SECTION 22, TOWNSHIP 25 SOUTH, RANGE 30 EAST, N.M.P.M.,
LEA COUNTY, NEW MEXICO.




BOPCO, L.P.
POKER LAKE UNIT 455H
 ELEV. - 3300'
 Lat - N 32°06'48.82"
 Long - W 103°51'55.13"
 NMSPCE - N 405350.8
 E 644904.9
 (NAD-27)

LOVING, NM IS ±14 MILES TO THE SOUTHWEST OF LOCATION.




Directions to Location:

FROM THE JUNCTION OF ROCK DOVE AND
 HEDGEHOG, TO NORTHEAST ON ROCK DOVE FOR 1.3
 MILES TO PROPOSED LEASE ROAD.





P.O. Box 1786 (575) 395-7316 - Office
 1120 N. West County Rd. (575) 392-2206 - Fax
 Hobbs, New Mexico 88241 basin-surveys.com

BOPCO, L.P.
REF: POKER LAKE UNIT 455H / WELL PAD TOPO
THE POKER LAKE UNIT 455H LOCATED 1890' FROM THE SOUTH LINE AND 1670' FROM THE EAST LINE OF SECTION 22, TOWNSHIP 25 SOUTH, RANGE 30 EAST, N.M.P.M., EDDY COUNTY, NEW MEXICO.



SECTION 22, TOWNSHIP 25 SOUTH, RANGE 30 EAST, N.M.P.M.,
LEA COUNTY, NEW MEXICO.




BOPCO, L.P. 

REF: POKER LAKE UNIT 455H / WELL PAD TOPO

THE POKER LAKE UNIT 455H LOCATED 1890' FROM
THE SOUTH LINE AND 1670' FROM THE EAST LINE OF
SECTION 22, TOWNSHIP 25 SOUTH, RANGE 30 EAST,
N.M.P.M., EDDY COUNTY, NEW MEXICO.


basin surveys
focused on excellence
in the oilfield

P.O. Box 1786 (575) 393-7316 - Office
1120 N. West County Rd. (575) 392-2206 - Fax
Hobbs, New Mexico 88241 basinsurveys.com




POKER LAKE UNIT 455H

Located 1890' FSL and 1670' FEL
 Section 22, Township 25 South, Range 30 East,
 N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (575) 393-7316 - Office
 (575) 392-2206 - Fax
 basinsurveys.com




W.O. Number: KAN. 30051

Survey Date: 02-13-2014

YELLOW TINT - USA LAND
 BLUE TINT - STATE LAND
 NATURAL COLOR - USA LAND



BOPCO, L.P.



BOTTOM HOLE LOCATION FOR POKER LAKE UNIT 455H

Located 1890' FSL and 2090' FWL
 Section 21, Township 25 South, Range 30 East,
 N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (575) 393-7316 - Office
 (575) 392-2206 - Fax
 basinsurveys.com

0' 1000' 2000' 3000' 4000'

SCALE: 1" = 2000'

W.O. Number: KAN 30051

Survey Date: 02-13-2014

YELLOW TINT - USA LAND
 BLUE TINT - STATE LAND
 NATURAL COLOR - USA LAND




BOPCO, L.P.

focused on excellence
 in the oilfield

Flowline Route Diagram 4



Access Road Diagram



**DRILLING PROGRAM
BOPCO, L.P.**

NAME OF WELL: Poker Lake Unit 455H

1. LEGAL DESCRIPTION - SURFACE: 1890' FSL, 1670' FEL, Sec 22-T25S-R30E. BHL: 1890' FSL, 2090' FEL, Sec 21-T25S-R30E. The Poker Lake Unit 455H has a nonstandard surface location.

2. Ground level elevation: 3297' KB elevation (estimated): 3315'

3. Proposed Drilling Depth: 14,267' MD 7,565' TVD

4. WATER, OIL, GAS AND/OR MINERAL BEARING FORMATIONS:

Formation Description	Est. from KB (TVD)	BEARING
T/Fresh Water	401	Fresh Water
T/Rustler	1335	Barren
T/Salado	1865	Barren
T/Lamar	3965	Barren
Bell Canyon	3995	Oil/Gas
Cherry Canyon	4885	Oil/Gas
Brushy Canyon	6110	Oil/Gas
LBC "8A" Sand	7480	Oil/Gas
TD Horizontal Hole (In LBC "8A" Sand)	7565	Oil/Gas

5. Possible mineral bearing formation: Shown above

6. Casing Program

<i>See COA</i> Casing	Set Depth MD	Set Depth (Deepest) TVD	Casing Size	Hole Size	Casing Weight	Casing Grade	Thread	Condition	Tension SF	Collapse SF	Burst SF
Surface	0-1360'	1360'	13-3/8"	17-1/2"	54.5 #	J-55	ST&C	New	13.39	1.69	1.75
Intermediate	0- 3985' <i>3125'</i>	3985' <i>3125'</i>	9-5/8"	12-1/4"	40 #	J-55	LT&C	New	4.68	1.22	1.78
Production	0-7938'	7645'	7"	8-3/4"	26 #	N-80	LT&C	New	3.03	1.25	1.70
Completion System/Liner	7888' <i>OK</i> 14267'	7680' <i>OK</i>	4-1/2"	6-1/8"	11.6 #	HCP-110	LT&C	New	3.63	2.09	2.49

* Depending on availability.

DESIGN CRITERIA AND CASING LOADING ASSUMPTIONS:

SURFACE CASING - (13-3/8")

Tension A 1.6 design factor utilizing the effects of buoyancy (9.2 ppg).

Collapse A 1.0 design factor with full internal evacuation and a collapse force equal to the mud gradient in which the casing will be run (0.48 psi/ft). The effects of axial load on collapse will be considered.

Burst A 1.3 design factor with a surface pressure equal to the fracture gradient at setting depth less a gas gradient to the surface. Internal burst force at the shoe will be fracture pressure at that depth. Backup pressure will be formation pore pressure. In all cases a conservative fracture pressure will be used such that it represents the upper limit of potential fracture resistance up to a 1.0 psi/ft gradient. The effects of tension on burst will not be utilized.

PROTECTIVE CASING - (9-5/8")

- Tension A 1.6 design factor utilizing the effects of buoyancy (10.2 ppg).
- Collapse A 1.125 design factor with full internal evacuation and a collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.

In the case of development drilling, collapse design should be analyzed using internal evacuation equal to 1/3 the proposed total depth of the well. This criterion will be used when there is absolutely no potential of the protective string being used as a production casing string.

- Burst A 1.0 surface design factor and a 1.3 downhole design factor with a surface pressure equivalent to the fracture gradient at setting depth less a gas gradient to the surface. Internal burst force at the shoe will be fracture pressure at that depth. Back pressure will be formation pore pressure. In all cases a conservative fracture pressure will be used such that it represents the upper limit of potential fracture resistance up to a 1.0 psi/ft gradient.

Production CASING - (7")

- Tension A 1.6 design factor utilizing the effects of buoyancy (9.0 ppg).
- Collapse A 1.125 design factor with full internal evacuation and a collapse force equal to the mud gradient in which the casing will be run (0.48 psi/ft). The effects of axial load on collapse will be considered.
- Burst A 1.25 design factor with anticipated maximum tubing pressure (5000 psig) on top of the maximum anticipated packer fluid gradient. (0.433 psi/ft) Backup on production strings will be formation pore pressure. (0.433 psi/ft) The effects of tension on burst will not be utilized.

Completion System - (4-1/2")

- Tension A 1.6 design factor utilizing the effects of buoyancy (9.0 ppg).
- Collapse A 1.125 design factor with full internal evacuation and a collapse force equal to the mud gradient in which the casing will be run (0.48 psi/ft). The effects of axial load on collapse will be considered.
- Burst A 1.25 design factor with anticipated maximum tubing pressure (5000 psig) on top of the maximum anticipated packer fluid gradient. (0.433 psi/ft) Backup on production strings will be formation pore pressure. (0.433 psi/ft) The effects of tension on burst will not be utilized.

7. CEMENT

Surface	Sacks	Weight (ppg)	Yield (FT ³ /SX)	GALS/SX	Cement Blend
Lead	850	13.50	1.75	8.69	Class C +2% CACL + 4% Bentonite + 0.25 LB/SK Cello Flake + 3 lb/sk LCM-1
Tail	340	14.80	1.35	6.35	Class C + 2% CACL + 0.25 LB/SK CF, 0.25LB/SK Cello Flake +3 lb/sk LCM-1

TOC: 0' 100% Excess

Intermediate	Sacks	Weight (ppg)	Yield (FT ³ /SX)	GALS/SX	Cement Blend
Lead	780	12.90	1.85	9.32	EconoCEM HLC + 5% CaCl + 5#/sk Gilsonite
Tail	190	14.80	1.33	6.34	HalCem C

TOC: 0' 30% Excess

Production Stage 1	Sacks	Weight (ppg)	Yield (FT ³ /SX)	GALS/SX	Cement Blend
Lead	180	11.0	2.64	14.87	Tuned Light + 0.125 pps Poly-E-Flake
Tail	110	12.00	2.03	11.41	Class "H" + 0.5% Halad-344 + 0.25% CFR-3 + 0.5% Econolite

TOC: 5000' 50% Excess DV Tool @ 5000'

Production Stage 2	Sacks	Weight (ppg)	Yield (FT ³ /SX)	GALS/SX	Cement Blend
Lead	140	11.0	2.35	11.70	Tuned Light + 0.125 pps Poly-E-Flake

TOC: 3485' (500' inside intermediate casing). 10% Excess inside casing, 50% excess in open hole
 Cement volumes will be adjusted proportionately for depth changes of the multi stage tool.

See COA

COMPLETIONS SYSTEM

A 4-1/2" completion system with open hole packers will be run in the producing lateral to a depth of 14267'. The top of the Completion System will be set at approximately 7888'. Cement will not be required for this system.

8. PRESSURE CONTROL EQUIPMENT (SEE ATTACHED DIAGRAM A, B, C or Z)

After running the 13-3/8" surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 3M will be installed on the Cameron Multi-Bowl System (MBS) wellhead. The BOP/BOPE will be pressure tested to 250 psi low and 3000 psi high after installation on the surface casing which will cover testing requirements for the duration of the well as per Onshore Order #2. The 9-5/8" intermediate casing and 7" production casing will be run with a mandrel hanger through the 13-5/8" BOP/BOPE system without breaking any connections on the BOP/BOPE system and thus not requiring a pressure test. Please find attached wellhead schematic. The field reports from the Cameron representative and the BOP test information will be provided in a subsequent report.

These tests will be performed:

- a) Upon installation
- b) After any component changes
- c) Thirty days after a previous test
- d) As required by well conditions
- e) Any time a seal is broken within a system

A function test to insure that the preventers are operating correctly will be performed on each trip

See COA

BOPCO, L.P. would like to request a variance to use an armored, 3" flex hose for the choke line in the drilling of the well if the rig is equip with hose. (See specification for hose that might be used, attached with APD exhibits). **If an armored flex hose is utilized, the company man will have all of the proper certified paper work for that hose available on location.**

9. MUD PROGRAM

See COA

DEPTH	MUD TYPE	WEIGHT	FV	PV	YP	FL	Ph	
0 -1360'	FW Spud Mud	8.5 - 9.2	38-70	NC	NC	NC	10.0	9.5 - 10.5
1360' - 3985'	Brine Water	9.8 - 10.2	28-30	NC	NC	NC	9.5 - 10.5	9.5 - 10.5
3985' - 7938'	FW/Gel	8.7 - 9.0	28-36	NC	NC	NC	9.5 - 10.0	9.5 - 10.5
7938'-14267'	FW/Gel/Starch	8.7 - 9.0	28-36	NC	NC	<100	9.5 - 10.0	9.5 - 10.5

NOTE: Sufficient mud materials will be kept on location at all times in order to combat lost circulation or control unexpected kicks. May increase vis for logging purposes only.

The mud monitoring system installed on the rig is an electronic Pason, which satisfies onshore order 1 requirements.

10. Drilling Plan

KOP: 7,038' EOC: 8,149' MD (7,680' TVD)

Set surface and intermediate casing strings. Drill production hole to KOP, continue drilling curve. Set and cement production casing at the end of a 70 degree, 200' tangent (in curve). Drill completion hole to TD. Run completions system.

11. TECHNICAL STAGES OF OPERATION

A) TESTING

None anticipated.

B) LOGGING

Run #1: GR with MWD during drilling of build and horizontal portions of 8-3/4" and 6-1/8" hole.

Run #2: Shuttle log w/GR, PE, Density, Neutron, Resistivity in lateral leg open hole are possible.

Mud Logger: Rigged up at 100'

C) CONVENTIONAL CORING

None anticipated

12. H₂S SAFETY EQUIPMENT

H₂S monitors shall be installed prior to drilling out the surface shoe. If H₂S is encountered in quantities greater than 10 PPM, the well will be shut and H₂S equipment will be installed, including a flare line that will be extended pursuant to Onshore Oil and Gas Order #6. **(Please refer to diagram B, or C for choke manifold and closed loop system layout when H₂S is present) Please refer to H₂S location diagram for location of important H₂S safety items.**

13. ANTICIPATED RESERVOIR CONDITIONS

Normal pressures are anticipated throughout Delaware section. A BHP of 3594 psi (max) or MWE of 9.0 ppg is expected. Lost circulation may exist in the Delaware Section from 3,995'-7,680' TVD.

14. OTHER PERTINENT INFORMATION

A) Auxiliary Equipment

Upper and lower kelly cocks. Full opening stab in valve on the rig floor.

B) Anticipated Starting Date

Upon approval

30 days drilling operations

14 days completion operations

BTC

BOPCO, L.P.
Poker Lake Unit 455H
Eddy Co, NM



Plan Data for PLU 455H

Plan Point Information:
 DogLeg Severity Unit: */100.00ft Position offsets from Slot centre

MD	Inc	Az	TVD	N/S	E/W	Northing	Easting	VSec	DLS
(USft)	(")	(")	(USft)	(USft)	(USft)	(USft)	(USft)	(USft)	(DLSU)
0.00	0.00	0.00	0.00	0.00	0.00	405350.90	644304.90	0.00	0.00
7038.74	0.00	0.00	7038.74	0.00	0.00	405350.90	644304.90	0.00	0.00
7738.74	70.00	269.43	7577.14	-3.75	-376.99	405347.15	644327.92	376.99	10.00
7938.74	70.00	269.43	7645.55	-5.62	-564.91	405345.28	644339.99	564.93	0.00
8149.51	91.08	269.43	7660.00	-7.67	-771.63	405343.23	644133.27	771.67	10.00
14267.27	91.08	269.43	7565.00	-68.50	-6886.00	405282.40	638016.90	6886.34	0.00

Plan Data for PLU 455H

Target Set Information:
 Name: PLU 455H

Position offsets from Slot centre

Name	TVD	Elevation	N/S	E/W	Northing	Easting	Shape	Comment
(USft)	(USft)	(USft)	(USft)	(USft)	(USft)	(USft)		
PBHL 455H	7565.00	-4250.00	-68.50	-6886.00	405282.40	638016.90	Cuboid	



Plan Data for PLU 455H

Slot: PLU 455H



Position:
 Offset from Slot centre

N/S	E/W	Northing	Easting	Latitude	Longitude
(USft)	(USft)	(USft)	(USft)	(deg)	(deg)
0.00	0.00	405350.90	644304.90	32°46'48.8"	-103°51'55.1"

Elevation Above VPD: 3257.00USft



KB: 3315
 GR: 3297



Sign Off: Russell Joyner

5D Plan Report**BOPCO, L.P.**

Field Name: *Eddy Co, NM Nad27 NMEZ*
Site Name: *Poker Lake Unit 455H*
Well Name: *PLU 455H*
Plan: *P1:V1*

04 March 2014



PLU 455H

Field Name
Eddy Co, NM
Nad27 NMEZ

Map Units : US ft **Company Name :** BOPCO, L.P.
Vertical Reference Datum (VRD) : Mean Sea Level
Projected Coordinate System : NAD27 / New Mexico East
Comment :

Site Name
Poker Lake Unit
455H

Units : US ft **North Reference :** Grid **Convergence Angle :** 0.25
Position
Northing : 405350.90 US ft **Latitude :** 32°6'48.82"
Easting : 644904.90 US ft **Longitude :** -103°51'55.13"
Elevation above Mean Sea Level: 3297.00 US ft
Comment :

Slot Name
PLU 455H

Position (Offsets relative to Site Centre)
+N / -S : 0.00 US ft **Northing :** 405350.90 US ft **Latitude :** 32°6'48.82"
+E / -W : 0.00 US ft **Easting :** 644904.90 US ft **Longitude :** -103°51'55.13"
Slot TVD Reference : Ground Elevation
Elevation above Mean Sea Level : 3297.00 US ft
Comment :

Well Name
PLU 455H

Type : Main well **UWI :** **Plan :** P1:V1
Rig Height Drill Floor : 18.00 US ft **Comment :**
Relative to Mean Sea Level: 3315.00 US ft
Closure Distance : 6888.34 US ft **Closure Azimuth :** 269.43°
Vertical Section (Position of Origin Relative to Slot)
+ N / -S : 0.00 US ft **+ E / -W :** 0.00 US ft **Az :** 269.43°
Magnetic Parameters
Model : BGGM **Field Strength :** 48215.2nT **Dec :** 7.46° **Dip :** 59.94° **Date :** 15/Jun/2014

Target Set

Name : PLU 455H **Number of Targets :** 1

Comment :

Target Name:
PBHL 455H

Shape:
Cuboid

Position (Relative to Slot centre)
+N / -S : -68.50 US ft **Northing :** 405282.40 US ft **Latitude :** 32°6'48.43"
+E / -W : -6888.00 US ft **Easting :** 638016.90 US ft **Longitude :** -103°53'15.22"
TVD (Drill Floor) : 7565.00 US ft
Orientation Azimuth : 0.00° **Inclination :** 0.00°
Dimensions Length : 0.00 US ft **Breadth :** 0.00 US ft **Height :** 0.00 US ft

Casing Points (Relative to Slot centre, TVD relative to Drill Floor)									
MD (US ft)	Inc (°)	Az (°)	TVD (US ft)	N.Offset (US ft)	E.Offset (US ft)	Northing (US ft)	Easting (US ft)	Name	
7938.74	70.00	269.43	7645.55	-5.62	-564.91	405345.28	644339.99	7 in	

Well path created using minimum curvature

5D Plan Report

Salient Points (Relative to Slot centre, TVD relative to Drill Floor)											
MD (US ft)	Inc (°)	Az (°)	TVD (US ft)	N. Offset (US ft)	E. Offset (US ft)	DLS (°/100 US ft)	VS (US ft)	B. Rate (°/100 US ft)	T. Rate (°/100 US ft)	T. Face (°)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	-0.00	0.00	0.00	0.00	
7038.74	0.00	0.00	7038.74	0.00	0.00	0.00	-0.00	0.00	0.00	0.00	KOP
7738.74	70.00	269.43	7577.14	-3.75	-376.98	10.00	376.99	10.00	0.00	269.43	Hold
7938.74	70.00	269.43	7645.55	-5.62	-564.91	0.00	564.93	0.00	0.00	0.00	Build; 7 in
8149.51	91.08	269.43	7680.00	-7.67	-771.63	10.00	771.67	10.00	-0.00	-0.00	LP
14267.27	91.08	269.43	7565.00	-68.50	-6888.00	0.00	6888.34	0.00	0.00	0.00	PBHL 455H

Interpolated Points (Relative to Slot centre, TVD relative to Drill Floor)											
MD (US ft)	Inc (°)	Az (°)	TVD (US ft)	N. Offset (US ft)	E. Offset (US ft)	VS (US ft)	DLS (°/100 US ft)	Northing (US ft)	Easting (US ft)	Comment	
7000.00	0.00	0.00	7000.00	0.00	0.00	-0.00	0.00	405350.90	644904.90		
7038.74	0.00	0.00	7038.74	0.00	0.00	-0.00	0.00	405350.90	644904.90	KOP	
7100.00	6.13	269.43	7099.88	-0.03	-3.27	3.27	10.00	405350.87	644901.63		
7200.00	16.13	269.43	7197.88	-0.22	-22.54	22.54	10.00	405350.68	644882.36		
7300.00	26.13	269.43	7291.04	-0.58	-58.54	58.54	10.00	405350.32	644846.36		
7400.00	36.13	269.43	7376.53	-1.10	-110.16	110.17	10.00	405349.80	644794.74		
7500.00	46.13	269.43	7451.76	-1.75	-175.85	175.85	10.00	405349.15	644729.05		
7542.41	50.37	269.43	7480.00	-2.06	-207.47	207.49	10.00	405348.84	644697.43	LBC 8A Sand	
7600.00	56.13	269.43	7514.45	-2.52	-253.60	253.61	10.00	405348.38	644651.30		
7700.00	66.13	269.43	7562.67	-3.39	-341.05	341.07	10.00	405347.51	644563.85		
7738.74	70.00	269.43	7577.14	-3.75	-376.98	376.99	10.00	405347.15	644527.92	Hold	
7800.00	70.00	269.43	7598.10	-4.32	-434.54	434.56	0.00	405346.58	644470.36		
7900.00	70.00	269.43	7632.30	-5.26	-528.50	528.53	0.00	405345.64	644376.40		
7938.74	70.00	269.43	7645.55	-5.62	-564.91	564.93	0.00	405345.28	644339.99	Build; 7 in	
8000.00	76.13	269.43	7663.39	-6.20	-623.48	623.51	10.00	405344.70	644281.42		
8100.00	86.13	269.43	7678.79	-7.18	-722.15	722.18	10.00	405343.72	644182.75		
8149.51	91.08	269.43	7680.00	-7.67	-771.63	771.67	10.00	405343.23	644133.27	LP	
8200.00	91.08	269.43	7679.05	-8.18	-822.10	822.14	0.00	405342.72	644082.80		
8300.00	91.08	269.43	7677.17	-9.17	-922.08	922.13	0.00	405341.73	643982.82		
8400.00	91.08	269.43	7675.29	-10.16	-1022.06	1022.11	0.00	405340.74	643882.84		
8500.00	91.08	269.43	7673.41	-11.16	-1122.04	1122.09	0.00	405339.74	643782.86		
8600.00	91.08	269.43	7671.53	-12.15	-1222.01	1222.07	0.00	405338.75	643682.89		
8700.00	91.08	269.43	7669.65	-13.15	-1321.99	1322.06	0.00	405337.75	643582.91		
8800.00	91.08	269.43	7667.77	-14.14	-1421.97	1422.04	0.00	405336.76	643482.93		
8900.00	91.08	269.43	7665.89	-15.14	-1521.94	1522.02	0.00	405335.76	643382.96		
9000.00	91.08	269.43	7664.01	-16.13	-1621.92	1622.00	0.00	405334.77	643282.98		
9100.00	91.08	269.43	7662.13	-17.12	-1721.90	1721.98	0.00	405333.78	643183.00		
9200.00	91.08	269.43	7660.25	-18.12	-1821.88	1821.97	0.00	405332.78	643083.02		
9300.00	91.08	269.43	7658.37	-19.11	-1921.85	1921.95	0.00	405331.79	642983.05		
9400.00	91.08	269.43	7656.49	-20.11	-2021.83	2021.93	0.00	405330.79	642883.07		
9500.00	91.08	269.43	7654.61	-21.10	-2121.81	2121.91	0.00	405329.80	642783.09		
9599.99	91.08	269.43	7652.73	-22.10	-2221.78	2221.89	0.00	405328.80	642683.12		
9699.99	91.08	269.43	7650.85	-23.09	-2321.76	2321.88	0.00	405327.81	642583.14		
9799.99	91.08	269.43	7648.98	-24.08	-2421.74	2421.86	0.00	405326.82	642483.16		
9899.99	91.08	269.43	7647.10	-25.08	-2521.72	2521.84	0.00	405325.82	642383.18		
9999.99	91.08	269.43	7645.22	-26.07	-2621.69	2621.82	0.00	405324.83	642283.21		
10099.99	91.08	269.43	7643.34	-27.07	-2721.67	2721.80	0.00	405323.83	642183.23		
10199.99	91.08	269.43	7641.46	-28.06	-2821.65	2821.79	0.00	405322.84	642083.25		
10299.99	91.08	269.43	7639.58	-29.06	-2921.62	2921.77	0.00	405321.84	641983.28		
10399.99	91.08	269.43	7637.70	-30.05	-3021.60	3021.75	0.00	405320.85	641883.30		
10499.99	91.08	269.43	7635.82	-31.04	-3121.58	3121.73	0.00	405319.86	641783.32		
10599.99	91.08	269.43	7633.94	-32.04	-3221.56	3221.72	0.00	405318.86	641683.34		
10699.99	91.08	269.43	7632.06	-33.03	-3321.53	3321.70	0.00	405317.87	641583.37		
10799.99	91.08	269.43	7630.18	-34.03	-3421.51	3421.68	0.00	405316.87	641483.39		
10899.99	91.08	269.43	7628.30	-35.02	-3521.49	3521.66	0.00	405315.88	641383.41		
10999.99	91.08	269.43	7626.42	-36.01	-3621.46	3621.64	0.00	405314.89	641283.44		
11099.99	91.08	269.43	7624.54	-37.01	-3721.44	3721.63	0.00	405313.89	641183.46		
11199.99	91.08	269.43	7622.66	-38.00	-3821.42	3821.61	0.00	405312.90	641083.48		

5D Plan Report

Interpolated Points (Relative to Slot centre, TVD relative to Drill Floor)										
MD (US ft)	Inc (°)	Az (°)	TVD (US ft)	N.Offset (US ft)	E.Offset (US ft)	VS (US ft)	DLS (°/100 US ft)	Northing (US ft)	Easting (US ft)	Comment
11299.99	91.08	269.43	7620.78	-39.00	-3921.40	3921.59	0.00	405311.90	640983.50	
11399.99	91.08	269.43	7618.90	-39.99	-4021.37	4021.57	0.00	405310.91	640883.53	
11499.99	91.08	269.43	7617.02	-40.99	-4121.35	4121.55	0.00	405309.91	640783.55	
11599.99	91.08	269.43	7615.14	-41.98	-4221.33	4221.54	0.00	405308.92	640683.57	
11699.99	91.08	269.43	7613.26	-42.97	-4321.31	4321.52	0.00	405307.93	640583.59	
11799.99	91.08	269.43	7611.38	-43.97	-4421.28	4421.50	0.00	405306.93	640483.62	
11899.99	91.08	269.43	7609.50	-44.96	-4521.26	4521.48	0.00	405305.94	640383.64	
11999.99	91.08	269.43	7607.62	-45.96	-4621.24	4621.47	0.00	405304.94	640283.66	
12099.99	91.08	269.43	7605.74	-46.95	-4721.21	4721.45	0.00	405303.95	640183.69	
12199.99	91.08	269.43	7603.86	-47.95	-4821.19	4821.43	0.00	405302.95	640083.71	
12299.99	91.08	269.43	7601.98	-48.94	-4921.17	4921.41	0.00	405301.96	639983.73	
12399.99	91.08	269.43	7600.10	-49.93	-5021.15	5021.39	0.00	405300.97	639883.75	
12499.99	91.08	269.43	7598.22	-50.93	-5121.12	5121.38	0.00	405299.97	639783.78	
12599.99	91.08	269.43	7596.34	-51.92	-5221.10	5221.36	0.00	405298.98	639683.80	
12699.99	91.08	269.43	7594.46	-52.92	-5321.08	5321.34	0.00	405297.98	639583.82	
12799.99	91.08	269.43	7592.58	-53.91	-5421.05	5421.32	0.00	405296.99	639483.85	
12899.99	91.08	269.43	7590.70	-54.91	-5521.03	5521.30	0.00	405295.99	639383.87	
12999.99	91.08	269.43	7588.82	-55.90	-5621.01	5621.29	0.00	405295.00	639283.89	
13099.99	91.08	269.43	7586.94	-56.89	-5720.99	5721.27	0.00	405294.01	639183.91	
13199.99	91.08	269.43	7585.06	-57.89	-5820.96	5821.25	0.00	405293.01	639083.94	
13299.99	91.08	269.43	7583.18	-58.88	-5920.94	5921.23	0.00	405292.02	638983.96	
13399.99	91.08	269.43	7581.30	-59.88	-6020.92	6021.22	0.00	405291.02	638883.98	
13499.99	91.08	269.43	7579.42	-60.87	-6120.89	6121.20	0.00	405290.03	638784.01	
13599.99	91.08	269.43	7577.54	-61.87	-6220.87	6221.18	0.00	405289.03	638684.03	
13699.99	91.08	269.43	7575.66	-62.86	-6320.85	6321.16	0.00	405288.04	638584.05	
13799.99	91.08	269.43	7573.78	-63.85	-6420.83	6421.14	0.00	405287.05	638484.07	
13899.99	91.08	269.43	7571.90	-64.85	-6520.80	6521.13	0.00	405286.05	638384.10	
13999.99	91.08	269.43	7570.02	-65.84	-6620.78	6621.11	0.00	405285.06	638284.12	
14099.99	91.08	269.43	7568.14	-66.84	-6720.76	6721.09	0.00	405284.06	638184.14	
14199.99	91.08	269.43	7566.26	-67.83	-6820.73	6821.07	0.00	405283.07	638084.17	
14267.27	91.08	269.43	7565.00	-68.50	-6888.00	6888.34	0.00	405282.40	638016.90	PBHL 455H

Formation Points (Relative to Slot centre, TVD relative to Drill Floor)										
MD (US ft)	Inc (°)	Az (°)	TVD (US ft)	N.Offset (US ft)	E.Offset (US ft)	Northing (US ft)	Easting (US ft)	Name	Comment	
7542.41	50.37	269.43	7480.00	-2.06	-207.47	405348.84	644697.43	LBC 8A Sand		

5D Anti-Collision Report**BOPCO, L.P.****Field Name:** *Eddy Co, NM Nad27 NMEZ***Site Name:** *Poker Lake Unit 455H***Well Name:** *PLU 455H*

04 March 2014

**Weatherford®**

5D Anti-Collision Report

Anti-Collision Proximity Summary (TVD relative to)

Secondary Well Name	Prim MD (US ft)	Sec MD (US ft)	TVD (US ft)	CC (US ft)	ES (US ft)	SF	Risk
PLU 456H (p)	7062.50	7066.46	7062.49	40.02	7.94	1.25	SF (Med)

Secondary Well : PLU 456H (p) (TVD Relative to Drill Floor (Primary)) ; All Azimuth Relative to GRID NORTH

Prim MD (US ft)	TVD (US ft)	Sec MD (US ft)	T. Face to Sec (°)	S. Major (US ft)	S. Minor (US ft)	CC (US ft)	ES (US ft)	SF	Risk
0.00	0.00	4.00	359.71	0.02	0.02	40.00	39.39	65.81	
100.00	100.00	104.00	359.71	0.13	0.13	40.00	39.17	47.95	
200.00	200.00	204.00	359.71	0.35	0.35	40.00	38.72	31.32	
300.00	300.00	304.00	359.71	0.58	0.58	40.00	38.28	23.19	
400.00	400.00	404.00	359.71	0.80	0.80	40.00	37.83	18.40	
500.00	500.00	504.00	359.71	1.02	1.02	40.00	37.38	15.25	
600.00	600.00	604.00	359.71	1.25	1.25	40.00	36.93	13.02	
700.00	700.00	704.00	359.71	1.47	1.47	40.00	36.48	11.36	
800.00	800.00	804.00	359.71	1.70	1.70	40.00	36.03	10.07	
900.00	900.00	904.00	359.71	1.92	1.92	40.00	35.58	9.05	
1000.00	1000.00	1004.00	359.71	2.15	2.15	40.00	35.13	8.21	
1100.00	1100.00	1104.00	359.71	2.37	2.37	40.00	34.68	7.52	
1200.00	1200.00	1204.00	359.71	2.60	2.60	40.00	34.23	6.93	
1300.00	1300.00	1304.00	359.71	2.82	2.82	40.00	33.78	6.43	
1400.00	1400.00	1404.00	359.71	3.05	3.05	40.00	33.33	6.00	
1500.00	1500.00	1504.00	359.71	3.27	3.27	40.00	32.88	5.62	
1600.00	1600.00	1604.00	359.71	3.50	3.50	40.00	32.43	5.29	
1700.00	1700.00	1704.00	359.71	3.72	3.72	40.00	31.98	4.99	
1800.00	1800.00	1804.00	359.71	3.95	3.95	40.00	31.53	4.72	
1900.00	1900.00	1904.00	359.71	4.17	4.17	40.00	31.09	4.49	
2000.00	2000.00	2004.00	359.71	4.40	4.40	40.00	30.64	4.27	
2100.00	2100.00	2104.00	359.71	4.62	4.62	40.00	30.19	4.08	
2200.00	2200.00	2204.00	359.71	4.84	4.84	40.00	29.74	3.90	
2300.00	2300.00	2304.00	359.71	5.07	5.07	40.00	29.29	3.73	
2400.00	2400.00	2404.00	359.71	5.29	5.29	40.00	28.84	3.58	
2500.00	2500.00	2504.00	359.71	5.52	5.52	40.00	28.39	3.44	
2600.00	2600.00	2604.00	359.71	5.74	5.74	40.00	27.94	3.32	
2700.00	2700.00	2704.00	359.71	5.97	5.97	40.00	27.49	3.20	
2800.00	2800.00	2804.00	359.71	6.19	6.19	40.00	27.04	3.09	
2900.00	2900.00	2904.00	359.71	6.42	6.42	40.00	26.59	2.98	
3000.00	3000.00	3004.00	359.71	6.64	6.64	40.00	26.14	2.89	
3100.00	3100.00	3104.00	359.71	6.87	6.87	40.00	25.69	2.80	
3200.00	3200.00	3204.00	359.71	7.09	7.09	40.00	25.24	2.71	
3300.00	3300.00	3304.00	359.71	7.32	7.32	40.00	24.79	2.63	
3400.00	3400.00	3404.00	359.71	7.54	7.54	40.00	24.34	2.55	
3500.00	3500.00	3504.00	359.71	7.77	7.77	40.00	23.89	2.48	
3600.00	3600.00	3604.00	359.71	7.99	7.99	40.00	23.44	2.42	
3700.00	3700.00	3704.00	359.71	8.22	8.22	40.00	22.99	2.35	
3800.00	3800.00	3804.00	359.71	8.44	8.44	40.00	22.54	2.29	
3900.00	3900.00	3904.00	359.71	8.67	8.67	40.00	22.10	2.23	
4000.00	4000.00	4004.00	359.71	8.89	8.89	40.00	21.65	2.18	
4100.00	4100.00	4104.00	359.71	9.12	9.12	40.00	21.20	2.13	
4200.00	4200.00	4204.00	359.71	9.34	9.34	40.00	20.75	2.08	
4300.00	4300.00	4304.00	359.71	9.56	9.56	40.00	20.30	2.03	
4400.00	4400.00	4404.00	359.71	9.79	9.79	40.00	19.85	1.98	SF (Lo)
4500.00	4500.00	4504.00	359.71	10.01	10.01	40.00	19.40	1.94	SF (Lo)
4600.00	4600.00	4604.00	359.71	10.24	10.24	40.00	18.95	1.90	SF (Lo)
4700.00	4700.00	4704.00	359.71	10.46	10.46	40.00	18.50	1.86	SF (Lo)
4800.00	4800.00	4804.00	359.71	10.69	10.69	40.00	18.05	1.82	SF (Lo)
4900.00	4900.00	4904.00	359.71	10.91	10.91	40.00	17.60	1.79	SF (Lo)
5000.00	5000.00	5004.00	359.71	11.14	11.14	40.00	17.15	1.75	SF (Lo)
5100.00	5100.00	5104.00	359.71	11.36	11.36	40.00	16.70	1.72	SF (Lo)
5200.00	5200.00	5204.00	359.71	11.59	11.59	40.00	16.25	1.68	SF (Lo)

5D Anti-Collision Report

Secondary Well : PLU 456H (p) (TVD Relative to Drill Floor (Primary) ; All Azimuth Relative to GRID NORTH)									
Pri MD (US ft)	TVD (US ft)	Sec MD (US ft)	T-Face to Sec (°)	S-Major (US ft)	S-Minor (US ft)	CC (US ft)	ES (US ft)	SF	Risk
5300.00	5300.00	5304.00	359.71	11.81	11.81	40.00	15.80	1.65	SF (Lo)
5400.00	5400.00	5404.00	359.71	12.04	12.04	40.00	15.35	1.62	SF (Lo)
5500.00	5500.00	5504.00	359.71	12.26	12.26	40.00	14.90	1.59	SF (Lo)
5600.00	5600.00	5604.00	359.71	12.49	12.49	40.00	14.45	1.57	SF (Lo)
5700.00	5700.00	5704.00	359.71	12.71	12.71	40.00	14.00	1.54	SF (Lo)
5800.00	5800.00	5804.00	359.71	12.94	12.94	40.00	13.55	1.51	SF (Lo)
5900.00	5900.00	5904.00	359.71	13.16	13.16	40.00	13.10	1.49	SF (Med)
6000.00	6000.00	6004.00	359.71	13.39	13.39	40.00	12.66	1.46	SF (Med)
6100.00	6100.00	6104.00	359.71	13.61	13.61	40.00	12.21	1.44	SF (Med)
6200.00	6200.00	6204.00	359.71	13.84	13.84	40.00	11.76	1.42	SF (Med)
6300.00	6300.00	6304.00	359.71	14.06	14.06	40.00	11.31	1.39	SF (Med)
6400.00	6400.00	6404.00	359.71	14.28	14.28	40.00	10.86	1.37	SF (Med)
6500.00	6500.00	6504.00	359.71	14.51	14.51	40.00	10.41	1.35	SF (Med)
6600.00	6600.00	6604.00	359.71	14.73	14.73	40.00	9.96	1.33	SF (Med)
6700.00	6700.00	6704.00	359.71	14.96	14.96	40.00	9.51	1.31	SF (Med)
6800.00	6800.00	6804.00	359.71	15.18	15.18	40.00	9.06	1.29	SF (Med)
6900.00	6900.00	6904.00	359.71	15.41	15.41	40.00	8.61	1.27	SF (Med)
7000.00	7000.00	7004.00	359.71	15.63	15.63	40.00	8.16	1.26	SF (Med)
7100.00	7099.17	7103.29	99.45	15.84	15.75	40.56	8.36	1.26	SF (Med)
7200.00	7186.53	7192.25	133.26	16.02	15.65	59.32	27.13	1.84	SF (Lo)
7300.00	7251.04	7260.30	151.08	16.16	15.36	114.75	83.20	3.64	
7400.00	7292.32	7305.54	155.61	16.25	15.10	193.84	162.82	6.25	
7500.00	7314.99	7331.14	151.46	16.32	14.96	285.62	254.80	9.27	
7600.00	7324.00	7341.49	123.29	16.34	14.89	383.43	352.72	12.48	
7700.00	7323.10	7340.45	38.34	16.34	14.90	482.86	452.07	15.68	
7800.00	7316.25	7332.57	23.46	16.32	14.95	581.41	550.47	18.79	
7900.00	7309.92	7325.35	21.93	16.30	14.99	680.07	648.97	21.87	
8000.00	7303.26	7317.82	12.15	16.29	15.04	778.38	747.07	24.86	
8100.00	7291.93	7305.10	6.80	16.25	15.11	873.22	841.71	27.72	
8200.00	7277.07	7288.64	5.43	16.21	15.18	963.47	931.76	30.38	
8300.00	7263.07	7273.32	5.26	16.18	15.28	1054.05	1022.13	33.02	
8400.00	7250.42	7259.63	5.12	16.16	15.36	1145.67	1113.51	35.63	
8500.00	7238.95	7247.34	4.99	16.13	15.43	1238.18	1205.82	38.26	
8600.00	7228.53	7236.24	4.88	16.11	15.49	1331.45	1298.91	40.92	
8700.00	7219.02	7226.18	4.79	16.09	15.53	1425.37	1392.70	43.62	
8800.00	7210.31	7217.03	4.71	16.07	15.57	1519.86	1487.10	46.39	
8900.00	7202.33	7208.68	4.63	16.05	15.60	1614.84	1581.97	49.13	
9000.00	7194.97	7201.02	4.56	16.04	15.62	1710.25	1677.28	51.88	
9100.00	7188.19	7193.97	4.50	16.02	15.65	1806.03	1772.96	54.60	
9200.00	7181.91	7187.48	4.45	16.01	15.66	1902.15	1868.97	57.33	
9300.00	7176.08	7181.46	4.40	16.00	15.68	1998.57	1965.29	60.05	
9400.00	7170.67	7175.89	4.36	15.99	15.69	2095.25	2061.89	62.80	
9500.00	7165.62	7170.70	4.32	15.98	15.69	2192.17	2158.76	65.62	
9600.00	7160.90	7165.87	4.28	15.97	15.70	2289.30	2255.82	68.38	
9700.00	7156.49	7161.36	4.25	15.96	15.71	2386.62	2353.08	71.16	
9800.00	7152.35	7157.13	4.21	15.95	15.71	2484.11	2450.56	74.05	
9900.00	7148.46	7153.16	4.18	15.94	15.71	2581.76	2548.16	76.84	
10000.00	7144.80	7149.43	4.16	15.93	15.72	2679.56	2645.90	79.61	
10100.00	7141.35	7145.92	4.13	15.93	15.72	2777.48	2743.76	82.36	
10200.00	7138.09	7142.61	4.11	15.92	15.72	2875.52	2841.74	85.13	
10300.00	7135.01	7139.49	4.09	15.92	15.72	2973.68	2939.84	87.89	
10400.00	7132.10	7136.53	4.06	15.91	15.72	3071.93	3038.04	90.66	
10500.00	7129.33	7133.72	4.04	15.90	15.72	3170.27	3136.34	93.43	
10600.00	7126.70	7131.06	4.03	15.90	15.72	3268.71	3234.73	96.21	
10700.00	7124.21	7128.54	4.01	15.89	15.72	3367.22	3333.20	98.97	
10800.00	7121.83	7126.13	3.99	15.89	15.71	3465.80	3431.73	101.74	
10900.00	7119.56	7123.84	3.98	15.88	15.72	3564.45	3530.34	104.49	
11000.00	7117.40	7121.66	3.96	15.88	15.72	3663.17	3629.00	107.22	

5D Anti-Collision Report

Secondary Well : PLU 456H (p) (TVD Relative to Drill Floor (Primary) ; All Azimuth Relative to GRID NORTH)									
Pri MD (US.ft)	TVD (US.ft)	Sec MD (US.ft)	T.Face to Sec (°)	S.Major (US.ft)	S.Minor (US.ft)	CC (US.ft)	ES (US.ft)	SF	Risk
11100.00	7115.34	7119.58	3.95	15.88	15.73	3761.94	3727.73	109.96	
11200.00	7113.37	7117.59	3.94	15.87	15.73	3860.77	3826.51	112.69	
11300.00	7111.48	7115.69	3.92	15.87	15.74	3959.65	3925.34	115.42	
11400.00	7109.68	7113.87	3.91	15.87	15.74	4058.58	4024.22	118.14	
11500.00	7107.94	7112.12	3.90	15.86	15.74	4157.55	4123.15	120.85	
11600.00	7106.28	7110.45	3.89	15.86	15.74	4256.57	4222.12	123.56	
11700.00	7104.69	7108.84	3.88	15.86	15.75	4355.62	4321.13	126.27	
11800.00	7103.15	7107.30	3.87	15.85	15.75	4454.72	4420.17	128.96	
11900.00	7101.68	7105.81	3.86	15.85	15.75	4553.84	4519.26	131.65	
12000.00	7100.26	7104.38	3.85	15.85	15.75	4653.01	4618.37	134.34	
12100.00	7098.89	7103.01	3.84	15.84	15.75	4752.20	4717.52	137.02	
12200.00	7097.58	7101.69	3.83	15.84	15.75	4851.42	4816.69	139.69	
12300.00	7096.31	7100.41	3.82	15.84	15.76	4950.67	4915.89	142.35	
12400.00	7095.08	7099.18	3.82	15.84	15.76	5049.95	5015.12	145.00	
12500.00	7093.90	7097.99	3.81	15.83	15.76	5149.25	5114.38	147.65	
12600.00	7092.76	7096.84	3.80	15.83	15.76	5248.58	5213.66	150.30	
12700.00	7091.65	7095.73	3.80	15.83	15.76	5347.93	5312.95	152.89	
12800.00	7090.58	7094.66	3.79	15.83	15.76	5447.30	5412.26	155.47	
12900.00	7089.55	7093.62	3.78	15.83	15.76	5546.69	5511.59	158.04	
13000.00	7088.55	7092.62	3.78	15.82	15.76	5646.10	5610.94	160.61	
13100.00	7087.58	7091.64	3.77	15.82	15.76	5745.53	5710.31	163.16	
13200.00	7086.64	7090.70	3.76	15.82	15.76	5844.98	5809.70	165.70	
13300.00	7085.73	7089.79	3.76	15.82	15.76	5944.44	5909.11	168.24	
13400.00	7084.85	7088.90	3.75	15.82	15.76	6043.92	6008.53	170.76	
13500.00	7083.99	7088.04	3.75	15.82	15.76	6143.41	6107.96	173.28	
13600.00	7083.16	7087.20	3.74	15.81	15.76	6242.92	6207.41	175.78	
13700.00	7082.35	7086.39	3.74	15.81	15.76	6342.45	6306.87	178.28	
13800.00	7081.56	7085.60	3.73	15.81	15.76	6441.99	6406.35	180.78	
13900.00	7080.80	7084.84	3.73	15.81	15.76	6541.54	6505.84	183.27	
14000.00	7080.05	7084.09	3.72	15.81	15.76	6641.10	6605.35	185.75	
14100.00	7079.33	7083.37	3.72	15.81	15.76	6740.68	6704.86	188.22	
14200.00	7078.63	7082.66	3.72	15.80	15.76	6840.26	6804.39	190.68	
14267.27	7078.17	7082.20	3.71	15.80	15.76	6907.26	6871.34	192.32	



Weatherford

Weatherford Drilling Services

GeoDec v5.03

Report Date: March 04, 2014
 Job Number: _____
 Customer: BOPCO
 Well Name: Poker Lake Unit 455H
 API Number: _____
 Rig Name: _____
 Location: Eddy Co, NM
 Block: _____
 Engineer: RWJ

US State Plane 1927	Geodetic Latitude / Longitude
System: New Mexico East 3001 (NON-EXACT)	System: Latitude / Longitude
Projection: SPC27 Transverse Mercator	Projection: Geodetic Latitude and Longitude
Datum: NAD 1927 (NADCON CONUS)	Datum: NAD 1927 (NADCON CONUS)
Ellipsoid: Clarke 1866	Ellipsoid: Clarke 1866
North/South 405350.900 USFT	Latitude 32.1135610 DEG
East/West 644904.900 USFT	Longitude -103.8653147 DEG
Grid Convergence: .25°	
Total Correction: +7.21°	

Geodetic Location WGS84 Elevation = 0.0 Meters
 Latitude = 32.11356° N 32° 6 min 48.820 sec
 Longitude = 103.86531° W 103° 51 min 55.133 sec

Magnetic Declination =	7.46°	[True North Offset]	
Local Gravity =	.9988 g	Checksum =	6720
Local Field Strength =	48215 nT	Magnetic Vector X =	23946 nT
Magnetic Dip =	59.94°	Magnetic Vector Y =	3137 nT
Magnetic Model =	bggm2013	Magnetic Vector Z =	41731 nT
Spud Date =	Jun 15, 2014	Magnetic Vector H =	24151 nT

Signed: _____

Date: _____

Note: Dimensional information reflected on this drawing are estimated measurements only





Diagram Z



BOPCO
Project: South East New Mexico




Jeanette

7-22-13


#

21077904-A




13-5/8" X 3-M BOPE (2 Rams and Rotating Head) & Closed Loop System Equipment Schematic Diagram A

Note: all valves & lines on choke manifold are 3" unless otherwise noted. Exact manifold configuration may vary.



13-5/8" X 3-M BOPE (2 Rams and Rotating Head) & Closed Loop System Equipment Schematic H2S contingency Diagram B

Note: all valves & lines on choke manifold are 3" unless otherwise noted. Exact manifold configuration may vary.



Latshaw 4 closed loop system, with Latshaw 18 addition "clouded."

Latshaw 13-5/8" X 3-M BOPE (2 Rams and Rotating Head) & Closed Loop System Equipment Schematic Diagram C

Note: all valves & lines on choke manifold are 3" unless otherwise noted. Exact manifold configuration may vary.

M I D W E S T

HOSE AND SPECIALTY INC.

INTERNAL HYDROSTATIC TEST REPORT		
Customer: LATSHAW DRILLING		P.O. Number: RIG#4
HOSE SPECIFICATIONS		
Type: CHOKER LINE	Length: 30'	
I.D. 3" INCHES	O.D. 6" INCHES	
WORKING PRESSURE 5,000 PSI	TEST PRESSURE 10,000 PSI	BURST PRESSURE PSI
COUPLINGS		
Type of End Fitting 4 1/16 5K FLANGE		
Type of Coupling: SWEDGED	MANUFACTURED BY MIDWEST HOSE & SPECIALTY	
PROCEDURE		
<i>Hose assembly pressure tested with water at ambient temperature.</i>		
TIME HELD AT TEST PRESSURE 1 MIN.	ACTUAL BURST PRESSURE: 0 PSI	
COMMENTS: SO#81610 Hose is covered with stainless steel armour cover and wrapped with fire resistant vermiculite coated fiberglass insulation rated for 1500 degrees complete with lifting eyes		
Date: 3/2/2011	Tested By: BOBBY FINK	Approved: MENDI JACKSON



Midwest Hose & Specialty, Inc.

Internal Hydrostatic Test Graph

April 4, 2012

Customer: Latshaw


Pick Ticket #: 81610

Hose Specifications

Hose Type	Length
D	30'
I.D.	O.D.
3"	4 15/32
Working Pressure	Burst Pressure
5000 PSI	Standard Safety Multiplier Applies

Verification

Type of Fitting	Coupling Method
41/16 SK	Swage
Die Size	Final O.D.
5.12"	5.16"
Hose Serial #	Hose Assembly Serial #
6884	E1610



Test Pressure
10000 PSI

Time Held at Test Pressure
6 1/4 Minutes

Actual Burst Pressure

Peak Pressure
10195 PSI


Comments: Hose assembly pressure tested with water at ambient temperature.

Tested By: Donnie Mclemore

Approved By: Bobby Fink

EXHIBIT "D"

RIG LAYOUT SCHEMATIC
INCLUSIVE OF CLOSED-LOOP DESIGN PLAN



- SOLIDS CONTROL EQUIPMENT LEGEND**
- 1) ROLL OFF BIN
 - 2) STEEL TANK
 - 3) MUD CLEANER
 - 4) SHAKER
 - 5) CENTRIFUGE
 - 6) DEWATERING UNIT
 - 7) CATCH TANK
 - 8) CHOKE MANIFOLD
 - A) BLEED LINE FROM CHOKE MANIFOLD

POKER LAKE UNIT 455H

Located 1890' FSL and 1670' FEL
Section 22, Township 25 South, Range 30 East,
N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786
1120 N. West County Rd.
Hobbs, New Mexico 88241
(575) 393-7316 - Office
(575) 392-2206 - Fax
basinsurveys.com

SCALE: NONE

W.O. Number: KAN 30051

Survey Date: 02-13-2014

BOPCO, L.P.

TABLE OF CONTENTS

I. H₂S Contingency Plan

- A. Scope
- B. Objective
- C. Discussion of Plan

II. Emergency Procedures

- A. Emergency Procedures and Public Protection
- B. Emergency Procedures Implementation
- C. Simulated Blowout Control Drills

III. Ignition Procedures

- A. Responsibility
- B. Instructions

IV. Training Requirements

V. Emergency Equipment

VI. Evacuation Plan

- A. General Plan
- B. Emergency Phone Lists

VII. General Information

- A. H₂S Toxicity Table
- B. Respirator Use
- C. Emergency Rescue

H₂S CONTINGENCY PLAN SECTION

Scope:

This contingency plan provides an organized plan of action for alerting and protecting the public within an area of exposure prior to an intentional release, or following the accidental release of a potentially hazardous volume of hydrogen sulfide. The plan establishes guidelines for all personnel whose work activity may involve exposure to Hydrogen Sulfide Gas (H₂S).

Objective:

Prevent any and all accidents, and prevent the uncontrolled release of H₂S into the atmosphere.

Provide proper evacuation procedures to cope with emergencies.

Provide immediate and adequate medical attention should an injury occur.

Discussion of Plan:

Suspected Problem Zones:

Implementation: This plan, with all details, is to be fully implemented 500' above or three days prior to drilling into the first known sour zone

Emergency Response and Public Protection Procedure: This section outlines the conditions and denotes steps to be taken in the event of an emergency.

Emergency Equipment and Procedure: This section outlines the safety and emergency equipment that will be required for the drilling of this well.

Training Provisions: This section outlines the training provisions that must be adhered to 500 feet above or three days prior to drilling into the first known sour zone.

Emergency call lists: Included are the telephone numbers of all persons that would need to be contacted should an H₂S emergency occur.

Briefing: This section deals with the briefing of all persons involved with the drilling of this well.

Public Safety: Public Safety Personnel will be made aware of the drilling of this well.

EMERGENCY PROCEDURES AND PUBLIC PROTECTION SECTION

- I. In the event of any evidence of H₂S levels above 10 ppm, take the following steps immediately:
 - A. Secure breathing apparatus.
 - B. Order non-essential personnel out of the danger zone.
 - C. Take steps to determine if the H₂S level can be corrected or suppressed, and if so, proceed with normal operations.
- II. If uncontrollable conditions occur, proceed with the following:
 - A. Take steps to protect and/or remove any public downwind of the rig, including partial evacuation or isolation. Notify necessary public safety personnel and the New Mexico Oil & Gas of the situation.
 - B. Isolate area and prevent entry by unauthorized persons into the 100 ppm ROE.
 - C. Remove all personnel to the Safe Briefing Area.
 - D. Notify public safety personnel for help with maintaining roadblocks and implementing evacuation. Phone number list attached.
 - E. Determine and proceed with the best possible plan to regain control of the well. Maintain tight security and safety measures.
- III. Responsibility:
 - A. The Company Approved Supervisor shall be responsible for the total implementation of the plan.
 - B. The Company Approved Supervisor shall be in complete command during any emergency.
 - C. The Company Approved Supervisor shall designate a back up Supervisor in the event that he/she is not available.

EMERGENCY PROCEDURE IMPLEMENTATION

I. Drilling or Tripping

A. All Personnel

1. When alarm sounds, don escape unit and report to upwind Safe Briefing Area.
2. Check status of other personnel (buddy system).
3. Secure breathing apparatus.
4. Wait for orders from supervisor.

B. Drilling Foreman

1. Report to the upwind Safe Briefing Area.
2. Don Breathing Apparatus and return to the point of release with the Tool Pusher or Driller (buddy system).
3. Determine the concentration of H₂S.
4. Assess the situation and take appropriate control measures.

C. Tool Pusher

1. Report to the upwind Safe Briefing Area.
2. Don breathing apparatus and return to the point of release with the Drilling Foreman or the Driller (buddy system).
3. Determine the concentration.
4. Assess the situation and take appropriate control measures.

D. Driller

1. Check the status of other personnel (in a rescue attempt, always use the buddy system).
2. Assign the least essential person to notify the Drilling Foreman and Tool Pusher, in the event of their absence.

3. Assume the responsibility of the Drilling Foreman and the Tool Pusher until they arrive, in the event of their absence.

E. Derrick Man and Floor Hands

1. Remain in the upwind Safe Briefing Area until otherwise instructed by a supervisor.

F. Mud Engineer

1. Report to the upwind Safe Briefing Area.
2. When instructed, begin check of mud for pH level and H₂S level.

G. On-site Safety Personnel

1. Don Breathing Apparatus.
2. Check status of all personnel.
3. Wait for instructions from Drilling Foreman or Tool Pusher.

II. Taking a Kick

- A. All personnel report to the upwind Safe Briefing Area.
- B. Follow standard BOP procedures.

III. Open Hole Logging

- A. All unnecessary personnel should leave the rig floor.
- B. Drilling Foreman and Safety Personnel should monitor the conditions and make necessary safety equipment recommendations.

IV. Running Casing or Plugging

- A. Follow "Drilling or Tripping" procedures.
- B. Assure that all personnel have access to protective equipment.

SIMULATED BLOWOUT CONTROL DRILLS

All drills will be initiated by activating alarm devices (air horn). Use one long blast on the air horn for ACTUAL and SIMULATED Blowout Control Drills. This operation will be performed by the Drilling Foreman or Tool Pusher at least one time per week for each of the following conditions, with each crew:

Drill # 1 Bottom Drilling

Drill # 2 Tripping Drill Pipe

In each of these drills, the initial reaction time to shutting in the well shall be timed as well as the total time for the crew to complete its entire pit drill assignment. The times must be recorded on the IADC Driller's Log as "Blowout Control Drill".

Drill No.:			
Reaction Time to Shut-In:	minutes,	seconds.	
Total Time to Complete Assignment:	minutes,	seconds.	

I. Drill Overviews

A. Drill No. 1- Bottom Drilling

1. Sound the alarm immediately.
2. Stop the rotary and hoist kelly joint above the rotary table.
3. Stop the circulatory pump.
4. Close the drill pipe rams.
5. Record casing and drill pipe shut-in pressures and pit volume increases.

B. Drill No. 2 – Tripping Drill Pipe

1. Sound the alarm immediately.
2. Position the upper tool joint just above the rotary table and set the slips.

3. Install a full opening valve or inside blowout preventor tool in order to close the drill pipe.
4. Close the drill pipe rams.
5. Record the shut-in annular pressure.

II. Crew Assignments

A. Drill No. 1 – Bottom Drilling

1. Driller
 - a) Stop the rotary and hoist kelly joint above the rotary table.
 - b) Stop the circulatory pump.
 - c) Check flow.
 - d) If flowing, sound the alarm immediately.
 - e) Record the shut-in drill pipe pressure.
 - f) Determine the mud weight increase needed or other courses of action.
2. Derrickman
 - a) Open choke line valve at BOP.
 - b) Signal Floor Man # 1 at accumulator that choke line is open.
 - c) Close choke and upstream valve after pipe tams have been closed.
 - d) Read the shut-in annular pressure and report readings to Driller.
3. Floor Man # 1
 - a) Close the pipe rams after receiving the signal from the Derrickman.
 - b) Report to Driller for further instructions.

4. Floor Man # 2
 - a) Notify the Tool Pusher and Operator Representative of the H₂S alarms.
 - b) Check for open fires and, if safe to do so, extinguish them.
 - c) Stop all welding operations.
 - d) Turn-off all non-explosion proof lights and instruments.
 - e) Report to Driller for further instructions.
5. Tool Pusher
 - a) Report to the rig floor.
 - b) Have a meeting with all crews.
 - c) Compile and summarize all information.
 - d) Calculate the proper kill weight.
 - e) Ensure that proper well procedures are put into action.
6. Operator Representative
 - a) Notify the Drilling Superintendent.
 - b) Determine if an emergency exists and if so, activate the contingency plan.

B. Drill No. 2 – Tripping Pipe

1. Driller
 - a) Sound the alarm immediately when mud volume increase has been detected.
 - b) Position the upper tool joint just above the rotary table and set slips.
 - c) Install a full opening valve or inside blowout preventor tool to close the drill pipe.
 - d) Check flow.

- e) Record all data reported by the crew.
- f) Determine the course of action.

2. Derrickman

- a) Come down out of derrick.
- b) Notify Tool Pusher and Operator Representative.
- c) Check for open fires and, if safe to do so, extinguish them.
- d) Stop all welding operations.
- e) Report to Driller for further instructions.

3. Floor Man # 1

- a) Pick up full opening valve or inside blowout preventor tool and stab into tool joint above rotary table (with Floor Man # 2).
- b) Tighten valve with back-up tongs.
- c) Close pipe rams after signal from Floor Man # 2.
- d) Read accumulator pressure and check for possible high pressure fluid leaks in valves or piping.
- e) Report to Driller for further instructions.

4. Floor Man # 2

- a) Pick-up full opening valve or inside blowout preventor tool and stab into tool joint above rotary table (with Floor Man # 1).
- b) Position back-up tongs on drill pipe.
- c) Open choke line valve at BOP.
- d) Signal Floor Man # 1 at accumulator that choke line is open.
- e) Close choke and upstream valve after pipe rams have been closed.
- f) Check for leaks on BOP stack and choke manifold.

- g) Read annular pressure.
- h) Report readings to the Driller.

5. Tool Pusher

- a) Report to the rig floor.
- b) Have a meeting with all of the crews.
- c) Compile and summarize all information.
- d) See that proper well kill procedures are put into action.

6. Operator Representative

- a) Notify Drilling Superintendent
- b) Determine if an emergency exists, and if so, activate the contingency plan.

IGNITION PROCEDURES

Responsibility:

The decision to ignite the well is the responsibility of the DRILLING FOREMAN in concurrence with the STATE POLICE. The State Police shall be the Incident Command on the scene of any major release. Intentional ignition must be coordinated with the NMOCD and local officials. In the event the Drilling Foreman is incapacitated, it becomes the responsibility of the RIG TOOL PUSHER. This decision should be made only as a last resort and in a situation where it is clear that:

1. Human life and property are endangered.
2. There is no hope of controlling the blowout under the prevailing conditions.

If time permits, notify the main office, but do not delay if human life is in danger. Initiate the first phase of the evacuation plan.

Instructions for Igniting the Well:

1. Two people are required for the actual igniting operation. Both men must wear self-contained breathing apparatus and must use a full body harness and attach a retrievable safety line to the D-Ring in the back. One man must monitor the atmosphere for explosive gases with the LEL monitor, while the Drilling Foreman is responsible for igniting the well.
2. The primary method to ignite is a 25mm flare gun with a range of approximately 500 feet.
3. Ignite from upwind and do not approach any closer than is warranted.
4. Select the ignition site best suited for protection and which offers an easy escape route.
5. Before igniting, check for the presence of combustible gases.
6. After igniting, continue emergency actions and procedures as before.
7. All unassigned personnel will limit their actions to those directed by the Drilling Foreman.

NOTE: After the well is ignited, burning Hydrogen Sulfide will convert to Sulfur Dioxide (SO₂), which is also highly toxic. Do not assume the area is safe after the well is ignited.

TRAINING REQUIREMENTS

When working in an area where Hydrogen Sulfide (H₂S) might be encountered, definite training requirements must be carried out. The Company Supervisor will ensure that all personnel at the well site, whether regularly assigned, contracted, or employed on an unscheduled basis, have had adequate training by a qualified instructor in the following:

1. Hazards and Characteristics of Hydrogen Sulfide and Sulfur Dioxide.
2. Physicals effects of Hydrogen Sulfide on the human body.
3. Toxicity of Hydrogen Sulfide and Sulfur Dioxide.
4. H₂S detection, emergency alarm and sensor location.
5. Emergency rescue.
6. First aid and artificial resuscitation.
7. The effects of Hydrogen Sulfide on metals.
8. Location safety.

In addition, Supervisory Personnel will be trained in the following areas:

1. If high tensile tubular are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well as well as blowout prevention and well control procedures.
3. The contents and requirements of the H₂S Drilling Operations Contingency Plan and the Public Protection Plan.

Service company personnel and visiting personnel must be notified if the zone contains H₂S, and each service company must provide adequate training and equipment for their employees before they arrive at the well site.

EMERGENCY EQUIPMENT

As stated in the BLM Onshore Order 6, for wells located in a known H₂S areas, H₂S equipment will be rigged up after setting surface casing. For wells located inside known H₂S areas, the flare pit will be located 150' from the location and for wells located outside known H₂S areas, the flare pit will be located 100' away from the location. (See page 6 of Survey plat package and diagram B or C.)

It is not anticipated that any H₂S is in the area, however in the event that H₂S is encountered, the attached H₂S Contingency Plan will be implemented. (Please refer to diagrams B or C for choke manifold and closed loop system layout.) See H₂S location layout diagram for location of all H₂S equipment on location.

All H₂S safety equipment and systems will be installed, tested and be operational when drilling reaches a depth of 500' above, or three days prior to penetrating a known formation containing H₂S.

Lease Entrance Sign:

Caution signs should be located at all roads providing direct access to the location. Signs shall have a yellow background with black lettering and contain the words "CAUTION" and "POISON GAS" that is legible from a distance of at least 50 feet.

**LEASE NAME
CAUTION – POTENTIAL POISON GAS
HYDROGEN SULFIDE
NO ADMITTANCE WITHOUT AUTHORIZATION**

Windssocks or Wind Streamers:

- A minimum of two 10" windssocks located at strategic locations so that they may be seen from any point on location.
- Wind streamers (if preferred) should be placed at various locations on the well site to ensure wind consciousness at all times. (Corners of location)

Hydrogen Sulfide Detector and Alarms:

- H₂S monitors with alarms will be located on the rig floor, at the cellar, and at the mud pits. These monitors will be set to alarm at 10 PPM with a red light and to alarm at 15 PPM with a red light and audible alarm.

Well Condition Flags:

The Well Condition flags should be located at all roads providing direct access to the location. It should have three (3) color coded flags (green, yellow and red) that will be used to denote the following location conditions:

GREEN – Normal Operating Conditions
YELLOW – Potential Danger
RED – Danger, H₂S Gas Present

Respiratory Equipment:

- Fresh air breathing equipment should be placed at the company supervision trailer and the safe briefing areas and should include the following:
 - A minimum of two SCBA's at each briefing area and the supervisor company supervision trailer.
 - Enough air line units to operate safely, anytime the H₂S concentration reaches the IDLH level (100 PPM).
 - Cascade system with enough breathing air hose and manifolds to reach the rig floor, the derrickman and the other operation areas.

Fire Extinguishers:

Adequate fire extinguishers shall be located at strategic locations.

Mud Program:

The mud program has been designed to minimize the volume of H₂S circulated to the surface. Proper mud weight, safe drilling practices and the use of H₂S scavengers will minimize hazards when penetrating H₂S bearing zones.

Metallurgy:

All drill strings, casing, tubing, wellhead; blowout preventer, drilling spools, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.

Well Control Equipment:

- Flare Line (See page 6 of survey plat package for flare line reference).
- Choke manifold (See diagram B or C and refer to H2S location diagram for location of important H2S safety items).
- Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing units.
- Auxiliary equipment may include, if applicable, annular preventer & rotating head.

Communication Equipment:

- Proper communication equipment such as cell phones or 2 – way radios should be available for communication between the company man's trailer, rig floor and tool pusher's trailer.

Well Testing:

- There will be no drill stem testing.

Evacuation Plan:

- Evacuation routes should be established prior to spudding the well.
- Should be discussed with all rig personnel.

Designated Areas:

Parking and Visitor area:

- All vehicles are to be parked at a pre-determined safe distance from the wellhead.
- A smoking area will be designated at a pre-determined safe distance from the wellhead and any other possible flammable areas.

Safe Briefing Areas:

- Two Safe Briefing Areas shall be designated on either side of the location at the maximum allowable distance from the well bore so they offset prevailing winds or they are at a 180 degree angle if wind directions tend to shift in the area.

- Personal protective equipment should be stored at both briefing areas or if a moveable cascade trailer is used, it should be kept upwind of existing winds. When wind is from the prevailing direction, both briefing areas should be accessible.

NOTE:

- Additional equipment will be available at Indian Fire and Safety in Hobbs, NM or at Total Safety in Hobbs, NM.

EVACUATION PLAN

General Plan

The direct lines of action to protect the public from hazardous gas situations are as follows:

1. When the company approved supervisor (Drilling Foremen, Tool Pusher or Driller) determine that Hydrogen Sulfide gas cannot be limited to the well location, and the public will be involved, he will activate the evacuation plan. Escape routes are noted on the Area Map.
2. Company safety personnel or designee will notify the appropriate local government agency that a hazardous condition exists and evacuation needs to be implemented.
3. Company approved safety personnel that have been trained in the use of the proper emergency equipment will be utilized.
4. Law enforcement personnel (State Police, Local Police Department, Fire Department, and the Sheriff's Department) will be called to aid in setting up and maintaining road blocks. Also, they will aid in evacuation of the public if necessary.

NOTE: Law enforcement personnel will not be asked to come into a contaminated area. Their assistance will be limited to uncontaminated areas. Constant radio contact will be maintained with them.

5. After the discharge of gas has been controlled, Company approved safety personnel will determine when the area is safe for re-entry.

See Emergency Action Plan

Contacting Authorities

BOPCO L.P. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including directions to site. The following call list of essential and potential responders has been prepared for use during a release. (Operator Name)'s response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER).

H₂S CONTINGENCY PLAN EMERGENCY CONTACTS

BOPCO L.P. Midland Office

432-683-2277

Key Personnel

<u>Name</u>	<u>Title</u>	<u>Cell Phone Number</u>
Stephen Martinez	Drilling & Completions Manager	432-556-0262
Charles Warne	Division Engineer	432-312-4431
Don Wood	Division Drilling Specialist	432-266-2674
Leo Bojorquez	Area Drilling Superintendent	702-280-4424
Chris Giese	Engineer	432-661-7328
Chris Volek	Engineer	785-979-2643
Brian Braun	Engineer	210-683-9849
Jeremy Braden	Engineer	432-312-1113
Kevin Burns	Engineer	432-934-5499

Artesia

Ambulance	911
State Police	575-746-2703
City Police	575-746-2703
Sheriff's Office	575-746-9888
Fire Department	575-746-2701
Local Emergency Planning Committee	575-746-2122
New Mexico Oil Conservation Division	575-748-1283

Carlsbad

Ambulance	911
State Police	575-885-3137
City Police	575-885-2111
Sheriff's Office	575-887-7551
Fire Department	575-887-3798
Local Emergency Planning Committee	575-887-6544
US Bureau of Land Management	575-887-6544

New Mexico Emergency Response Commission (Santa Fe)	505-476-9600
24 Hour	505-827-9126
New Mexico State Emergency Operations Center	505-476-9635
National Emergency Response Center (Washington, DC)	800-424-8802

Other

Wild Well Control	432-550-6202 (Permian Basin)
Cudd PressureControl	432-580-3544 or 432-570-5300 (Permian Basin)
Flight For Life – 4000 24 th St. Lubbock, Texas	806-743-9911
Aerocare – R3, Box 49F, Lubbock, Texas	806-747-8923
Med Flight Air Amb – 2301 Yale Blvd SE #D3, Albuquerque, NM	505-842-4433
S B Air Med Service – 2505 Clark Carr Loop SE, Albuquerque, NM	505-842-4949
Indian Fire and Safety – 3317 NW Cnty Rd, Hobbs, NM	575-393-3093
Total Safety – 3229 Industrial Dr., Hobbs, NM	575-392-2973

TOXIC EFFECTS OF HYDROGEN SULFIDE

Hydrogen Sulfide is extremely toxic. The acceptable ceiling concentration for eight-hour exposure is 10 PPM, which is .001% by volume. Hydrogen Sulfide is heavier than air (specific gravity = 1.192) and colorless. It forms an explosive mixture with air between 4.3 and 46.0 percent by volume. Hydrogen sulfide is almost as toxic as hydrogen cyanide and is between five and six times more toxic than carbon monoxide. Toxicity data for hydrogen sulfide and various other gases are compared in Table I. Physical effects at various Hydrogen Sulfide exposure levels are shown in Table II.

Table I - TOXICITY OF VARIOUS GASES

Common Name	Chemical Formula	Specific Gravity (SC=1)	Threshold Limit (1)	Hazardous Limit (2)	Lethal Concentration (3)
Hydrogen Cyanide	HCN	0.94	10 PPM	150 PPM/HR	300 PPM
Hydrogen Sulfide	H ₂ S	1.18	10 PPM	250 PPM/HR	600 PPM
Sulfur Dioxide	SO ₂	2.21	5 PPM	--	1000 PPM
Chlorine	CL ₂	2.45	1 PPM	4 PPM/HR	1000 PPM
Carbon Monoxide	CO	0.97	50 PPM	400 PPM/HR	1000 PPM
Carbon Dioxide	CO ₂	1.52	5000 PPM	5%	10%
Methane	CH ₄	0.55	90,000 PPM	Combustible in air	Above 5%

- 1) **Threshold Limit** – Concentration at which it is believed that all worker may be repeatedly exposed day after day without adverse effects.
- 2) **Hazardous Limit** – Concentration that will cause death with short-term exposure.
- 3) **Lethal Concentration** – Concentration that will cause death with short-term exposure.

Table II – PHYSICAL EFFECTS OF HYDROGEN SULFIDE

Percent (%)	PPM	Concentration Grains 100 STD. FT3*	Physical Effects
0.001	< 10	00.65	Obvious & unpleasant odor.
0.002	10	01.30	Safe for 8 hours of exposure.
0.010	100	06.48	Kills smell in 3-15 minutes. May sting eyes & throat.
0.020	200	12.96	Kills smell shortly; stings eyes & throat.
0.050	500	32.96	Dizziness; Breathing ceases in a few minutes. Needs prompt artificial respiration.
0.070	700	45.36	Unconscious quickly; Death will result if not rescued promptly.
0.100	1000	64.30	Unconscious at once; Followed by death within minutes.

- At 15.00 PSIA and 60° F.

USE OF SELF-CONTAINED BREATHING APPARATUS

1. Anyone who uses an SCBA shall: Be approved by a physician or licensed health care practitioner; Pass a fit test; Be trained in donning and doffing, proper use, including how to ensure a proper face seal, conducting an inspection of the SCBA, and conduct proper maintenance.
2. Such items as facial hair (beard or sideburns) and eyeglasses will not allow a proper face mask seal.
3. Anyone reasonably expected to wear SCBA's shall have these items removed before entering a toxic atmosphere.
4. A special mask with a mount for prescription glasses must be obtained for anyone who must wear eyeglasses in order to see while using an SCBA.
5. SCBA's should be worn in H₂S concentrations above 10 PPM.

RESCUE & FIRST AID FOR H₂S POISONING


DO NOT PANIC – REMAIN CALM – THINK

1. Hold your breath – do not inhale first.
2. Put on SCBA.
3. Remove victim(s) to fresh air as quickly as possible. Go upwind from source or at right angle to the wind. Do not go downwind.
4. Briefly apply chest pressure – using arm lift method of artificial respiration to clean victim's lungs and to avoid inhaling any toxic gas directly from victim's lungs.
5. Provide artificial respiration if needed.
6. Provide for prompt transportation to the hospital and continue giving artificial respiration if needed.
7. Inform hospital/medical facilities of the possibility of H₂S gas poisoning before they treat.

Besides basic first aid, everyone on location should have a good working knowledge of artificial respiration and CPR, as well as first aid for eyes and skin contact with liquid H₂S.

Proposed H2S Safety Schematic

- 1) Location of windsocks.
- 2) Location of H2S alarms
- 3) Location of briefing areas.
- 4) Terrain of surrounding area (Please refer to page 2 of survey plat package also see point 11 of multi-surface use plan)
- 5) Location of flare line(s) and pit(s) (Please refer to diagram 2 choke manifold diagram and or page six of survey plat packet)
- 6) Location of caution and/or danger signs.
- 7) Location of Breathing Equipment



Location On-Site Notes

Location on-site conducted by Cecil Watkins-BOPCO L.P., Jarrel Brooks-BOPCO L.P., Chris Boyd-BOPCO L.P., Jesse Rice-BLM, and Robert Gomez-Basin Surveys on 02/07/2014. The Poker Lake Unit 455H was approved as is with the surface footage call of 1890' FSL & 1670' FEL of Sec 22-T25S-R30E. Location layout is as follows: v-door will face the north, frac tank pad will be on the south/southwest corner, access road will enter location from the northeast corner and topsoil will be stockpiled to the east side of location.

MULTI-POINT SURFACE USE PLAN

NAME OF WELL: Poker Lake Unit #455H

LEGAL DESCRIPTION

SURFACE: 1890' FSL, 1670' FEL, Section 22, T25S, R30E, Eddy County, NM.

BHL: 1890' FSL, 2090' FWL, Section 21, T25S, R30E, Eddy County, NM.

POINT 1: EXISTING ROADS

- A) Proposed Well Site Location:

See Form C-102 (Survey Plat).

- B) Existing Roads:

From the junction of Rock Dove and Hedgehog, go northeast on Rock Dove for 1.3 miles to the proposed lease road.

- C) Existing Road Maintenance or Improvement Plan:

Existing roads will be maintained and kept in the same or better condition than before operations began. See the Well Pad Layout and Topo Map of the survey plat (Sheet 1 and 2 of plat package)

POINT 2: NEW PLANNED ACCESS ROUTE

- A) Route Location:

There will be 2,271.6' of new road built. (See the Well Pad Layout of the survey plat (Sheet 1 of plat package).

- B) Width

14' wide

- C) Maximum Grade

Grade to match existing topography or as per BLM requirements.

- D) Turnout Ditches

As required by BLM stipulations.

- E) Culverts, Cattle Guards, and Surfacing Equipment

If required, culverts and cattle guards will be set per BLM Specs.

POINT 3: LOCATION OF EXISTING WELLS

The following wells are located within a one-mile radius of the location site. See the One-Mile Radius Map (Sheet 5 of the plat package).

Existing wells..... 4 (Four)
Water wells..... 0 (Zero)

POINT 4: LOCATION OF EXISTING OR PROPOSED FACILITIES

A) A BOPCO, L.P. operated production facility is located within the ideal operating range of the Poker Lake Unit 455H.

B) In the Event of Production:

Poker Lake Unit 455H will pipe production to Poker Lake Unit 421 Battery. A new 2-7/8" or 3-1/2" in diameter steel flowline is to be run above ground for approximately 2.30 miles, working pressure of the line is going to be 125 psi. The flowline is expected to carry oil, water, and gas. In the event that the power is not accessible or insufficient, power will be supplied by a generator until adequate power can be supplied from the utility company.

C) Rehabilitation of Disturbed Areas Unnecessary for Production:

Following the construction, those access areas required for continued production will be graded to provide drainage and minimize erosion. The areas unnecessary for use will be graded to blend in with the surrounding topography (see Point 10).

POINT 5: LOCATION AND TYPE OF WATER SUPPLY

A) Location and Type of Water Supply

Fresh water will be hauled from Johnson Station 50 miles east of Carlsbad, New Mexico or other commercial facilities. Brine water will be hauled from commercial facilities.

B) Water Transportation System

Water hauling to the location will be over the existing and proposed roads.

POINT 6: SOURCE OF CONSTRUCTION MATERIALS

A) Materials

On-site caliche will be used. If this is not sufficient, caliche will be hauled from a BLM approved pit.

B) Land Ownership
Federally Owned

C) Materials Foreign to the Site

No construction materials foreign to this area are anticipated for this drill site.

D) Access Roads

See the Well Pad Layout and Aerial Map of the survey plat (Sheet 1 and 4 of plat package).

POINT 7: METHODS FOR HANDLING WASTE MATERIAL

A) Cuttings

Cuttings will be contained in the roll off bins and disposed at R360 Environmental located in Lea County, NM.

B) Drilling Fluids

Drilling fluids will be contained in the steel pits, frac tanks and disposed at licensed disposal sites.

C) Produced Fluids

Water production will be contained in the steel pits.

Hydrocarbon fluid or other fluids that may be produced during testing will be retained in test tanks. Prior to cleanup operations, any hydrocarbon material in the reserve pit will be removed by skimming or burning as the situation would dictate.

D) Sewage

Current laws and regulations pertaining to the disposal of human waste will be complied with.

E) Garbage

Portable containers will be utilized for garbage disposal during the drilling of this well.

F) Cleanup of Well Site

Upon release of the drilling rig, the surface of the drilling pad will be graded to accommodate a completion rig if electric log analysis indicate potential productive zones. Reasonable cleanup will be performed prior to the final restoration of the site.

POINT 8: ANCILLARY FACILITIES

None required.

POINT 9: WELL SITE LAYOUT

A) Rig Orientation and Layout

The "Rig Layout Schematic" (Sheet 6 of plat package) shows the dimensions of the well pad, closed loop system, and the location of major rig components. Only minor leveling of the well site will be required. No significant cuts or fills will be necessary. **The top soil will be stockpiled on the east side of the location.**

B) Locations of Access Road

See the Well Pad Layout, Topo Map, and Vicinity Map of the survey plat (Sheet 1, 2, and 3 of plat package).

C) Lining of the Pits

No reserve pits - closed loop system.

POINT 10: PLANS FOR RESTORATION OF THE SURFACE

A) Reserve Pit Cleanup - Not applicable. Closed loop drilling fluid system will be used

B) Restoration Plans - Production Developed

BOPCO, L.P. has no plans for interim reclamation to allow for additional wells to be drilled on this pad

C) Restoration Plans - No Production Developed

BOPCO, L.P. has no plans for interim reclamation to allow for additional wells to be drilled on this pad

POINT 11: OTHER INFORMATION

A) On-Site

Location on-site conducted by Cecil Watkins-BOPCO L.P., Jarrel Brooks-BOPCO L.P., Chris Boyd-BOPCO L.P., Jesse Rice-BLM, and Robert Gomez-Basin Surveys on 02/07/2014. The Poker Lake Unit 455H was approved as is with the surface footage call of 1890' FSL & 1670' FEL of Sec 22-T25S-R30E. Location layout is as follows: v-door will face the north, frac tank pad will be on the south/southwest corner, access road will enter location from the northeast corner and topsoil will be stockpiled to the east side of location.

B) Soil

Caliche and sand.

C) Vegetation

Sparse, primarily grasses and mesquite with very little grass.

D) Surface Use

Primarily grazing.

E) Surface Water

There are no ponds, lakes, streams or rivers within several miles of the wellsite.

F) Water Wells

There are no water wells located within a 1 mile radius of the proposed location.

G) Residences and Buildings

None in the immediate vicinity.

H) Historical Sites

None observed.

I) Archeological Resources

No independent archeological survey has been done. This well location is located in the area covered by Memorandum of Agreement – Permian Basin. A Payment of \$1,688.00 fee for this project is included in this application. Any location or construction conflicts will be resolved before construction begins. Please see diagram 4 for flowline route.

J) Surface Ownership

The well site is on federally owned land. There will be 2,271.6' of new road required for this location.

K) Well signs will be posted at the drilling site.

L) Open Pits

No open pits will be used for drilling or production. Any open top tanks will be netted.

M) Terrain

Slightly rolling hills.

POINT 12: OPERATOR'S FIELD REPRESENTATIVE

(Field personnel responsible for compliance with development plan for surface use).

DRILLING

Stephen Martinez
Box 2760
Midland, Texas 79702
(432) 683-2277

PRODUCTION

Gary Fletcher
3104 East Green Street
Carlsbad, New Mexico 88220
(575) 887-7329

Fritz Schoch
Box 2760
Midland, Texas 79702
(432) 683-2277

WBM