ubmit 1 Copy To Appropriate District	State of New Mexico			Form C-103
<u>District 1</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		WELL API NO.	Revised July 18, 2013
<u>District II</u> – (575) 748-1283	OH CONCEDUATION DIVISION		30-015-23566	
811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178	OIL CONSERVATION DIVISION		5. Indicate Type o	
1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.		STATE 🗵	
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505		6. State Oil & Gas LG-827	Lease No.
87505	neis Dr., Sama-re, Nivi			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			7. Lease Name or Unit Agreement Name Arnold OR State	
PROPOSALS.)			8. Well Number	
1. Type of Well: Oil Well Gas Well Other P&A			l o company	
Name of Operator Yates Petroleum Corporation			9. OGRID Number 025575	
3. Address of Operator			10. Pool name or Wildcat	
105 South Fourth Street, Artesia, NM 88210			Wildcat; Abo	
4. Well Location				
Unit Letter O :	660 feet from the So	outh line and	1980 feet from	the <u>East</u> line
Section 34	Township 18S	Range 24E	NMPM Eddy	County
	11. Elevation (Show whether I		c.)	
U. M.	3,7	'48' GR		$(x^{2}x^{2})$, (x^{2}) , $(x^{2}x^{2})$, $(x^{2}x^{2})$
12. Check	Appropriate Box to Indicate	Nature of Notice	e, Report or Other I	Data
	• •			
NOTICE OF II PERFORM REMEDIAL WORK □	NTENTION TO: PLUG AND ABANDON	REMEDIAL WO	BSEQUENT REF	'ORTOF: ALTERING CASING □
TEMPORARILY ABANDON		1		PANDA
PULL OR ALTER CASING	<u> </u>	CASING/CEME		711271
DOWNHOLE COMMINGLE		0,10,110,000,000		
CLOSED-LOOP SYSTEM				
OTHER:		OTHER:		
	pleted operations. (Clearly state a			
proposed completion or re	vork). SEE RULE 19.15.7.14 NM	IAC. For Multiple C	ompletions: Attach we	elibore diagram of
proposed completion of re	completion.			
6/20-22/14 – NU BOP. 6/24/14 – Loaded hole with 200 bb		s "C" Neat at 5189'.	Calc TOC is 4913'. Di	splaced with 28 bbls fresh
water. WOC. Tagged TOC at 5088		5 1/22 CIDD at 40002	Tanadan an CIDD at	44907 C
6/25/14 – Made 4.6" gauge ring/junk basket run down to 4900'. Set 5 ½" CIBP at 4880'. Tagged up on CIBP at 4880'. Spotted 25 sx Class "C" Neat Cement from 4880' to 4630'. Circulated salt gel to 3800'. WOC. Tagged TOC at 4649'. Perf'd 4 squeeze holes at 3880'.				
Tried to break circulation. Pressured up to 1100 psi. Could not pump into squeeze perfs at 3880'.				
6/26/14 - Spotted 25 sx Class "C" Neat across squeeze perfs at 3880' while spotting plugging mud up to 1900'. Calc TOC is 3688'.				
WOC. Tagged TOC at 3720'. Perf'd 4 squeeze holes at 1904'. Broke circulation through 5-1/2" x 8-5/8"casing. Spotted 40 sacks Class "C" Neat Cement thru squeeze perfs at 1904'. Calc TOC is 1741'.				
• •				
Tile Supaguent	0102 Q. Q. D. J +	CONTINU	ED ON NEXT PAGE	
Tile Dubelquene	103 An govercous	nc :		NM OIL CONSERVATION
	release	/		ARTESIA DISTRICT
Spud Date:	Rig Release			JUL 2 1 2014
,				
			<u> </u>	RECEIVED
I hereby certify that the information	above is true and complete to the	e best of my knowled	lge and belief. Liabilit	v under bond is retained pending receipt
\sim \sim			of C-10	3 (Subsequent Report of Well Plugging)
SIGNATURE IN SIGNATURE	TITLE D			nav be found at OCD Web Page under "This page 4.54 page and a common service of the comm
STOWN TOKE THE	TILE R	egulatory Reporting	reconnician DATE	
Type or print name Julie Thornton	n E-mail address: jthornton@	@yatespetroleum.com	<u>n</u> PHONE: <u>57</u>	75-748-4190
For State Use Only				_
ADDROVED BY:	Wille TITLE DI	3/1/5		- 7/4/11
APPROVED BY: Conditions of Approval (if any):	TILE TO	11 (11 Day	DAT	E // //

Arnold OR State #1 Sec 34-T18S-R24E Eddy County, New Mexico Page 2

Form C-103 Continued:

6/27/14 – Broke circulation up 5-1/2" x 8-5/8" with 5 bbls water. Spotted 65 sx Class "C" with 2% CaCl. Calc TOC 1741'. WOC 4 hours. Tagged TOC at 1680'. Perf'd 4 squeeze holes at 1038'. Pumped 40 sx Class "C" Neat. Displaced down to 874'.
6/28-29/14 – Tagged TOC at 838'. Perf'd at 488'. Nippled down BOP. Broke circulation thru 5-1/2" x 8-5/8" casing. Circulated 125 sx Class "C" Neat to surface.

7/17/14 – Installed dry hole marker, Cleaned and secured location. WELL IS PLUGGED AND ABANDONED.

Regulatory Reporting Technician

July 21), 2014