

Submit To Appropriate District Office.
Two Copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
July 17, 2008

1. WELL API NO.
30-015-42156
2. Type of Lease
 STATE FEE FED/INDIAN
3. State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

4. Reason for filing:
 COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only)
 C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)

5. Lease Name or Unit Agreement Name
ENRON STATE
6. Well Number: **#21**

NM OIL CONSERVATION
ARTESIA DISTRICT

7. Type of Completion:
 NEW WELL WORKOVER DEEPENING PLUGBACK DIFFERENT RESERVOIR OTHER

8. Name of Operator: **LRE OPERATING, LLC**
9. OGRID: 281994

10. Address of Operator: c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401
11. Pool name or Wildcat: Red Lake, Glorieta Yeso NE (96836)

RECEIVED

OCT 20 2014

12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	D	32	17-S	28-E		385	North	900	West	Eddy
BH:										

13. Date Spudded 9/9/14
14. Date T.D. Reached 9/13/14
15. Date Drilling Rig Released 9/14/14
16. Date Completed (Ready to Produce) 9/29/14
17. Elevations (DI and RKB, RT, GR, etc.): 3676' GR
18. Total Measured Depth of Well 4250'
19. Plug Back Measured Depth 4170'
20. Was Directional Survey Made? Yes
21. Type Electric and Other Logs Run Casing Hole Neutron

22. Producing Interval(s), of this completion - Top, Bottom, Name
3417'-3720' - Yeso, 3810'-4140' - Yeso

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24# J-55	420'	11"	400 sx CI C	0'
5-1/2"	17# J-55	4232'	7-7/8"	325 sx 35/65 Poz/C + 550 sx C	0'

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET
					2-7/8"	3999'

26. Perforation record (interval, size, and number)	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.
Yeso: 3417'-3720', 43-0.41" holes Yeso: 3810'-4140', 34-0.41" holes	DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 3417'-3720' 3000 gals 15% HCL; fraced w/159,475# brady & 65,512# super LC 16/30 sand in 25# X-linked gel. 3810'-4140' 3000 gals 15% HCL; fraced w/162,922# brady & 68,129# super LC 16/30 sand in 25# X-linked gel.

28. PRODUCTION

Date First Production READY	Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping	Well Status (Prod. or Shut-in) Pumping					
Date of Test Within 30 days	Hours Tested	Choke Size	Prod'n For Test Period:	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
To Be Sold
30. Test Witnessed By: Jerry Smith

31. List Attachments
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.
33. If an on-site burial was used at the well, report the exact location of the on-site burial:

Latitude Longitude NAD 1927 1983

I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature: *Mike Pippin*
Printed Name: Mike Pippin Title: Petroleum Engineer Date: 10/17/14

E-mail Address: mike@pippinllc.com

AB

INSTRUCTIONS

ENRON STATE #21 -- New Well

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "A"
T. Salt	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers 588'	T. Devonian	T. Cliff House	T. Leadville
T. Queen 1149'	T. Silurian	T. Menefee	T. Madison
T. Grayburg 1566'	T. Moitaya	T. Point Lookout	T. Elbert
M. San Andres 1882'	T. Simpson	T. Mancos	T. McCracken
T. Glorieta 3323'	T. McKee	T. Gallup	T. Ignacio Otzte
T. Yeso 3417'	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand	T. Morrison	
T. Drinkard	T. Bone Springs	T. Todilto	
T. Abo	T.	T. Entrada	
T. Wolfcamp	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
 No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
			- On File -				