Submit 1 Copy To Appropriate District Office	State of New M			Form C-103
District 1 - (575) 393-6161	Energy, Minerals and Nat	tural Resources	WELT ADDAG	Revised August 1, 2011
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283		·	WELL API NO.	
811 S. First St., Artesia, NM 88210	OÍL CONSERVATIO		5. Indicate Type of	Lease
District III - (505) 334-6178	1220 South St. Fra	ancis Dr.	STATE	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV - (505) 476-3460	Santa Fe, NM 8	87505	6. State Oil & Gas	
1220 S. St. Francis Dr., Santa Fe, NM				
87505 SUNDRY NOT	ICES AND REPORTS ON WELL	S	7. Lease Name or I	Jnit Agreement Name
(DO NOT USE THIS FORM FOR PROPO	DSALS TO DRILL OR TO DEEPEN OR P	LUG BACK TO A	,	
DIFFERENT RESERVOIR. USE "APPL PROPOSALS:)	ICATION FOR PERMIT" (FÖRM.C-101).	FOR SUCH	Washington 33 State	s ballery.
1. Type of Well: Oil Well	Gas Well 🔲 Other		8. Well Number	,
2. Name of Operator			9. OGRID Number	·
Apache Corporation			873	
3. Address of Operator			10. Pool name or W	
303 Veterans Airpark Lane, Suite 3	000 Midland, TX 79705		Yeso (96830) & Gray	yburg-San Andres (3230)
4. Well Location			·	
Unit Letter	feet from the			
Section 33		Range 28E		County Eddy
	11. Elevation (Show whether D	R, RKB, RT, GR, etc.		
				× ,
12. Check	Appropriate Box to Indicate 1	Nature of Notice,	Report or Other D	lata
	NTENTION TO:	SUB	SEQUENT REP	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR				
TEMPORARILY ABANDON				AND A
PULL OR ALTER CASING		CASING/CEMEN		
			·, · · · · · · · · · · · · · · · · · ·	
OTHER: Flare Gas		OTHER:	J	
	pleted operations. (Clearly state al ork). SEE RULE 19.15.7.14 NMA			
proposed completion or re			mpictions. Attach we	none diagram of
		· · · · · · · · · · · · · · · · · · ·	•	
Apache is requesting permission	to tomporarily tiara all of the Wyashi		1 - 4	United and the second second second second
measured prior to flaring The AF	1# for each well are as follows:	ngion 33 Glate Wells.	Intermittent flaring wil	Il occur and gas will be
measured prior to flaring. The AF	Pl# for each well are as follows:			
measured prior to flaring. The AF 30-015-30299 30-0	PI# for each well are as follows: 15-22821 30-015-398	95 30-0	015-40020	30-015-40078
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398	95 - 30-(83 - 30-(015-40020 015-40021	30-015-40078 30-015-40114
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0	PI# for each well are as follows: 15-22821 30-015-398	95 30-(83 30-(84 30-(015-40020	30-015-40078
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30138 30-0 30-015-30189 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-30334 30-015-398	95 30-(83 30-(84 30-(85 30-(86 30-(015-40020 015-40021 015-40022	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40115 30-015-40111
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30138 30-0 30-015-30189 30-0 30-015-30190 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-30334 30-015-398 15-30334 30-015-398 15-01690 30-015-400	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 15 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40088	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40111
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30138 30-0 30-015-30189 30-0 30-015-30190 30-0 30-015-30191 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-30334 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 115 30-0 114 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40088 015-40089	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40111 30-015-40116 30-015-40117
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30138 30-0 30-015-30190 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30195 30-015-398 15-30334 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 15 30-0 14 30-0 16 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40088 015-40089 015-40089	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40117 30-015-40112
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30138 30-0 30-015-30190 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30193 30-0 30-015-22524 30-0 30-015-30194 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30195 30-015-398 15-3034 30-015-398 15-0196 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22124 30-015-400 15-2214 30-015-400	95 30-0 183 30-0 184 30-0 185 30-0 186 30-0 115 30-0 114 30-0 116 30-0 117 30-0 118 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40088 015-40089 015-40090 015-40090 015-40076	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40117 30-015-40112 30-015-40118 30-015-40119
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30138 30-0 30-015-30190 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30193 30-0 30-015-22524 30-0 30-015-30194 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30334 30-015-398 15-30334 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22124 30-015-400	95 30-0 183 30-0 184 30-0 185 30-0 186 30-0 115 30-0 114 30-0 116 30-0 117 30-0 118 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40088 015-40089 015-40090 015-40113	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40117 30-015-40112 30-015-40118
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30190 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22822 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-30334 30-015-398 15-01690 30-015-398 15-22464 30-015-400 15-22605 30-015-400 15-22124 30-015-400 15-22465 30-015-400 15-22465 30-015-400	95 30-0 183 30-0 184 30-0 185 30-0 186 30-0 115 30-0 116 30-0 117 30-0 118 30-0 119 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40088 015-40089 015-40090 015-40090 015-40076	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40116 30-015-40112 30-015-40112 30-015-40118 30-015-40119
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30138 30-0 30-015-30190 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30193 30-0 30-015-22524 30-0 30-015-30194 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30195 30-015-398 15-3034 30-015-398 15-0196 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22124 30-015-400 15-2214 30-015-400	95 30-0 183 30-0 184 30-0 185 30-0 186 30-0 115 30-0 116 30-0 117 30-0 118 30-0 119 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40088 015-40089 015-40090 015-40090 015-40076	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40117 30-015-40112 30-015-40118 30-015-40119
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30190 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22822 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30334 30-015-398 15-30334 30-015-398 15-30196 30-015-398 15-01690 30-015-398 15-22464 30-015-400 15-22124 30-015-400 15-22417 30-015-400 15-22465 30-015-400	95 30-0 183 30-0 184 30-0 185 30-0 186 30-0 115 30-0 116 30-0 117 30-0 118 30-0 119 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40088 015-40089 015-40090 015-40090 015-40076	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40117 30-015-40112 30-015-40118 30-015-40119
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30189 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-22524 30-0 30-015-30194 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30334 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22124 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 914 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 Date:	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40077	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40117 30-015-40112 30-015-40118 30-015-40119
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30190 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22822 30-0	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30334 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22124 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 914 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 Date:	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40077	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40117 30-015-40112 30-015-40118 30-015-40119
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30189 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-22524 30-0 30-015-30194 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30334 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22124 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 914 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 Date:	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40077	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40116 30-015-40112 30-015-40118 30-015-40119
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30189 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-22524 30-0 30-015-30194 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22124 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 914 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 Date:	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40077 ge and belief.	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40116 30-015-40112 30-015-40112 30-015-40118 30-015-40119
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30199 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22524 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22124 30-015-400 15-22417 30-015-400 15-22465 30-015-400 Rig Release I n above is true and complete to the TITLE Reg	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 910 30-0 9119 30-0 912 30-0 913 30-0 914 30-0 915 30-0 916 30-0 917 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40077 ge and belief.	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40112 30-015-40112 30-015-40119 30-015-40120
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30188 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22124 30-015-400 15-22417 30-015-400 15-22465 30-015-400 Rig Release I n above is true and complete to the TITLE Reg	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 918 30-0 919 30-0 918 30-0 919 30-0 914 30-0 915 30-0 916 30-0 917 30-0 918 30-0 919 30-0 918 30-0 919 30-0 910 30-0 910 30-0 9110 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40077 ge and belief.	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40116 30-015-40116 30-015-40112 30-015-40112 30-015-40118 30-015-40119 30-015-40120
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30199 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22524 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22124 30-015-400 15-22417 30-015-400 15-22465 30-015-400 Rig Release I n above is true and complete to the TITLE Reg	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 910 30-0 9119 30-0 912 30-0 913 30-0 914 30-0 915 30-0 916 30-0 917 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40076 015-40077 ge and belief. DAT	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40112 30-015-40112 30-015-40119 30-015-40120
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30199 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22524 30-0 30-015-30194 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22477 30-015-400 15-22465 30-015-400 Rig Release I n above is true and complete to the TITLE Regression of the to	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 910 30-0 9119 30-0 912 30-0 913 30-0 914 30-0 915 30-0 916 30-0 917 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40076 015-40077 ge and belief. DAT	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40112 30-015-40112 30-015-40119 30-015-40120
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30189 30-0 30-015-30190 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22524 30-0 30-015-30194 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22124 30-015-400 15-22417 30-015-400 15-22465 30-015-400 Rig Release I n above is true and complete to the TITLE Reg	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 910 30-0 9119 30-0 9119 30-0 9110 30-0 9110 30-0 91110 30-0 91110 30-0 91110 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40077 ge and belief. DAT	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40117 30-015-40112 30-015-40119 30-015-40120
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30199 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22524 30-0 30-015-30194 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30334 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22124 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 15-22465 30-015-400 I5-22465 30-015-400 I5-22465 30-015-400 I5-22465 30-015-400 I5-22465 30-015-400 I5-22465 30-015-400 Rig Release I Rig Release I n above is true and complete to the TITLE Regression If addression If addression	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 910 30-0 9119 30-0 9119 30-0 9110 30-0 9110 30-0 91110 30-0 91110 30-0 91110 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40076 015-40077 ge and belief. DAT	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40112 30-015-40112 30-015-40119 30-015-40120
measured prior to flaring. The AF 30-015-30299 30-0 30-015-30276 30-0 30-015-30277 30-0 30-015-30138 30-0 30-015-30199 30-0 30-015-30190 30-0 30-015-30191 30-0 30-015-30193 30-0 30-015-30194 30-0 30-015-22524 30-0 30-015-30194 30-0 30-015-22822 30-0 Spud Date:	PI# for each well are as follows: 15-22821 30-015-398 15-30332 30-015-398 15-30195 30-015-398 15-30196 30-015-398 15-01690 30-015-400 15-22464 30-015-400 15-22605 30-015-400 15-22477 30-015-400 15-22465 30-015-400 I5-22465 30-015-400 Rig Release I n above is true and complete to the TITLE Regression of the to	95 30-0 83 30-0 84 30-0 85 30-0 86 30-0 916 30-0 917 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 919 30-0 918 30-0 919 30-0 919 30-0 910 30-0 9119 30-0 9119 30-0 9110 30-0 9110 30-0 91110 30-0 91110 30-0 91110 30-0	015-40020 015-40021 015-40022 015-40023 015-40087 015-40089 015-40090 015-40076 015-40076 015-40077 ge and belief. DAT	30-015-40078 30-015-40114 30-015-40110 30-015-40115 30-015-40111 30-015-40116 30-015-40112 30-015-40112 30-015-40119 30-015-40120

.

.

٠

District 1 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV. 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-129 Revised August 1, 2011

Submit one copy to appropriate District Office

NFO Permit No.

(For Division Use Only)

APPLICATION FOR EXCEPTION TO NO-FLARE RULE 19.15.18.12 (See Rule 19.15.18.12 NMAC and Rule 19.15.7.37 NMAC)

	whose address is1945 Bluestem Road	d, Artesia, NM 88210		
	hereby requests an exception to Rule 19.15.1	00		
	, Yr,	for the following described tank battery (or LACT):		
	Name of Lease	Name of Pool Yeso & Grayburg-SA		
		Section 33 Township 17S Range 28E		
	Number of wells producing into battery	55		
В.	B. Based upon oil production ofbarrels per day, the estimate			
		MCF; Valueper day.		
C.	Name and location of nearest gas gathering facility: DCP / Frontier Empire Abo Plant			
D,	DistanceEstimated c	ost of connection		
Ę.	This exception is requested for the following reasons: DCP & Frontier curtails their gas			
÷		is is an extension to the permit that expires		
	06/30/2014.			
	· · · · · · · · · · · · · · · · · · ·			
PERATOR creby certify		OIL CONSERVATION DIVISION		
ereby certify vision have b	that the rules and regulations of the Oil Conservation een complied with and that the information-given above plete to the best of my knowledge and belief.	Approved Until 100 30, 2014		
ereby certify vision have b rue and com	that the rules and regulations of the Oil Conservation een complied with and that the information given above			
ereby certify vision have b rue and com gnature	that the rules and regulations of the Oil Conservation een complied with and that the information given above plete to the best of my knowledge and belief.	Approved Until NOV 30, 2014		
ereby certify vision have b	that the rules and regulations of the Oil Conservation een complied with and that the information given above plete to the best of my knowledge and belief.	Approved Until NOV 30, 2014 By Read Deck		

* See Attached COA's

NEW MEXICO OIL CONSERVATION DIVISION DISTRICT 2 OFFICE 811 SOUTH FIRST STREET ARTESIA, NM 88210 (575)748-1283

CONDITIONS OF APPROVAL for FLARING or VENTING GAS

- 1. Venting gas is absolutely not allowed.
- 2. Prior to flaring gas, C-129 must be filed & approved. Blanket approval cannot be given for this operation.
- 3. Flared volumes of gas are to be metered & reported.
- 4. Flares WILL be manned at all times. Brush should be cut down to 1 or 2 inches around flare stack at least a radial distance of 2 times the height of the flare stack.
- 5. Flares WILL NOT be left unattended.
- 6. No flaring operations to be conducted during red-flag days. <u>http://www.gacc.nifc.gov/swcc</u> (go to "Predictive Services" on SWCC website) to check for red flag warnings.
- 7. Follow safe practices for flaring guidelines.
- 8. Permit may be rescinded at any time by NMOCD.
- 9. If well is able to be connected to a gas gathering system, it will be done so as soon as possible.
- 10. Flaring of gas is prohibited. The State Forester grants an exception to the prohibition on open fires for the flaring of natural gas when the following conditions are met. Unless flaring is needed for safety purposes, flaring pursuant to this exception shall not be done on days that are "red flag days" as determined by the National Weather Service or on days when the sustained wind is in excess of 25 miles per hour in the area.
- 1 1.1. The day is not a "red flag day" as determined by the National Weather Service and the sustained wind is not in excess of 25 miles per hour in the area.

- 12.2. The local fire department and county dispatch are notified at least 24 hours in advance of anticipated releases that will result in flaring. If flaring is done by an automated system then the schedule of flaring shall be provided to the local fire department and county dispatch. The area is mowed and maintained at a length not to exceed 4 inches and all other flammable products or debris shall be cleared in the area for a distance of one and one half times the height of the stack.
- 13.3. At least one adult is on site with communications equipment adequate to reach county dispatch and the local fire department in the event of a fire. The individual should also be equipped with a shovel and a water backpack pump or other equipment to deliver water to suppress a fire.
- 14.4. If flaring is to take place at an unmanned facility, then the area around the flare stack is mowed and maintained at a length not to exceed 4 inches and all other flammable products or debris shall be cleared in the area for a distance of three times the height of the stack.

Your initials here R

8/12/ 2014

State of New Mexico Energy, Minerals and Natural Resources Department

Jami Bailey, Division Director

Oil Conservation Division

Susana Martinez Governor

David Martin Cabinet Secretary

Brett F. Woods, Ph.D. Deputy Cabinet Secretary

March 7, 2014

FOR IMMEDIATE RELEASE Contact: Jim Winchester (505)231-8800 E-Mail: jim.winchester@state.nm.us

Notice to Oil and Gas Facilities and Operators Flaring Gas in New Mexico

SANTA FE, NM – The Oil Conservation Division (OCD) encourages all oil and gas facilities with flare stacks and well operators that are flaring gas to upgrade their *Fire Awareness Programs* this year. New Mexico State Forestry reports that 362 fires burned 6,879 acres on state and private land in calendar year 2013.

Forecasts remain dismal this spring with fewer chances for normal precipitation, particularly in southwestern New Mexico and southeastern Arizona. Temperatures are expected to be higher than normal.

Open flames and gas flares should be monitored carefully and oil and gas operators should create a defensible space to help prevent wildfires. Defensible Space is the area around a structure where combustible vegetation that can spread fire has been cleared, reduced or replaced. This space acts as a barrier between a structure and an advancing wildfire.

This means that as a general rule of thumb, the area around staffed flaring facilities should be mowed and maintained at a length not to exceed 4 inches and all other flammable products or debris should be cleared in the area for a distance of at least one and one half times the height of the stack.

If flaring is to take place at an unstaffed facility, then the mowed area around the flare stack should be increased to three times the height of the stack. On "red flag" days local fire departments should be notified prior to the flaring operations.

During the course of the upcoming fire season, it may become necessary for New Mexico State Forestry to issue fire restriction on State and private land. Log on to <u>www.nmforestry.com</u> for updates or to get information on how contact your local State Forestry District office.

For the latest fire weather information please visit USDA Forest Service website: <u>http://gacc.nifc.gov/swcc/predictive/outlooks/monthly/swa_monthly.pdf</u>

###

The Energy, Minerals and Natural Resources Department provides resource protection and renewable energy resource development services to the public and other state agencies.

