

CISF

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill, or to deepen or reentry to a different reservoir  
Use "APPLICATION FOR PERMIT TO DRILL" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☐ Gas Well ☐ Other:

2. Name of Operator

BOB RYMAL  
TOM BROWN, INC. Phone: (915) 682-9944

3. Address and Telephone No.

P. O. Box 10829, Midland, Texas 79702

4. Location of Well (Footage, T, R, M, or Survey Description)

1980' FSL & 1980' FWL  
Section 5, T-20-S, R-29-E

5. Lease Designation and Serial No.

MN0144698

6. If Indian, Allote or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Superior Federal #5

9. API Well No.

30-015-23975

10. Field and Pool, or Exploratory Area

East Burton Flat Field

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

**TYPE OF SUBMISSION**

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

**TYPE OF ACTION**

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Surface Casing/Cementing  
☒ Other: Plug & Abandon

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.

If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.)\*

Note: See attached 3160-5 dated June 8, 2001 for reference.

- 1 MIRU - NUBOP - Lower tubing to td or 4100'
- 2 Circ. Hole w/10# mud
- 3 Spot 30 sxs Class c cement @ 4100-4000' & tag
- 4 Pull casing Est. @ 3265'
- 5 Spot 40 sxs Class c cement @ 50' in & 50' out of stud &
- 6 Spot 35 sxs Class c cement @ 400'-300'
- 7 Spot 35 sxs Class c cement @ 60' to surface
- 8 Rig down - install dry hole marker
- 9 Cut off wellhead & anchors - Level pit
- 10 Move out



RECEIVED  
2001 SEP 12 AM 7 37  
BUREAU OF LAND MGMT.  
CARLSBAD FIELD OFFICE

**APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS AND  
SPECIAL STIPULATIONS ATTACHED**

Signed: Bob Rymal

*Bob Rymal*

Title: MATERIALS SUPERVISOR

Date:

September 7, 2001

Approved:

(Orig. SGD.) ALEXIS C. SWOBODA

Title:

PETROLEUM ENGINEER

Date:

SEP 18 2001

Conditions of approval, if any: