

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SALE PRICE	✓
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	✓

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED RECEIVED

OCT 6 1978

SEP 28 1978

Form C-101
Supersedes (M)
C-102 and C-103
Effective 1-1-65

10. Indicate Type of Lease	State ☒ Fee ☐
11. State Oil & Gas Lease No.	L-6654
12. Unit Department Name	-
13. Name of Lease Owner	State "19" Com.
14. Well No.	2
15. Field and Pool, or Subunit	South Millman (Morrow)
16. County	Eddy

SUNDY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR NOTICES TO WELLS IN THE STATE OF NEW MEXICO TO A DIFFERENT OPERATOR
SEE STATE DEPARTMENT FOR DETAILS ON NOTICES TO WELLS

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Southland Royalty Company

3. Address of Operator
1100 Wall Towers West, Midland, TX 79701

4. Location of Well
UNIT LETTER N 860 FEET FROM THE south LINE AND 2057 FEET FROM
THE west LINE, SECTION 19 TOWNSHIP 19-S RANGE 28-E MAPAL.

5. Elevation (Show whether DF, RT, GR, etc.)
3493' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPER. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☒
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 7 7/8" hole to 11,340' T.D. MW 9.7#, Vis 42, WL 16.
Ran Compensated Neutron/Formation Density w/GR-Caliper and Dual Laterolog w/RXO.
Ran 5 1/2" 17#, 20# N-80, K-55, MN-80 casing, set @ 11,150'.*
Cemented w/235 sx Lite cement w/5# Gilsontite/sk, 1/4# Flocele/sk plus 230 sx
Class "H" cement w/3/4# CFR-2, 5# KCl/sk. P.D. @ 7:40 p.m., 9-16-78.
Top cement by temperature survey @ 8990'.
MOR.
Prep to move in completion unit. Will test 5 1/2" casing with completion unit.

* 5 1/2" casing in hole as follows: (all casing new - electronic inspected)

Top of hole	2467'	5 1/2" 17# MN-80	Buttress
	4338'	5 1/2" 17# K-55	LT&C
	3573'	5 1/2" 17# N-80	LT&C
Btm of hole	772'	5 1/2" 20# N-80	LT&C
	11,150'		

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. Harvey Can TITLE District Engineer DATE 9-22-78
APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE OCT 6 1978
CONDITIONS OF APPROVAL, IF ANY