

30-015-22307

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: BOGLE STATE COM 1	Field: DIAMOND MOUND
Location: 2560' FNL & 660' FEL; SEC 2-T16S-R27E	County: EDDY State: NM
Elevation: 3590' RKB; 3578' GL	Spud Date: 10/22/77 Compl Date: 12/8/77
API#: 30-015-22307 Prepared by: Ronnie Slack	Date: 4/16/14 Rev:

RECOMPLETION SCHEMATIC

17-1/2" hole

13-3/8", 72#, H40, YB BT&C, @ 345'

Cmt'd w/350 Sx + 4 yds redi-mix to surface

11" Hole

8-5/8", 24#, K55, ST&C, @ 1632'

Cmt'd w/675 Sx. TOC @ 130' (temp survey)

Glorieta2,896 - 2,911' 6 spf

2,000 gal 7.5% HCl Acid stimulate

WOLFCAMP6,360 - 6,364' 6 spf

2,000 gal 7.5% HCl Acid stimulate

Perfed 3 sqz holes @ 6490'. Sqzd 1250 sx
cement to surface--(2/14/81)

WOLFCAMP (11/15/06)6,512 - 6,516' 4 spf

swab dry, no gas-11/16/06

11/16/06 Acidize w/1000 gals 15% HCl

TOC @ 6540' (cbl)

PENN (6/22/02)7926' - 7932' 4 SPF7994' - 8003' 4 SPF

6/24/02: acidized w/1500 gals 15% HCl

MORROW (ATOKA) (12/5/77)8438 - 84468578 - 85838600 - 8602

7-7/8" Hole

4-1/2", 11.6#, K55, LTC, 0 - 1571'4-1/2", 10.5#, K55, STC, 1571' - 6164'4-1/2", 11.6#, K55, LTC, 6164' - 8780'

Cmt'd w/730 Sx

1/80: Casing inspection log indicated possible holes
from 4988-4998' and pitting from 4766-5088'. 3 sqz
holes shot at 6490' and 1250 sx cement squeezed
up 4-1/2" annulus to surface.

PBD @ 2,766' (12/29/14)

CIBP @ 2,796', w/35' cmt on top. (12/29/14)

PBD @ 6,288' (12/18/14)

CIBP @ 6,320', w/35' cmt on top. (12/18/14)

PBD @ 6,440' (5/21/10)

CIBP @ 6,475', w/35' cmt on top. (5/21/10)

PBD @ 7,865' (5/20/10)

CIBP @ 7,900', w/35' cmt on top. (5/20/10)

35' Cement. PBD @ 8365'

CIBP @ 8400' (6/21/02)

PBD @ 8714'

8780' TD

NM OIL CONSERVATION
ARTESIA DISTRICT

FEB 04 2015

RECEIVED