

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised August 1, 2011

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-015-42934
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-7377
7. Lease Name or Unit Agreement Name Skeen 21 B2CN State
8. Well Number 1H.
9. OGRID Number 14744
10. Pool name or Wildcat Hay Hollow; Bone Spring 30215
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3032 GL

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270 Hobbs, NM 88241

4. Well Location
 Unit Letter C : 266 feet from the North line and 2310 feet from the West line
 Section 21 Township 26S Range 28E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE

OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/04/15..MI & spud 17 1/2" hole. TD'd hole @ 503'. Ran 503' of 13 3/8" 48# J55 ST&C csg. Cemented with 550 sks Class C w/2% CaCl2. Mixed @ 14.8/g w/ 1.34 yd. Plug down @ 1:30 AM 03/05/15. Circ 80 sks cement to pit. WOC 18 hrs. At 9:30 PM 03/05/15, tested csg & BOPE to 1250# for 30 minutes, held OK. Drilled out with 12 1/4" bit.

Spud Date: 03/04/2015

Rig Release Date:

NM OIL CONSERVATION
 ARTESIA DISTRICT

MAR 16 2015

RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 03/10/15

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: ADade TITLE Dist. P. Supervisor DATE 3/18/15

Conditions of Approval (if any):