

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

S

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-32002

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-3850

7. Lease Name or Unit Agreement Name:

Lucy ALC State

8. Well No.

6

9. Pool name or Wildcat

Undesignated Lost Tank

Delaware West

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter A : 660 feet from the North line and 330 feet from the East line

Section 34 Township 21S Range 31E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3497' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Completion operations ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

5/9/03 - Perforate Basal Brushy Canyon 7770'-7780' (11), 7880'-7888' (9), 8038'-8046' (9).

5/10/03 - Frac Basal Brushy Canyon 7770'-8046' with Spearhead with 2000g 15% IC/HCL acid. Pumped 47,000# 20/40 Ottawa sand, 79,000# 20/40 Super LC.

5/13/03 - Perforate Basal Brushy Canyon 6976'-6984' (9), Livingston Ridge 6826'-6840' (15). Straddle perms 6976'-6984' and acidize with 1000g 7-1/2% IC/HCL with 18 ball sealers.

5/14/03 - Straddle perms 6826'-6840' and acidize with 1500g 7-1/2% IC/HCL with 30 ball sealers.

5/16-18/03 - Frac perms 6826'-6984' with 47,000# 20/40 Ottawa sand and 79,000# 20/40 Super LC.

5/20/03 - Perforate Cherry Canyon 6508'-6512' (5), 6550'-6552' (3), 6584'-6594' (11) for a total of 19 holes. Frac Cherry Canyon with Spearhead with 1000g 7-1/2% IC/HCL and 45,000# 20/40 Ottawa sand and 55,000# 16/30 Super LC.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jana Huerta TITLE Regulatory Compliance Supervisor DATE May 23, 2003

Type or print name Jana Huerta

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY Don W. Burns TITLE District Supervisor

DATE JUN 02 2003

Conditions of approval, if any: