Form C-103 State of New Mexico Submit 3 Copies To Appropriate District Office Energy, Minerals and Natural Resources Revised May 08, 2003 District I WELL API NO. 1625 N. French Dr., Hobbs, NM 87240 30-015-34249 District II OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease 1220 South St. Francis Dr. District III STATE X FEE \square 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV 6. State Oil & Gas Lease No. 1220 S. St. Francis Dr., Santa Fe, NM 87505 34967 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH 1625 State Com PROPOSALS.) 8. Well Number 1. Type of Well: Oil Well Gas Well X **BECEIVED** Other 281 2. Name of Operator 9. OGRID Number DEC _ 7 2005 LCX Energy, LLC 218885 CCUMPTESIA 3. Address of Operator 10. Pool name or Wildcat 110 N. Marienfeld, Ste. 200, Midland, TX 79701 Cottonwood Creek-Wolfcamp 4. Well Location 660 North 760 feet from the West feet from the Unit Letter line and line 28 Section Township 16S Range 25E NMPM County Eddy 11. Elevation (Show whether DR, RKB, RT. GR. etc.) 3546' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. X **PLUG AND ABANDONMENT** CASING TEST AND PULL OR ALTER CASING ... MULTIPLE \mathbf{x} COMPLETION **CEMENT JOB** OTHER: OTHER: Amended 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 11/24/05 Spud well @ 11:00 pm w/ 17 1/2" hole. Ran 9 jts 13 3/8" 48# H-40 ST&C casing. Casing set at 387'. Cemented casing as follows: Pump 10 bbls FW spacer, 490 sx of Class "C" cement with 2% CaCl2 & .25#/sk celloflake. Displaced with 55 bbls of FW. Bumped plug to 350' & float held. Circulated 41 sx to reserve pit. Heat & weld 13 3/8" wellhead. Test good to 500 psi for 30 mins. NU BOP trip in hole test casing to 500 psi for 30 mins. WOC time total 34 1/2 hrs. I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE Regulatory Analyst DATE 12/06/2005 SIGNATURE

FOR RECORDS ONLY TITLE

Telephone No. 432 687-1575

DEC 0 8 2005

Ext 296

Conditions of approval, if any:

(This space for State use)

APPROVED BY

Type or print name Sharon Hindman